

Unica Interact V12.1.2 Rest API



Contents

Chapter 1. Rest API Guide.....	1
Authentication.....	1
Interact Design time.....	1
Interact Run time.....	2
Errors.....	2
Pagination.....	3
Abbreviations.....	4
Unica Interact Runtime APIs.....	5
Objects.....	5
API - Sessions.....	6
Offers.....	8
API - Events.....	16
API - Profiles.....	17
API - Audience.....	18
API - Batch Execute.....	20
API - Deployment.....	24
Audit.....	28
API - Event Pattern State.....	31
API - Statistics.....	35
API - Interact Status.....	36
Unica Interact Design time APIs.....	37
Interactive Channel.....	37
API – Zone and Interaction Point wrapper.....	46

Category.....	52
Event.....	57
Event Pattern.....	66
Strategy.....	81
Smart Rule.....	87
Strategy Deployment.....	97
Smart Rule Group.....	101
FlexOffers.....	106
FlexOffers Rules.....	116
FlexOffers Filters.....	125
FlexOffers Deployment.....	132
Triggered Action.....	135
Gateway Groups (Outbound Channel).....	150
Gateway.....	156
Interactive Channel Depolymment.....	164
Interactive Flowchart Process Box.....	165
Interactive Flowchart.....	171

Chapter 1. Rest API Guide

This contains information about Rest API for Unica Interact Runtime and Unica Interact Design Time. Interact API has predictable resource-oriented URLs. It accepts form-encoded request bodies, returns JSON-encoded responses, and uses standard HTTP response codes, authentication, and verbs.

Authentication

This section describes the authentication mechanism.

Interact Design time

To authenticate internal users in client applications, use the Unica Platform login API to generate secure tokens. You can then invoke any protected APIs by passing the required parameters in the request header, in addition to the parameters expected by the API itself.

Example

POST /unica/api/manager/authentication/login/

Name	Type	In	Description
m_user_name	string	header	The internal user's Unica Platform login name.
m_user_password	string	header	The internal user's Unica Platform password in plain text.

Response

```
{
  "m_tokenId": "<randomly generated token>",
  "m_user_name": "<username of the logged in user>",
  "createDate": "Mon Jan 01 12:34:56 IST 2021"
}
```

Interact Run time

To enable authentication on Unica Interact Run time API calls, specify the API Authentication (`Affinium|interact|general|API`) property to `true`. When it is enabled, Unica Interact Run time checks if an incoming API request has a valid authentication token, else it authenticates with the supplied username and password with Unica Platform or LDAP. Request is rejected if token is invalid or username or password is invalid. The token is tied with the session-Id, which is provided during the `startSession()` API call. So, all other API calls validate this token before proceeding.

Name	Type	In	Description
m_user_name	string	header	The internal user's Unica Platform login name.
m_user_password	string	header	The internal user's Unica Platform password in plain text.

Errors

Interact uses conventional HTTP response codes to indicate the success or failure of an API request. In general, codes in the 2xx range indicate success. Codes in the 4xx range indicate an error that failed on the basis of the information provided. Codes in the 5xx range indicate an error with Interact servers (these are rare).

HTTP STATUS CODE SUMMARY

200 - OK	Everything worked as expected.
201 - Created	Resource is created.
202 - Accepted	Resource is updated.

204 - No Content	Everything worked as expected.
207 - Miscellaneous	Status code of batch request.
400 - Bad Request	The request was unacceptable, often due to missing a required parameter or invalid input to the parameter.
401 - Unauthorized	No valid API token or credentials provided.
404 - Not Found	The requested resource does not exist.
500 - Server Errors	Something went wrong on Interact server's end. (This is rare.)

Pagination

Requests that return multiple items are paginated to 10 items by default. You can specify further pages with the page parameter.

Name	Type	In	Description
page	number	query	nth page to retrieve records. Default is 0 (first page).
size	number	query	Number of records per page. Default is 10.

Example

```
GET /Campaign/api/interact/rest/v2/channels?page=0&size=10
```

Response

```
{
  "content": [],
```

```
"page": {  
  "hasNext": true,  
  "hasPrev": true,  
  "pageNumber": 0,  
  "size": 10,  
  "totalElements": 0,  
  "totalPages": 0  
}  
}
```

Abbreviations

Abbreviations include acronyms, initialisms, shortened words, and contractions used in this document.

Abbrevia- tions	Description
DT	Design time
RT	Run time
CRUD	Create, Read, Update, and Delete
ic	Interactive Channel
al	Audience Level
ald	Audience Id

The following are the abbreviations and symbols used in Objects section.

Abbrevia- tions	Description
Cr	Create

Up	Update
Cp	Copy
✓	Mandatory Parameter
x	Unexpected Parameter
<blank>	Optional Parameter

Unica Interact Runtime APIs

The following section includes the Rest APIs for Unica Interact Runtime.

Objects

Parameter Object. See the [Abbreviations \(on page 4\)](#) topic for details on the abbreviations used.

Attribute Name	Type	Description
n	string	Parameter name
t	string	Parameter type • string • numeric • datetime
v	object	Parameter value This can either be string or numeric or datetime object.

Parameter

```
{
  "n": "string",
  "t": "string",
  "v": "string"
}
```

Sessions

These APIs are used to start or end the Interact Runtime session.

Start Session

POST /interact/v2/sessions/{sessionID}?

ic={ic}&audienceLevel={al}&audienceIDField={ald}

Parameters

Name	Type	In	Description
sessionID	string	path	Interact Run time Session ID
ic	string	query	Interactive Channel Name
audienceLevel	string	query	Audience Level
audienceID-Field	string	query	Audience ID Format: Name Value Type;Name2 Value2 Type2 Type: • string • numeric • datetime Example: AudienceID 1 numeric

REQUEST

See the [Abbreviations \(on page 4\)](#) topic for the abbreviations used here.

```
{
  "auIdParams": [
    {
      "n": "string",
      "t": "string",
      "v": ""
    }
  ],
  "debug": true,
  "parameters": [
    {
      "n": "string",
      "t": "string",
      "v": ""
    }
  ],
  "relyOnExistingSession": true
}
```

RESPONSE (Status Code: 201)

```
{
  "messages": [],
  "sessionId": "101",
  "version": "1.0.0",
  "statusCode": 0
}
```

End Session

DELETE/interact/v2/sessions/{sessionID}

Parameters

Name	Type	In	Description
sessionID	string	Path	Interact Run time Session ID
parameters	string	Query	Parameters Format: Name Value Type;Name2 Value2 Type2 Type: • string • numeric • datetime Example: UACICachedOffers 1 numeric

RESPONSE (Status Code: 200)

```
{
  "messages": null,
  "sessionId": "101",
  "version": "1.0.0",
  "statusCode": 0
}
```

Offers

These APIs are used to get the offers from the started Interact runtime session.

Get Offers

GET/interact/v2/offers/{sessionID}/{interactionPointID}?

number={numberRequested}

Parameters

Name	Type	In	Description
sessionID	string	path	Interact Run time Session ID
IPID	string	query	Interaction Point ID
number	string	query	Number of offers requested
parameters	string	query	Parameters Format: Name Value Type;Name2 Value2 Type2 Type: • string • numeric • datetime Example: UACICachedOffers 1 numeric

RESPONSE (Status Code: 200)

See the [Abbreviations \(on page 4\)](#) topic for the abbreviations used here.

```
{
  "messages": null,
  "offerLists": [
    {
      "defaultString": "string",
      "ip": "string",
      "offers": [
```

```

    {
      "attributes": [
        {
          "n": "string",
          "t": "string",
          "v": "string"
        }
      ],
      "code": [
        "string"
      ],
      "desc": "string",
      "n": "string",
      "score": 0,
      "treatmentCode": "string"
    }
  ]
}
],
"sessionId": "string",
"statusCode": 0,
"version": "string"
}

```

Get Offers for Multiple IPs

POST/interact/v2/offers/{sessionId}

Parameters

Name	Type	In	Description
sessionId	string	path	Interact Run time Session ID

REQUEST

```
{
  "getOfferRequests": [
    {
      "dupPolicy": 0,
      "ip": "string",
      "numberRequested": 0,
      "offerAttributes": {
        "attributes": [
          {
            "n": "string",
            "t": "string",
            "v": {}
          }
        ],
        "childRequirements": [
          {
            "attributes": [
              {
                "n": "string",
                "t": "string",
                "v": {}
              }
            ],
            "childRequirements": [
              {}
            ],
            "numberRequested": 0
          }
        ],
        "numberRequested": 0
      }
    ]
  ],
  "numberRequested": 0
}
```

```

    }
  ],
  "parameters": [
    {
      "n": "string",
      "t": "string",
      "v": {}
    }
  ]
}

```

RESPONSE (Status Code: 200)

```

{
  "messages": null,
  "offerLists": [
    {
      "defaultString": "string",
      "ip": "string",
      "offers": [
        {
          "attributes": [
            {
              "n": "string",
              "t": "string",
              "v": "string"
            }
          ],
          "code": [
            "string"
          ],
          "desc": "string",
          "n": "string",

```

```

        "score": 0,
        "treatmentCode": "string"
      }
    ]
  }
],
"sessionId": "string",
"statusCode": 0,
"version": "string"
}

```

Get Offers for Multiple IPs

POST/interact/v2/offers/{sessionId}

Parameters

Name	Type	In	Description
sessionId	string	path	Interact Run time Session ID

REQUEST

```

{
  "getOfferRequests": [
    {
      "dupPolicy": 0,
      "ip": "string",
      "numberRequested": 0,
      "offerAttributes": {
        "attributes": [
          {
            "n": "string",

```

```

        "t": "string",
        "v": {}
    }
],
"childRequirements": [
    {
        "attributes": [
            {
                "n": "string",
                "t": "string",
                "v": {}
            }
        ],
        "childRequirements": [
            {}
        ],
        "numberRequested": 0
    }
],
"numberRequested": 0
}
}
],
"parameters": [
    {
        "n": "string",
        "t": "string",
        "v": {}
    }
]
}

```

RESPONSE (Status Code: 200)

See the [Abbreviations \(on page 4\)](#) topic for the abbreviations used here.

```
{
  "messages": null,
  "offerLists": [
    {
      "defaultString": "string",
      "ip": "string",
      "offers": [
        {
          "attributes": [
            {
              "n": "string",
              "t": "string",
              "v": "string"
            }
          ],
          "code": [
            "string"
          ],
          "desc": "string",
          "n": "string",
          "score": 0,
          "treatmentCode": "string"
        }
      ]
    }
  ],
  "sessionId": "string",
  "statusCode": 0,
  "version": "string"
}
```

Events

These APIs are used to post the event to the started Interact Runtime session.

Post Event

POST/interact/v2/events/{sessionId}/{eventName}

Parameters

Name	Type	In	Description
sessionId	string	path	Interact Run time Session ID
event-Name	string	path	Event Name

REQUEST

See the [Abbreviations \(on page 4\)](#) topic for the abbreviations used here.

```
{
  "parameters": [
    {
      "n": "string",
      "t": "string",
      "v": "string"
    }
  ]
}
```

RESPONSE Status Code: 200)

```
{
  "messages": null,
  "sessionId": "101",
```

```
"version": "1.0.0",
"statusCode": 0
}
```

Profiles

These APIs are used to get the profile data from started Interact Runtime Session.

Get Profiles

GET/interact/v2/profiles/{sessionID}

Parameters

Name	Type	In	Description
sessionID	string	path	Interact Run time Session ID
parameters	string	query	Parameters Format: Name Value Type;Name2 Value2 Type2 Type • string • numeric • datetime Example: UACIGetProfileShowDimFields 1 numeric

RESPONSE (Status Code: 200)

See the [Abbreviations \(on page 4\)](#) topic for the abbreviations used here.

```
{
  "messages": null,
  "profile": [
    {
      "n": "string",
      "t": "string",
      "v": "string"
    }
  ],
  "sessionId": "string",
  "statusCode": 0,
  "version": "string"
}
```

Audience

These APIs are used to set the audience data to the existing Interact runtime session.

Set Audience

Set Audience

PUT /interact/v2/audience/{sessionId}?
audienceLevel={al}&audienceIDField={ald}

Parameters

Name	Type	In	Description
sessionId	string	path	Interact Run time Session ID
audienceLevel	string	query	Audience Level

audienceID-Field	string	query	Audience ID Format: Name Value Type;Name2 Value2 Type2 Type • string • numeric • datetime Example: AudienceID 1 numeric
------------------	--------	-------	---

REQUEST

See the [Abbreviations \(on page 4\)](#) topic for the abbreviations used here.

```
{
  "parameters": [
    {
      "t": "string",
      "v": "string",
      "n": "string"
    }
  ]
}
```

RESPONSE (Status Code: 200)

```
{
  "statusCode": 0,
  "sessionId": "101",
  "messages": null,
  "version": "1.0.0"
}
```

Batch Execute

These APIs are used to execute batch commands.

POST /v2/batch/{sessionID}

Parameters

Name	Type	In	Description
sessionID	string	path	Interact Run time Session ID

REQUEST

See the [Abbreviations \(on page 4\)](#) topic for the abbreviations used here.

```
{
  "endSession": true,
  "getOffers": {
    "interactionPointID": "string",
    "numberRequested": 0
  },
  "getOffersForMultipleInteractionPoints": {
    "getOfferRequests": [
      {
        "dupPolicy": 0,
        "ip": "string",
        "numberRequested": 0,
        "offerAttributes": {
          "attributes": [
            {
              "n": "string",
              "t": "string",
              "v": {}
            }
          ]
        }
      }
    ]
  }
}
```

```

        }
      ],
      "childRequirements": [
        {}
      ],
      "numberRequested": 0
    }
  }
]
},
"getProfile": true,
"getVersion": true,
"postEvent": {
  "event": "string",
  "parameters": [
    {
      "n": "string",
      "t": "string",
      "v": {}
    }
  ]
},
"setAudience": {
  "audienceID": [
    {
      "n": "string",
      "t": "string",
      "v": {}
    }
  ]
},
"audienceLevel": "string",
"parameters": [

```

```

        {
            "n": "string",
            "t": "string",
            "v": {}
        }
    ]
},
"setDebug": {
    "debug": true
},
"startSession": {
    "auIdParams": [
        {
            "n": "string",
            "t": "string",
            "v": {}
        }
    ],
    "audienceID": [
        {
            "n": "string",
            "t": "string",
            "v": {}
        }
    ],
    "audienceLevel": "string",
    "debug": true,
    "ic": "string",
    "parameters": [
        {
            "n": "string",
            "t": "string",

```

```

        "v": {}
    }
],
    "relyOnExistingSession": true
}
}

```

RESPONSE (Status Code: 200)

```

{
    "batchStatusCode": 0,
    "responses": [
        {
            "messages": [
                {
                    "detailMsg": "string",
                    "msg": "string",
                    "msgCode": 0,
                    "msgLevel": 0
                }
            ],
            "offerLists": [
                {
                    "defaultString": "string",
                    "ip": "string",
                    "offers": [
                        {
                            "attributes": [
                                {
                                    "n": "string",
                                    "t": "string",
                                    "v": {}
                                }
                            ]
                        }
                    ]
                }
            ]
        }
    ]
}

```

```

        ],
        "code": [
            "string"
        ],
        "desc": "string",
        "n": "string",
        "score": 0,
        "treatmentCode": "string"
    }
]
}
],
"profile": [
    {
        "n": "string",
        "t": "string",
        "v": {}
    }
],
"sessionId": "string",
"statusCode": 0,
"version": "string"
}
]
}

```

Deployment

These APIs are used to get the deployment information of interactive channels.

Get Deployed Channel

GET/interact/v2/deployments/channels/{icldOrName}

Parameters

Name	Type	In	Description
icldOrName	string	path	Interact Channel ID or Name

RESPONSE (Status Code: 200)

See the [Abbreviations \(on page 4\)](#) topic for the abbreviations used here.

```
{
  "deployment": {
    "categoriesAndEvents": [
      {
        "categoryName": "string",
        "events": [
          {
            "eventActions": "string",
            "eventName": "string"
          }
        ]
      }
    ],
    "constraints": [
      {
        "constraintId": 0,
        "constraintName": "string",
        "offerConstraint": "string"
      }
    ],
    "flowcharts": [
      {
```

```

        "audienceLevel": "string",
        "flowchartName": "string"
    }
],
    "icName": "string",
    "lastDeploymentTime": "string",
    "offerThreshold": 0,
    "strategies": [
        {
            "ruleGroups": [
                {
                    "cellCode": "string",
                    "rules": [
                        {
                            "marketWeight": 0,
                            "offerAttributes": [
                                "string"
                            ],
                            "offerCodes": "string",
                            "offerName": "string",
                            "predicate": "string",
                            "predicateState": "string",
                            "ruleEnabled": "string",
                            "zoneName": "string"
                        }
                    ]
                }
            ]
        }
    ],
    "stratergyName": "string"
}
],
"tableMapping": [

```

```

{
  "audienceLevel": "string",
  "tableInfo": [
    {
      "parentTableName": "string",
      "preLoaded": true,
      "tableName": "string"
    }
  ]
},
"zonesAndInteractionPoints": [
  {
    "interactionPoints": [
      "string"
    ],
    "zoneName": "string"
  }
]
}

```

Get Deployed Offers

GET/interact/v2/deployments/offers

RESPONSE (STATUS CODE: 200)

```

{
  "offers": [
    {
      "constraintIds": [
        0
      ],
    },
  ],
}

```

```

    "offerCode": [
      "string"
    ],
    "offerId": 0,
    "offerName": "offer",
    "suppressionRules": {
      "categoryName": "string",
      "eventType": "string",
      "hidden": true,
      "id": 0,
      "name": "string"
    }
  }
]
}

```

Audit

Description

These APIs are used to get runtime API history.

Get API Audit by Session ID

GET/interact/v2/APIhistory/session/{sessionID}?

audiencelevel={audienceLevel} &startTime={startTime}&endTime={endTime}

Parameters

Name	Type	In	Description
sessionID	string	path	Interact Run time Session ID
audienceLevel	string	query	Audience Level

startTime	number	query	Start time in millisecond (optional) Example: 1609439400000
endTime	number	query	End time in millisecond (optional) Example: 1609439400000

RESPONSE (Status Code: 200)

```
{
  "api": "string",
  "apiTime": "2021-01-01T12:34:56.789Z",
  "audienceId": {},
  "batchId": "string",
  "event": "string",
  "intChannel": "string",
  "intPoint": "string",
  "message": "string",
  "noOfofferRequested": 0,
  "offerRequest": "string",
  "parameters": "string",
  "parametersCount": 0,
  "processTime": 0,
  "relyOnExistingSession": 0,
  "response": "string",
  "rtURL": "string",
  "sessionId": "string",
  "status": 0
}
```

Get API Audit by Audience ID

GET/interact/v2/APIhistory/audience?

audienceLevel={audienceLevel}&audienceIDField=

{audienceIDField}&startTime={startTime}&endTime={endTime}&offerArbitration=false

Parameters

Name	Type	In	Description
audienceLevel	string	query	Audience Level
audienceID-Field	string	query	Audience ID
startTime	number	query	Start time in Millis (Optional)
endTime	number	query	End time in Millis (Optional)
offerArbitration	bool	query	Offer Arbitration information flag (Optional)

RESPONSE (Status Code: 200)

```
{
  "api": "string",
  "apiTime": "2021-01-01T12:34:56.789Z",
  "audienceId": {},
  "batchId": "string",
  "event": "string",
  "intChannel": "string",
  "intPoint": "string",
  "message": "string",
  "noOfferRequested": 0,
  "offerRequest": "string",
  "parameters": "string",
  "parametersCount": 0,
```

```

    "processTime": 0,
    "relyOnExistingSession": 0,
    "response": "string",
    "rtURL": "string",
    "sessionId": "string",
    "status": 0
  }

```

Event Pattern State

These APIs are used to get the states of all event patterns and offer suppression rules belonging to the specified audience ID.

Get Event Pattern State

This API will return event pattern state from database and cache.

GET /interact/v2/eventpatterns?audienceLevel={al}&audienceIDField={ald}

Parameters

Name	Type	In	Description
audienceLevel	string	query	Audience Level
audienceIDField	string	query	Audience ID

RESPONSE (Status Code: 200)

```

{
  "lastUpdateTime": 0,
  "patternStates": [
    {
      "offerId": "string",
      "offerName": "string",

```

```

    "patternId": 0,
    "patternName": "string",
    "suppression": "string",
    "values": [
      {
        "activationTime": 0,
        "attrArray": {},
        "changed": true,
        "eventCounterDeltas": [
          0
        ],
        "initialEventCounters": [
          0
        ],
        "lastResetTime": 0,
        "lastUpdateTime": 0,
        "status": "string"
      }
    ]
  }
]
}

```

Get Event Pattern State from Cache

GET/interact/v2/eventpatterns/cache?

audienceLevel={audienceLevel}&audienceIDField={audienceIDFieldValue}

Parameters

Name	Type	In	Description
audienceLevel	string	query	Audience Level

audienceIDField	string	query	Audience ID
-----------------	--------	-------	-------------

RESPONSE (Status Code: 200)

```
{
  "lastUpdateTime": 0,
  "patternStates": [
    {
      "offerId": "string",
      "offerName": "string",
      "patternId": 0,
      "patternName": "string",
      "suppression": "string",
      "values": [
        {
          "activationTime": 0,
          "attrArray": {},
          "changed": true,
          "eventCounterDeltas": [
            0
          ],
          "initialEventCounters": [
            0
          ],
          "lastResetTime": 0,
          "lastUpdateTime": 0,
          "status": "string"
        }
      ]
    }
  ]
}
```

Get Event Pattern State from Database

GET/interact/v2/eventpatterns/db?

audienceLevel={audienceLevel}&audienceIDField={audienceIDFieldValue}

Parameters

Name	Type	In	Description
audienceLevel	string	query	Audience Level
audienceIDField	string	query	Audience ID

RESPONSE (Status Code: 200)

Content-Type: application/json

```
{
  "lastUpdateTime": 0,
  "patternStates": [
    {
      "offerId": "string",
      "offerName": "string",
      "patternId": 0,
      "patternName": "string",
      "suppression": "string",
      "values": [
        {
          "activationTime": 0,
          "attrArray": {},
          "changed": true,
          "eventCounterDeltas": [
            0
          ],

```

```

        "initialEventCounters": [
            0
        ],
        "lastResetTime": 0,
        "lastUpdateTime": 0,
        "status": "string"
    }
]
}
]
}

```

Statistics

These APIs are used to get the JMX sweep.

Get JMX Statistics

GET/interact/v2/stats/jmx

RESPONSE (Status code: 200)

```

{
  "statsJMX": [
    {
      "name": "com.unicacorp.interact:type=api,group=Statistics"
    },
    "information": {
      "WaitForFlowchartAverage": "1.0",
      "LoadScoreOverrideDuration": "0",
      "EndSessionCount": "0",
      "SetAudienceCount": "0",
      "GetProfileAverage": "0.0",
      "PostEventAverage": "0.0",
    }
  ]
}

```

```

        "ActiveSessionCount": "0",
        "PostEventCount": "1",
        "ExecuteBatchAverage": "0.0",
        "ExecuteBatchCount": "0",
        "SetDebugAverage": "0.0",
        "StartSessionAverage": "0.0",
        "GetProfileCount": "0",
        "SetDebugCount": "0",
        "SetAudienceAverage": "0.0",
        "LoadOfferSuppressionDuration": "0",
        "GetOffersCount": "1",
        "LoadOffersBySQLCount": "0",
        "LoadOffersBySQLAverage": "0.0",
        "GetVersionCount": "0",
        "EndSessionAverage": "0.0",
        "StartSessionCount": "0",
        "RunSegmentationDuration": "0",
        "GetVersionAverage": "0.0",
        "GetOffersAverage": "0.0"
    }
}
]
}

```

Interact Status

These APIs are used to check status of Interact.

Get Version

GET/interact/v2/status

RESPONSE (Status Code: 200)

```
{
  "messages": null,
  "sessionId": null,
  "version": "1.0.0"
  "statusCode": 0
}
```

Unica Interact Design time APIs

The following section includes the Rest APIs for Interact Design time objects.

Interactive Channel

These APIs are used to perform CRUD operations on Interactive Channel.

Objects

The Interactive Channel object.

For abbreviations, see the [Abbreviations \(on page 4\)](#) topic.


Attribute Name	Type	Description	Re- quired Cr	Re- quired Up
id	num- ber	Unique id	x	x
name	string	Interactive channel name	✓	
description	string	Description of the interactive channel		
offerThreshold	num- ber	Maximum number of times to show any of- fer during a single visit		

serverGroups	string-array	Runtime server groups	✓	
production-ServerGroup	string	Production runtime server groups	✓	
policyId	number	Security policy id	x	x
createBy	number	Created by user	x	x
createDate	number	Created date in Millis	x	x
updateBy	number	Updated by user	x	x
updateDate	number	Update date in Millis	x	x
waitingForDeployment	number	Number of items waiting for deployment	x	x
longestWaitTime	string	Longest wait time for an item	x	x
longestWaitDateTime	bool	Longest wait time available	x	x
lastDeploymentTime	number	Last Deployment Date in ms	x	x

Interactive Channel Object

For details, see the table in [Objects \(on page 37\)](#) topic.

Interactive Channel <interactive-channel-object>



```

"createBy": 0,
"createDate": 0,
"description": "string",
"id": 0,
"lastDeploymentTime": 0,
"longestWaitTime": "string",
"longestWaitTimeAvailable": true,
"name": "string",
"offerThreshold": 0,
"policyId": 0,
"productionServerGroup": "string",
"serverGroups": [
  "string"
],
"updateBy": 0,
"updateDate": 0,
"waitingForDeployment": 0
}

```

Get All Interactive Channels

GET /Campaign/api/interact/rest/v2/channels

Parameters

Name	Type	In	Description
page	number	query	nth page to retrieve records. Default is 0 (first page).
size	number	query	Number of records per page. Default is 10.

Response (Status Code: 200)

For <interactive-channel-object>, see the [Interactive Channel Object \(on page 38\)](#) topic.

```
{
  "content": [
    <interactive-channel-object>
  ],
  "page": {
    "hasNext": true,
    "hasPrev": true,
    "pageNumber": 0,
    "size": 0,
    "totalElements": 0,
    "totalPages": 0
  }
}
```

Get Interactive Channels

GET /Campaign/api/interact/rest/v2/channels/{icIdOrName}

Parameters

Name	Type	In	Description
icIdOrName	string	path	Interactive Channel id or name

Response (Status Code: 200)

[Interactive Channel Object \(on page 38\)](#)

Create Interactive Channels

POST /Campaign/api/interact/rest/v2/channels

REQUEST

For <interactive-channel-object>, see the [Interactive Channel Object \(on page 38\)](#) topic.

```
{
  "channels": [
    <interactive-channel-object>
  ]
}
```

RESPONSE (Status Code: 207)

```
[
  {
    "headers": {},
    "body": <interactive-channel-object>/<error-msg>,
    "status": 201/400/500
  }
]
```

Update Interactive Channels

PUT /Campaign/api/interact/rest/v2/channels/{icldOrName}

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name

REQUEST

[Interactive Channel Object \(on page 38\)](#)

RESPONSE (Status Code: 202)[Interactive Channel Object \(on page 38\)](#)

Delete Interactive Channels

DELETE /Campaign/api/interact/rest/v2/channels/{icldOrName}

Parameters

Name	Type	In	Description
icldOrName	string	Path	Interactive Channel id or name

RESPONSE (Status Code: 204)

```
no content
```

Get All Audience levels

GET /Campaign/api/interact/rest/v2/channels/{icldOrName}/audiencelevels

Output

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name

RESPONSE (Status Code: 200)

```
{
  "audienceLevels": [
    "audience1"
  ]
}
```

Map Profile Tables

POST /Campaign/api/interact/rest/v2/channels/{icldOrName}/profiletables

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name

REQUEST

```
{
  "audienceLevel": "string",
  "baseKeys": [
    "string"
  ],
  "baseTable": true,
  "dimKeys": [
    "string"
  ],
  "joinTable": "string",
  "joinType": 0,
  "preLoad": true,
  "tableName": "string",
  "unmap": true
}
```

Un-map Table

```
{
  "audienceLevel": "Customer",
  "tableName": "Credit_Details",
  "unmap": true
}
```

```
}
```

RESPONSE - Map Base Table (Status Code: 201)

```
{  
  "audienceLevel": "audience1",  
  "baseTable": true,  
  "tableName": "tableName"  
}
```

RESPONSE - Map Dimension Table (Status Code: 201)

```
{  
  "audienceLevel": "audience1",  
  "baseKeys": [  
    "bkey1"  
  ],  
  "baseTable": false,  
  "dimKeys": [  
    "dkey1"  
  ],  
  "joinTable": "table-name1",  
  "joinType": 1,  
  "preLoad": false,  
  "tableName": "table-name2"  
}
```

RESPONSE - Un-map Base Table (Status Code: 201)

```
{  
  "audienceLevel": "audience1",  
  "tableName": "table-name",  
  "unmap": true  
}
```

```
}

```

Get profile attributes for an audience level

GET /Campaign/api/interact/rest/v2/channels/{icldOrName}/
profileattributes?audienceLevel={ai}

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
audienceLevel	string	query	Name of Audience Level

RESPONSE (Status Code: 200)

```
[
  {
    "Real-time attributes": [
      {
        "attributes": [
          {
            "dataType": 0,
            "name": "string"
          }
        ]
      }
    ]
  },
  {
    "audience1": [
      {

```

```

    "attributes": [
      {
        "dataType": 0,
        "name": "string"
      }
    ],
    "tableName": "string"
  }
]

```

Zone and Interaction Point Wrapper

These APIs are used to perform CRUD operations on zones and interaction points.

Objects

For abbreviations, see the [Abbreviations \(on page 4\)](#) topic.

Attribute Name	Type	Description	Re- quired Cr	Re- quired Up
id	num- ber	Unique id	x	x
name	string	Zone name	✓	
description	string	Description of the zone		
interaction- Points	ar- ray-ob- ject	List of Interaction Point object		

percentRandom	number	Random Percentage		
ruleGroupResolutionType	number	For rule groups in this zone, resolve non-uniform learning rules • 1: Intermix - apply current learning mode • 2: Prioritize non-learning offers • 3: Prioritize learning offers • 4: Prioritize non-learning offers: dedupe • 5: Prioritize learning offers: dedupe		
learningMode	number	Learning mode • 1: Learning mode not set at this level; inherit setting • 2: Use Marketer score • 3: Use Learning score	✓	
learningModelID	number	Learning Model id		

Zone - object

For details, see the [Objects \(on page 46\)](#) topic.

Zone <zone-object>

```
{
  "description": "string",
  "id": 0,
  "interactionPoints": [
    <interaction-points-object>
  ],
}
```

```

"learningMode": 0,
"learningModelID": 0,
"name": "string",
"percentRandom": 0,
"ruleGroupResolutionType": 0
}

```

Interaction Point <interaction-points-object>

```

{
  "defaultString": "string",
  "description": "string",
  "id": 0,
  "name": "string"
}

```

Get All Zones

Get All Zones

GET /Campaign/api/interact/rest/v2/channels/{icIdOrName}/zones

Parameters

Name	Type	In	Description
icIdOr-Name	string	path	Interactive Channel id or name
page	number	query	nth page to retrieve records. Default is 0 (first page).
size	number	query	Number of records per page. Default is 10.

Response (Status Code: 200)

For <zone-object> code, see the [Zone - object \(on page 47\)](#) topic.

```
{
  "content": [
    <zone-object>
  ],
  "page": {
    "hasNext": true,
    "hasPrev": true,
    "pageNumber": 0,
    "size": 0,
    "totalElements": 0,
    "totalPages": 0
  }
}
```

Get Zone

GET /Campaign/api/interact/rest/v2/channels/{icldOrName}/zones/
{zoneldOrName}

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
zoneldOr- Name	string	path	Zone id or name

RESPONSE (Status Code: 200)

[Zone - object \(on page 47\)](#)

Create Zones

POST /Campaign/api/interact/rest/v2/channels/{icldOrName}/zones

Parameters

Name	Type	In	Description
icIdOrName	string	path	Interactive Channel id or name

REQUEST

For <zone-object> code, see the [Zone - object \(on page 47\)](#) topic.

```
{
  "zones": [
    <zone-object>
  ]
}
```

RESPONSE (Status Code: 207)

```
[
  {
    "headers": {},
    "body": <zone-object>/<error-msg>,
    "status": 201/400/500
  }
]
```

Update Zones

PUT /Campaign/api/interact/rest/v2/channels/{icIdOrName}/zones/
{zoneName}

Parameters

Name	Type	In	Description
------	------	----	-------------

icldOrName	string	path	Interactive Channel id or name
zoneldOr- Name	string	path	Zone id or name

REQUEST[Zone - object \(on page 47\)](#)**RESPONSE (Status Code: 202)**[Zone - object \(on page 47\)](#)

Delete a Zone or Interaction Points

DELETE /Campaign/api/interact/rest/v2/channels/{icldOrName}/zones/
{zoneldOrName}

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
zoneldOr- Name	string	path	Zone id or name
onlyIP	bool	query	Flag to delete only interaction points from zone.

RESPONSE (Status Code: 200)

No response.

Delete multiple zones

DELETE /Campaign/api/interact/rest/v2/channels/{icldOrName}/zones

Parameters

Name	Type	In	Description
icIdOrName	string	path	Interactive Channel id or name
ids	string	query	comma separated Zone IDs to be deleted.

RESPONSE (Status Code: 200)

No response.

Category

These APIs are used to perform CRUD operations on categories.

Objects

For abbreviations, see the [Abbreviations \(on page 4\)](#) topic.

Attribute Name	Type	Description	Re- quired Cr	Re- quired Up
id	number	Unique id	x	x
name	string	Zone name	✓	
description	string	Description of the zone		
systemDefined	bool	Indicates system defined category	x	x

Category - Objects

For details, see the [Objects \(on page 52\)](#) topic.

Category<category-object>

```
{
  "description": "string",
  "id": 0,
  "name": "string",
  "systemDefined": true
}
```

Get All Categories

GET /Campaign/api/interact/rest/v2/channels/{icIdOrName}/categories

Name	Type	In	Description
icIdOr-Name	string	path	Interactive Channel id or name
page	number	query	nth page to retrieve records. Default is 0 (first page).
size	number	query	Number of records per page. Default is 10.

RESPONSE (Status Code: 200)

For <category-object>, see the [Category - Objects \(on page 52\)](#) topic.

```
{
  "content": [
    <category-object>
  ],
  "page": {
    "hasNext": true,
    "hasPrev": true,
    "pageNumber": 0,
  }
}
```

```

    "size": 0,
    "totalElements": 0,
    "totalPages": 0
  }
}

```

Get Category

GET /Campaign/api/interact/rest/v2/channels/{icldOrName}/categories/
{categoryIdOrName}

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
zoneldOr- Name	string	path	Zone id or name

RESPONSE (Status Code: 200)

[Category - Objects \(on page 52\)](#)

Create Category

POST /Campaign/api/interact/rest/v2/channels/{icldOrName}/categories

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name

REQUEST

For <category-object>, see the [Category - Objects \(on page 52\)](#) topic.

```
{
  "categories": [
    <category-object>
  ]
}
```

RESPONSE (Status Code: 207)

```
[
  {
    "headers": {},
    "body": <category-object>/<error-msg>,
    "status": 201/400/500
  }
]
```

Update Category

PUT /Campaign/api/interact/rest/v2/channels/{icIdOrName}/categories/
{categoryIdOrName}

Parameters

Name	Type	In	Description
icIdOrName	string	path	Interactive Channel id or name
categoryIdOrName	string	path	Category id or name

REQUEST

[Category - Objects \(on page 52\)](#)

RESPONSE (Status Code: 202)

[Category - Objects \(on page 52\)](#)

Delete Category

DELETE /Campaign/api/interact/rest/v2/channels/{icldOrName}/categories/
{categoryIdOrName}

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
categoryIdOrName	string	path	Category id or name

RESPONSE (Status Code: 200)

No content

Delete Multiple Categories

DELETE /Campaign/api/interact/rest/v2/channels/{icldOrName}/categories

Parameters

Name	Type	In	Description
icldOr- Name	string	path	Interactive Channel id or name
ids	string	query	Comma separated Category IDs to be deleted.

RESPONSE (Status Code: 200)

No content

Event

These APIs are used to perform CRUD operations on Events.

Objects

For abbreviations, see the [Abbreviations \(on page 4\)](#) topic.

Event Object

Attribute Name	Type	Description	Re- quired Cr	Re- quired Up
Id	number	Unique id	x	x
Name	string	Event name	✓	
description	string	Description of the event		
eventType	Number	Event type • 1: Event	✓	
category	object	Category Object		
triggerResegmenta- tion	object	Predefined Event Action Ob- ject		
logOfferContact	object	Predefined Event Action Ob- ject		
logOfferAcceptance	object	Predefined Event Action Ob- ject		
logOfferRejection	object	Predefined Event Action Ob- ject		

executeExpression	object	Predefined Event Action Object		
eventActions	array-object	List of Event Action Object		
expression	object	Event Action Expression Object		
Pattern	object	Not required for Event	x	x
createBy	number	Created by user	x	x
createDate	number	Created date in Millis	x	x
updateBy	number	Updated by user	x	x
updateDate	number	Update date in Millis	x	x

The Predefined Event Action Object

Attribute Name	Type	Description	Re-quired Cr	Re-quired Up
eventActionID	number	Unique id	x	x
enabled	bool	Enable / Disable Event Action	✓	
conditions	array-object	List of Event Action Condition Object		

The Event Action Condition Object

Attribute Name	Type	Description	Re-quired Cr	Re-quired Up
----------------	------	-------------	--------------	--------------

id	number	Unique id	x	x
name	string	Parameter name	✓	✓
value	string	Parameter Value	✓	✓

Event Action Object

Attribute Name	Type	Description	Required Cr	Required Up
eventActionID	number	Unique id	x	✓
actionID	number	Event action type • 6: Event Action Inferred		
actionValue	number	Event action state • 0 • 1		
eventType	number	Event action type id		
isAsync	bool	Async event action		
executionOrder	number	Event action execution order		
details	string	Event action details		

Event Action Expression Object

Attribute Name	Type	Description	Required	Required
----------------	------	-------------	----------	----------

			Cr	Up
audienceLevel	string	Audience Level	✓	✓
expression	string	Expression	✓	✓
fieldName	string	Field Name		

Category Object

Attribute Name	Type	Description	Re-quired Cr	Re-quired Up
id	number	Unique id	✓	
name	string	Zone name	x	x
description	string	Description of the zone	x	x
systemDefined	bool	Indicates system defined category	x	x

Events - object

For details, see the [Objects \(on page 57\)](#) topic.

Event <event-object>

```
"category": <category-object>,
"createBy": 0,
"createDate": 0,
"description": "string",
"eventActions": [
  <event-action-object>
],
```

```

"eventType": 0,
"executeExpression": <predefined-event-action-object>,
"expression": <event-action-expression-object>,
"id": 0,
"logOfferAcceptance": <predefined-event-action-object>,
"logOfferContact": <predefined-event-action-object>,
"logOfferRejection": <predefined-event-action-object>,
"name": "string",
"pattern": null,
"triggerResegmentation": <predefined-event-action-object>,
"updateBy": 0,
"updateDate": 0
}

```

Predefined Event Action <predefined-event-action-object>

```

{
  "conditions": [
    <event-action-condition-object>
  ],
  "enabled": true,
  "eventActionID": 0
}

```

Event Action Condition <event-action-condition-object>

```

{
  "id": 0,
  "name": "string",
  "value": "string"
}

```

Event Action <event-action-object>

```
{
  "actionID": 0,
  "actionValue": 0,
  "async": true,
  "condition": [
    {
      "id": 0,
      "name": "string",
      "value": "string"
    }
  ],
  "details": "string",
  "eventActionID": 0,
  "eventType": 0,
  "executionOrder": 0,
  "inferredEvents": [
    0
  ]
}
```

Event Action Expression <event-action-expression-object>

```
{
  "audienceLevel": "string",
  "expression": "string",
  "fieldName": "string"
}
```

Category <category-object>

```
{
  "description": "string",
  "id": 0,
  "name": "string",
}
```

```
"systemDefined": true
}
```

Get All Events

GET /Campaign/api/interact/rest/v2/channels/{icldOrName}/events

Parameters

Name	Type	In	Description
icldOr-Name	string	path	Interactive Channel id or name
page	number	query	nth page to retrieve records. Default is 0 (first page).
size	number	query	Number of records per page. Default is 10.

RESPONSE (Status Code: 200)

For <event-object>, see the [Events - object \(on page 60\)](#) topic.

```
{
  "content": [
    <event-object>
  ],
  "page": {
    "hasNext": true,
    "hasPrev": true,
    "pageNumber": 0,
    "size": 0,
    "totalElements": 0,
    "totalPages": 0
  }
}
```

```
}
```

Get Event

GET /Campaign/api/interact/rest/v2/channels/{icIdOrName}/events/
{eventIdOrName}

Parameters

Name	Type	In	Description
icIdOrName	string	path	Interactive Channel id or name
eventIdOr- Name	string	path	Event id or name

RESPONSE (Status code: 200)

[Events - object \(on page 60\)](#)

Create Events

Create

POST /Campaign/api/interact/rest/v2/{icIdOrName}/events

Parameters

Name	Type	In	Description
icIdOrName	string	path	Interactive Channel id or name

REQUEST

For <event-object>, see the [Events - object \(on page 60\)](#) topic.

```
{
  "events": [
    <event-object>
  ]
}
```

RESPONSE (Status code: 207)

```
[
  {
    "headers": {},
    "body": <event-object>/<error-msg>,
    "status": 201/400/500
  }
]
```

Update Event

Update

PUT /Campaign/api/interact/rest/v2/channels/{icIdOrName}/events/
{eventIdOrName}

Parameters

Name	Type	In	Description
icIdOrName	string	path	Interactive Channel id or name
eventIdOr- Name	string	path	Event id or name

REQUEST

[Events - object \(on page 60\)](#)

RESPONSE (Status code: 202)

[Events - object \(on page 60\)](#)

Delete Events

DELETE /Campaign/api/interact/rest/v2/channels/{icldOrName}/events/
{eventIdOrName}

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
eventIdOr- Name	string	path	Event id or name

RESPONSE (Status Code: 200)

No Content.

Delete Multiple Events

DELETE /Campaign/api/interact/rest/v2/channels/{icldOrName}/events

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
ids	string	query	Comma separated Event IDs to be deleted.

RESPONSE (Status Code: 200)

No Content.

Event Pattern

These APIs are used to perform CRUD operations on event patterns.

Objects

For abbreviations, see the [Abbreviations \(on page 4\)](#) topic.

Event Pattern Object

Attribute Name	Type	Description	Re- quired Cr	Re- quired Up
Id	number	Unique id	x	x
Name	string	Event name	✓	
description	string	Description of the event		
eventType	Number	Event type • 8: Event Pattern	✓	
category	object	Category Object		
triggerResegmenta- tion	object	Predefined Event Action Ob- ject		
logOfferContact	object	Predefined Event Action Ob- ject		
logOfferAcceptance	object	Predefined Event Action Ob- ject		
logOfferRejection	object	Predefined Event Action Ob- ject		
executeExpression	object	Predefined Event Action Ob- ject		

eventActions	array-object	List of Event Action Object		
expression	object	Event Action Expression Object		
Pattern	object	Not required for Event	x	x
createBy	number	Created by user	x	x
createDate	number	Created date in Millis	x	x
updateBy	number	Updated by user	x	x
updateDate	number	Update date in Millis	x	x

The Predefined Event Action Object

Attribute Name	Type	Description	Re-quired Cr	Re-quired Up
eventActionID	number	Unique id	x	x
enabled	bool	Enable / Disable Event Action	✓	
conditions	array-object	List of Event Action Condition Object		

The Event Action Condition Object

Attribute Name	Type	Description	Re-quired Cr	Re-quired Up
id	number	Unique id	x	x

name	string	Parameter name	✓	✓
value	string	Parameter Value	✓	✓

Event Action Object

Attribute Name	Type	Description	Required Cr	Required Up
eventActionID	number	Unique id	x	✓
actionID	number	Event action type • 6: Event Action Inferred		
actionValue	number	Event action state • 0 • 1		
eventType	number	Event action type id		
isAsync	bool	Async event action		
executionOrder	number	Event action execution order		
details	string	Event action details		

Event Action Expression Object

Attribute Name	Type	Description	Required Cr	Required Up
----------------	------	-------------	-------------	-------------

audienceLevel	string	Audience Level	✓	✓
expression	string	Expression	✓	✓
fieldName	string	Field Name		

Category Object

Attribute Name	Type	Description	Required Cr	Required Up
id	number	Unique id	✓	
name	string	Zone name	x	x
description	string	Description of the zone	x	x
systemDefined	bool	Indicates system defined category	x	x

Pattern Object

Attribute Name	Type	Description	Required Cr	Required Up
type	number	Event pattern type • 1: And • 2: Counter • 3: Score • 4: Time And • 5: Time Counter • 6: Time Score	✓	

		• 7: Rolling And • 8: Rolling Counter • 9: Rolling Score		
enabled	bool	Enable / Disable Event pattern	✓	
async	bool	Async event pattern		
startTime	number	Start time in Millis		
endTime	number	End time in Millis		
timeDuration	number	Time duration		
resetDuration	number	Extend true state		
matchTotal	number	Number of occurrences of the selected event when pattern fires		
itemEvent	array-object	Event Pattern Item Object		
reset	object	Reset Pattern Object		

Event Pattern item Object

Attribute Name	Type	Description	Required Cr	Required Up
id	number	Unique id	✓	
eventId	number	Event id to trigger	✓	

name	string	Pattern item name		
value	number	Pattern item value		
attributes	array-object	Parameter Object		

Parameter Object

Attribute Name	Type	Description	Re-quired Cr	Re-quired Up
id	number	Unique id	û	û
name	string	Parameter name	✓	✓
comparator	string	Comparator		
dataType	number	Data type • 1: String • 2: Numeric • 3: Datetime • 4: Currency	✓	✓
value	string	Parameter value	✓	✓

Reset Pattern Object

Attribute Name	Type	Description	Re-quired Cr	Re-quired Up
id	number	Unique id	x	x

type	number	Reset pattern type • 0: None • 1: Inactivity • 2: Periodic • 3: Event Based	✓	✓
intervalType	string	Interval type • h: Hour • d: Day • w: Week • m: Month		
interval	number	Interval	✓	✓
startTime	number	Start time in ms		
eventId	number	Event id to trigger after re-set		

Event Pattern - object

For details, see the [Objects \(on page 67\)](#) topic.

Event pattern <event-pattern-object>

```
{
  "category": <category-object>,
  "createBy": 0,
  "createDate": 0,
  "description": "string",
  "eventActions": [
    <event-action-object>
  ],
  "eventType": 0,
```

```

"executeExpression": <predefined-event-action-object>,
"expression": <event-action-expression-object>,
"id": 0,
"logOfferAcceptance": <predefined-event-action-object>,
"logOfferContact": <predefined-event-action-object>,
"logOfferRejection": <predefined-event-action-object>,
"name": "string",
"pattern": <pattern-object>,
"triggerResegmentation": <predefined-event-action-object>,
"updateBy": 0,
"updateDate": 0
}

```

Predefined Event Action <predefined-event-action-object>

```

{
  "conditions": [
    <event-action-condition-object>
  ],
  "enabled": true,
  "eventActionID": 0
}

```

Event Action Condition <event-action-condition-object>

```

{
  "id": 0,
  "name": "string",
  "value": "string"
}

```

Event Action <event-action-object>

```
{
  "actionID": 0,
  "actionValue": 0,
  "async": true,
  "condition": [
    <event-action-condition-object>
  ],
  "details": "string",
  "eventActionID": 0,
  "eventType": 0,
  "executionOrder": 0,
  "inferredEvents": [
    0
  ]
}
```

Event Action Expression <event-action-expression-object>

```
{
  "audienceLevel": "string",
  "expression": "string",
  "fieldName": "string"
}
```

Pattern <pattern-object>

```
{
  "async": true,
  "enabled": true,
  "endTime": 0,
  "itemEvent": [
    <event-pattern-item-object>
  ],
  "matchTotal": 0,
```

```
"reset": <reset-pattern-object>,  
"resetDuration": 0,  
"startTime": 0,  
"timeDuration": 0,  
"type": 0  
}
```

Event Pattern Item <event-pattern-item-object>

```
{  
  "attributes": [  
    <parameter-object>  
  ],  
  "eventId": 0,  
  "id": 0,  
  "name": "string",  
  "value": 0  
}
```

Parameter <parameter-object>

```
{  
  "comparator": "string",  
  "dataType": 0,  
  "id": 0,  
  "name": "string",  
  "value": "string"  
}
```

Reset Pattern <reset-pattern-object>

```
{  
  "eventId": 0,  
  "id": 0,  
  "interval": 0,
```

```

"intervalType": "string",
"startTime": 0,
"type": 0
}

```

Category <category-object>

```

{
  "description": "string",
  "id": 0,
  "name": "string",
  "systemDefined": true
}

```

Get All Event Patterns

GET /Campaign/api/interact/rest/v2/channels/{icIdOrName}/eventpatterns

Parameters

Name	Type	In	Description
icIdOr-Name	string	path	Interactive Channel id or name
page	number	query	nth page to retrieve records. Default is 0 (first page).
size	number	query	Number of records per page. Default is 10.

RESPONSE (Status code: 200)

For <event-pattern-object>, see the [Event Pattern - object \(on page 73\)](#) topic.

```
{
  "content": [
    <event-pattern-object>
  ],
  "page": {
    "hasNext": true,
    "hasPrev": true,
    "pageNumber": 0,
    "size": 0,
    "totalElements": 0,
    "totalPages": 0
  }
}
```

Get Event Pattern

Get

GET /Campaign/api/interact/rest/v2/channels/{icIdOrName}/eventpatterns/
{eventpatternsIdOrName}

Parameters

Name	Type	In	Description
icIdOrName	string	path	Interactive Channel id or name
eventIdOr- Name	string	path	Event id or name

RESPONSE (Status code: 200)

[Event Pattern - object \(on page 73\)](#)

Create Event Pattern

POST /Campaign/api/interact/rest/v2/channels/{icldOrName}/eventpatterns

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name

REQUEST

For <event-pattern-object>, see the [Event Pattern - object \(on page 73\)](#) topic.

```
{
  "events": [
    <event-pattern-object>
  ]
}
```

RESPONSE (Status code: 207)

```
[
  {
    "headers": {},
    "body": <event-pattern-object>/<error-msg>,
    "status": 201/400/500
  }
]
```

Update Event Pattern

Update

PUT /Campaign/api/interact/rest/v2/channels/{icldOrName}/eventpatterns/
{evtpatternIdOrName}

Parameters

Name	Type	In	Description
icIdOrName	string	path	Interactive Channel id or name
evtpatternIdOr- Name	string	path	Event pattern id or name

REQUEST

[Event Pattern - object \(on page 73\)](#)

RESPONSE (Status code: 202)

[Event Pattern - object \(on page 73\)](#)

Delete Event Pattern

DELETE /Campaign/api/interact/rest/v2/{icIdOrName}/eventpatterns/
{evtpatternIdOrName}

Parameters

Name	Type	In	Description
icIdOrName	string	path	Interactive Channel id or name
eventIdOr- Name	string	path	Event id or name

RESPONSE (Status code: 200)

No content

Delete Multiple Event Patterns

DELETE /Campaign/api/interact/rest/v2/channels/{icldOrName}/
eventpatterns

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
ids	string	query	comma separated Event IDs to be deleted.

RESPONSE (Status code: 200)

No content

Strategy

Description

These APIs are used to perform CRUD operations on the strategy.

Objects

For abbreviations, see the [Abbreviations \(on page 4\)](#) topic.

Strategy Object

Attribute Name	Type	Description	Re- quired Cr	Re- quired Up	Re- quired Cp
id	num- ber	Unique id	x	x	x
name	string	Strategy name	✓		✓
description	string	Description of the strategy			

campaignId	number	Linked campaign id			
campaignName	string	Linked campaign name	x	x	x
campaignCode	string	Linked campaign code	x	x	x
interactiveChannelId	number	Interactive channel id	x	x	x
interactiveChannelName	string	Interactive channel name	x	x	x
createBy	number	Created by user	x	x	x
createDate	number	Created date in Millis	x	x	x
updateBy	number	Updated by user	x	x	x
updateDate	number	Update date in Millis	x	x	x
ruleCount	number	Rule count in strategy	x	x	x
lastProdDepTime	number	Last production deployment time in Millis	x	x	x

Strategy - object

For details, see the [Objects \(on page 81\)](#) topic.

Strategy <strategy-object>

```
{
  "campaignCode": "string",
  "campaignId": 0,
```

```
"campaignName": "string",
"createBy": "string",
"createDate": 0,
"description": "string",
"id": 0,
"interactiveChannelId": 0,
"interactiveChannelName": "string",
"lastProdDepTime": 0,
"name": "string",
"ruleCount": 0,
"updateBy": "string",
"updateDate": 0
}
```

Get All Strategies

GET /Campaign/api/interact/rest/v2/channels/{icldOrName}/strategies

Request Parameters

Name	Type	In	Description
icldOr-Name	string	path	Interactive Channel id or name
page	number	query	nth page to retrieve records. Default is 0 (first page).
size	number	query	Number of records per page. Default is 10.
mode	string	query	If value is <i>recent</i> , it returns 5 recently updated strategies. (Optional)

Output

Table 1. Response Codes

Success	200	Ok
Error	400	Inputs provided for the API are not valid.
Server Error	500	Internal Server Error. For more details, check the logs.

RESPONSE (Status Code: 200)

For <strategy-object>, see the [Strategy - object \(on page 82\)](#) topic.

```
{
  "content": [
    <strategy-object>
  ],
  "page": {
    "hasNext": true,
    "hasPrev": true,
    "pageNumber": 0,
    "size": 0,
    "totalElements": 0,
    "totalPages": 0
  }
}
```

Get Strategy

GET /Campaign/api/interact/rest/v2/channels/{icldOrName}/strategies/
{strategyIdOrName}

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
strategyIdOr- Name	string	path	Strategy id or name

RESPONSE (Status code: 200)

[Strategy - object \(on page 82\)](#)

Create Strategy

POST /Campaign/api/interact/rest/v2/channels/{icldOrName}/strategies

REQUEST

[Strategy - object \(on page 82\)](#)

RESPONSE (Status code: 201)

[Strategy - object \(on page 82\)](#)

Update Strategy

Update

PUT /Campaign/api/interact/rest/v2/channels/{icldOrName}/strategies/
{strategyIdOrName}

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name

strategyIdOr- Name	string	path	Strategy id or name
-----------------------	--------	------	---------------------

REQUEST

[Strategy - object \(on page 82\)](#)

RESPONSE (Status Code: 202)

[Strategy - object \(on page 82\)](#)

Delete Strategy

DELETE /Campaign/api/interact/rest/v2/channels/{icldOrName}/strategies/
{strategyIdOrName}

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
strategyIdOr- Name	string	path	Strategy id or name

RESPONSE (Status code: 200)

No content

Copy Strategy

POST /Campaign/api/interact/rest/v2/channels/{icldOrName}/strategies/
{strategyIdOrName}

Parameters

Name	Type	In	Description
------	------	----	-------------

icldOrName	string	path	Interactive Channel id or name
------------	--------	------	--------------------------------

REQUEST

[Strategy - object \(on page 82\)](#)

RESPONSE (Status code: 201)

[Strategy - object \(on page 82\)](#)

Smart Rule

These APIs are used to perform CRUD operations on the Smart Rules.

Objects

For abbreviations, see the [Abbreviations \(on page 4\)](#) topic.

Smart Rule Object

Attribute Name	Type	Description	Re- quired Cr	Re- quired Up
id	number	Unique id	✓	✓
ruleName	string	Smart Rule name		
segmentId	number	Segment id		
segmentName	string	Segment name	x	x
cellId	number	Cell id		
cellCode	string	Cell code	x	x
zoneId	number	Zone id		
zoneName	string	Zone name	x	x

offerId	number	Offer id		
offerName	string	Offer name	x	x
offerCode	number	Offer code	x	x
offerType	number	Type of offer • 0: Offer • 1: OfferList		
offerSelection	object	Offer Selection Policy Object		
offerAttrExpressions	array-object	List of Offer Attribute Expression Object		
groupByOfferName	string	Group by offer name		
ruleGroupName	string	Smart rule group name		
ruleGroups	array-object	List of Smart Rule Group Object		
score	number	Score		
scorePredicate	string	Predicate to calculate score		
scorePredicateEnabled	bool	Enable / Disable score predicate		
scorePredicateId	number	Predicate id for score		
enabled	Bool	Enable / Disable smart rule		
eligibilityPredicate	string	Predicate to define eligibility		
eligibilityPredicateEnabled	bool	Enable / Disable eligibility predicate		

eligibilityPredicateId	number	Predicate id for eligibility		
effectiveDate	number	Effective date in Millis		
expirationDate	number	Expiration date in Millis		
learningMode	number	Learning mode • 1: Learning mode not set at this level; inherit setting • 2: Use Marketer score • 3: Use Learning score		
learningModelId	number	Learning model id		
lmName	string	Learning model name		
maxScore	number	Max Score		
suppressCount	number	Suppression count		
hasABTest	bool	Has A/B Test?		
abTest	object	A/B Test Object		

Offer Selection Policy Object

Attribute Name	Type	Description	Required Cr	Required Up
num	number	Number of offers to return from offer list		
opt	number	Allowed offer selection policy		
param	string	Parameter	x	x

sort	string	Sort by	x	x
------	--------	---------	---	---

Offer Attribute Expression Object

Attribute Name	Type	Description	Re- quired Cr	Re- quired Up
attrId	number	Unique id	✓	✓
attrName	string	Attribute name		
expression	string	Expression to calculate value for attribute	✓	✓

Smart Rule Group Object

Attribute Name	Type	Description	Re- quired Cr	Re- quired Up
id	number	Unique id	✓	✓
name	string	Smart rule group name	x	x
description	string	Description of the smart rule group	x	x

A/B test Branch Object

Attribute Name	Type	Description	Re- quired Cr	Re- quired Up
branchId	number	Unique id		
branchName	string	A/B testing branch name		

enabled	bool	Enable / Disable A/B testing branch		
isDefault	bool	Indicates A/B testing default branch		
samplePer-cent	number	Sample percentage for A/B testing branch		
acceptRate	number	Acceptance rate		
selected-Branch	bool	A/B testing branch selection		
cellId	number	Cell id		
cellCode	string	Cell code	x	x
offerId	number	Offer id		
offerName	string	Offer name	x	x
offerAttribut-es	array-ob-ject	List of Offer Attribute Expression Ob-ject		
delete	bool	Delete A/B testing branch flag		

Smart Rule - object

For details, see the [Objects \(on page 87\)](#) topic.

Smart Rule <smart-rule-object>

```
{
  "abTest": <ab-test-object>,
  "cellCode": "string",
  "cellId": 0,
  "effectiveDate": 0,
  "eligibilityPredicate": "string",
  "eligibilityPredicateEnabled": true,
  "eligibilityPredicateId": 0,
  "enabled": true,
```

```

"expirationDate": 0,
"groupByOfferName": "string",
"hasABTest": true,
"id": 0,
"learningMode": 0,
"learningModelId": 0,
"lmName": "string",
"maxScore": true,
"offerAttrExpressions": [
  <offer-attribute-expression-object>
],
"offerCode": "string",
"offerId": 0,
"offerName": "string",
"offerSelection": <offer-selection-policy-object>,
"offerType": 0,
"ruleGroupName": "string",
"ruleGroups": [
  <smart-rule-group-object>
],
"ruleName": "string",
"score": 0,
"scorePredicate": "string",
"scorePredicateEnabled": true,
"scorePredicateId": 0,
"segmentId": 0,
"segmentName": "string",
"suppressCount": 0,
"zoneId": 0,
"zoneName": "string"
}

```

Offer Selection Policy <offer-selection-policy-object>

```
{
  "num": 0,
  "opt": 0,
  "param": "string",
  "sort": "string"
}
```

Offer Attribute Expression <offer-attribute-expression-object>

```
{
  "attrId": 0,
  "attrName": "string",
  "expression": "string"
}
```

A/B Test <ab-test-object>

```
{
  "branches": [
    <ab-test-branch-object>
  ],
  "effectiveDate": 0,
  "enabled": true,
  "expirationDate": 0,
  "readOnly": true,
  "selectionMode": 0,
  "status": "string"
}
```

A/B Test Branch <ab-test-branch-object>

```
{
  "acceptRate": 0,
  "branchId": 0,
  "branchName": "string",
```

```

"cellCode": "string",
"cellId": 0,
"delete": true,
"enabled": true,
"isDefault": true,
"offerAttributes": [
  <offer-attribute-expression-object>
],
"offerId": 0,
"offerName": "string",
"samplePercent": 0,
"selectedBranch": true
}

```

Smart Rule Group <smart-rule-group-object>

```

{
  "description": "string",
  "id": 0,
  "name": "string"
}

```

Get All Smart Rules

GET /Campaign/api/interact/rest/v2/channels/{icIdOrName}/strategies/
{strategyIdOrName}/rules

Parameters

Name	Type	In	Description
icIdOr- Name	string	path	Interactive Channel id or name

strategyId-OrName	string	path	Strategy id or name
page	number	query	nth page to retrieve records. Default is 0 (first page).
size	number	query	Number of records per page. Default is 10.
abtOnly	bool	query	If value is <i>true</i> , it returns smart rules with A/B testing data. (Optional)

RESPONSE (Status Code: 200)

For <smart-rule-object>, see the [Smart Rule - object \(on page 91\)](#) topic.

```
{
  "content": [
    <smart-rule-object>
  ],
  "page": {
    "hasNext": true,
    "hasPrev": true,
    "pageNumber": 0,
    "size": 0,
    "totalElements": 0,
    "totalPages": 0
  }
}
```

Get Smart Rule

GET /Campaign/api/interact/rest/v2/channels/{icldOrName}/strategies/{strategyIdOrName}/rules/{ruleIdOrName}

Parameters

Name	Type	In	Description
icIdOrName	string	path	Interactive Channel id or name
strategyIdOr- Name	string	path	Strategy id or name
ruleIdOrName	string	path	Smart rule id or name

RESPONSE (Status code: 200)

[Smart Rule - object \(on page 91\)](#)

Save Smart Rules

Create, Update, and delete smart rules

POST /Campaign/api/interact/rest/v2/channels/{icIdOrName}/strategies/
{strategyIdOrName}/rules

Parameters

Name	Type	In	Description
icIdOrName	string	path	Interactive Channel id or name
strategyIdOr- Name	string	query	Strategy id or name

REQUEST

For <smart-rule-object>, see the [Smart Rule - object \(on page 91\)](#) topic.

```
{
  "toAdd": [
```

```

    <smart-rule-object>
  ],
  "toDelete": [
    0
  ],
  "toUpdate": [
    <smart-rule-object>
  ]
}

```

RESPONSE (Status Code: 202)

No content.

Delete Smart Rules

DELETE /Campaign/api/interact/rest/v2/channels/{icldOrName}/strategies/
{strategyIdOrName}/rules

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
strategyIdOr- Name	string	path	Strategy id or name
ids	string	query	comma separated Smart rule IDs to be deleted.

RESPONSE (Status Code: 202)

No content.

Strategy Deployment

Description

These APIs are used to perform (un) deploy operations on the strategy.

Objects

For abbreviations, see the [Abbreviations \(on page 4\)](#) topic.

Strategy deployment Object

Attribute Name	Type	Description	Re- quired Cr	Re- quired Up
campaignId	num- ber	Campaign id		
deployAction	string	Deployment action • markDeploy • markUnDeploy • cancelDeploy • cancelUnDeploy	✓	✓
state	num- ber	State • 0: Ready for Deployment • 1: Ready for Undeployment • 2: Mark for Deployment • 3: Mark for Undeployment	x	x
deployedState	num- ber	Deployed state • 10: Not Yet Deployed • 11: Deployed • 12: Undeployed	x	x
dirty	bool	Dirty deployment flag	x	x

lastProdDepTime	date	Last production deployment time	x	x
lastMarkTime	date	Last (un) marked for (un) deployment time	x	x
deploymentStatus-Text	string	Status text	x	x
deploymentWaitMessage	string	Waiting message	x	x

Strategy Deployment - object

For details, see the [Objects \(on page 98\)](#) topic.

Strategy Deployment<strategy-deployment-object>

```
{
  "campaignId": 0,
  "deployAction": "string",
  "deployedState": 0,
  "deploymentStatusText": "string",
  "deploymentWaitMessage": "string",
  "dirty": true,
  "lastMarkTime": "2021-01-01T01:02:03.456Z",
  "lastProdDepTime": "2021-01-01T01:02:03.456Z",
  "state": 0
}
```

Get Deployment State

Get Deployment State

GET /Campaign/api/interact/rest/v2/channels/{icldOrName}/strategies/
{strategyIdOrName}/deployment

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
strategyIdOr- Name	string	path	Strategy id or name

RESPONSE (Status Code: 200)

[Strategy Deployment - object \(on page 99\)](#)

Mark for (Un) Deployment

PUT /Campaign/api/interact/rest/v2/channels/{icldOrName}/strategies/
{strategyIdOrName}/deployment

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
strategyIdOr- Name	string	path	Strategy id or name

REQUEST

[Strategy Deployment - object \(on page 99\)](#)

RESPONSE (Status code: 202)

[Strategy Deployment - object \(on page 99\)](#)

Cancel mark for (Un) Deployment

DELETE /Campaign/api/interact/rest/v2/channels/{icldOrName}/strategies/
{strategyIdOrName}/deployment

Parameters

Name	Type	In	Description
icIdOrName	string	path	Interactive Channel id or name
strategyIdOr- Name	string	path	Strategy id or name

REQUEST

[Strategy Deployment - object \(on page 99\)](#)

RESPONSE (Status Code: 200)

[Strategy Deployment - object \(on page 99\)](#)

Smart Rule Group

These APIs are used to perform CRUD operations on the Smart Rule Group.

Objects

For abbreviations, see the [Abbreviations \(on page 4\)](#) topic.

Smart Rule Group Object

Attribute Name	Type	Description	Re- quired Cr	Re- quired Up
id	number	Unique id	x	
name	string	Smart Rule Group name	✓	
description	string	Description of the Smart Rule Group		

strategyId	number	Strategy id	x	x
createBy	number	Created by user	x	x
createDate	number	Created date in Millis	x	x
updateBy	number	Updated by user	x	x
updateDate	number	Update date in Millis	x	x
ruleIdList	array-number	List of Smart rule ids	x	x

Smart Rule Group - object

For details, see the [Objects \(on page 101\)](#) topic.

Smart Rule Group <smart-rule-group-object>

```
{
  "createBy": 0,
  "createDate": 0,
  "description": "string",
  "id": 0,
  "name": "string",
  "ruleIdList": [
    0
  ],
  "strategyId": 0,
  "updateBy": 0,
  "updateDate": 0
}
```

Get Smart Rule Groups by Strategy

Get Smart Rule Groups by Strategy

GET /Campaign/api/interact/rest/v2/channels/{icldOrName}/strategies/
{strategyIdOrName}/ruleGroups

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
strategyIdOr- Name	string	query	Strategy id or name
page	num- ber	query	nth page to retrieve records. Default is 0 (first page).
size	num- ber	query	Number of records per page. Default is 10.

RESPONSE (Status Code: 200)

For <smart-rule-group-object>, see the [Smart Rule Group - object \(on page 102\)](#) topic.

```
{
  "content": [
    <smart-rule-group-object>
  ],
  "page": {
    "hasNext": true,
    "hasPrev": true,
    "pageNumber": 0,
    "size": 0,
    "totalElements": 0,
    "totalPages": 0
  }
}
```

Get Smart Rule Groups by Smart Rule

GET /Campaign/api/interact/rest/v2/channels/{icldOrName}/strategies/
{strategyIdOrName}/ruleGroups/{ruleIdOrName}

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
strategyIdOr- Name	string	query	Strategy id or name
ruleIdOrName	string	query	Smart rule id or name
page	num- ber	query	nth page to retrieve records. Default is 0 (first page).
size	num- ber	query	Number of records per page. Default is 10.

RESPONSE (Status code: 200)

For <smart-rule-group-object>, see the [Smart Rule Group - object \(on page 102\)](#) topic.

```
{
  "content": [
    <smart-rule-group-object>
  ],
  "page": {
    "hasNext": true,
    "hasPrev": true,
    "pageNumber": 0,
    "size": 0,
    "totalElements": 0,
```

```

    "totalPages": 0
  }
}

```

Create Smart Rule Group

POST /Campaign/api/interact/rest/v2/channels/{icldOrName}/strategies/
{strategyIdOrName}/ruleGroups

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
strategyIdOr- Name	string	query	Strategy id or name

REQUEST

[Smart Rule Group - object \(on page 102\)](#)

RESPONSE (Status Code: 201)

[Smart Rule Group - object \(on page 102\)](#)

Update Smart Rule Group

PUT /Campaign/api/interact/rest/v2/channels/{icldOrName}/strategies/
{strategyIdOrName}/ruleGroups/{ruleGroupIdOrName}

Parameters

Name	Type	In	Description
icldOrName	String	path	Interactive Channel id or name

strategyIdOrName	String	query	Strategy id or name
ruleGroupIdOr- Name	String	query	Smart rule group id or name

REQUEST

[Smart Rule Group - object \(on page 102\)](#)

RESPONSE (Status Code: 202)

[Smart Rule Group - object \(on page 102\)](#)

Delete Smart Rule Group

DELETE /Campaign/api/interact/rest/v2/channels/{icIdOrName}/strategies/
{strategyIdOrName}/ruleGroups/{ruleGroupIdOrName}

Parameters

Name	Type	In	Description
icIdOrName	string	path	Interactive Channel id or name
strategyIdOrName	string	query	Strategy id or name
ruleGroupIdOr- Name	string	query	Smart rule group id or name

RESPONSE (Status Code: 200)

No content.

FlexOffers

These APIs are used to perform CRUD operations on FlexOffers.

Objects

For abbreviations, see the [Abbreviations \(on page 4\)](#) topic.

FlexOffers Object

Attribute Name	Type	Description	Re- quired Cr	Re- quired Up
offerMappingId	number	Unique id	x	x
offerMapping- Name	string	FlexOffers name	✓	
offerMappingDe- sc	string	Description of the FlexOffers		
delimiter	string	Delimiter used to parse csv		
fields	array-ob- ject	List of FlexOffers Attribute Object		
filterfields	array-ob- ject	List of FlexOffers Attribute Object		
override	bool	Override FlexOffers		
physicalTable- Name	string	Database table name		
serverGroups	array-ob- ject	List of FlexOffers Server Group Ob- ject		
sourceFileName	string	Source file name		
sourceSG	string	Source server group name		
lastProdDep- Time	number	Last production deployment time in Millis	x	x
createBy	number	Created by user	x	x

createDate	number	Created date in Millis	x	x
updateBy	number	Updated by user	x	x
updateDate	number	Update date in Millis	x	x

FlexOffers Attribute Object

Attribute Name	Type	Description	Re- quired Cr	Re- quired Up
name	string	Attribute name	✓	
displayName	string	Display name for attribute		
dynamic	bool	Is attribute dynamic?		
relation	string	Relational operator • EQUAL • GREATER • GREATEREQUAL • LESS • LESSSQUEAL • NOTEQUAL • STARTSWITH • ENDSWITH • CONTAINS		
size	number	Size		
type	string	Data type • STRING • LONG	✓	

		• BIT • INTEGER • DATE • FLOAT		
dateFormat	string	Date format		
value	object	Attribute Value		

FlexOffers Server Group Object

Attribute Name	Type	Description	Re- quired Cr	Re- quired Up
name	string	Server group name	✓	
table	string	Table name specific to Server Group	✓	

FlexOffers - object

For details, see the [Objects \(on page 106\)](#) topic.

FlexOffers <flexoffers-object>

```
{
  "createBy": 0,
  "createDate": "2021-05-19T08:10:33.308Z",
  "delimiter": "string",
  "fields": [
    <flex-offer-attribute-object>
  ],
  "filterfields": [
    <flex-offer-attribute-object>
  ],
}
```

```

    "lastProdDepTime": "2021-05-19T08:10:33.308Z",
    "offerMappingId": 0,
    "offerMappingDesc": "string",
    "offerMappingName": "string",
    "override": true,
    "physicalTableName": "string",
    "serverGroups": [
        <flex-offer--server-group-object>
    ],
    "sourceFileName": "string",
    "sourceSG": "string",
    "updateBy": 0,
    "updateDate": "2021-05-19T08:10:33.309Z"
}

```

FlexOffers Attribute <flex-offer-attribute-object>

```

{
    "dateFormat": "string",
    "displayName": "string",
    "dynamic": true,
    "name": "string",
    "relation": "string",
    "size": 0,
    "type": "string",
    "value": {}
}

```

FlexOffers Server Group <flex-offer--server-group-object>

```

{
    "name": "string",
    "table": "string"
}

```

Get All FlexOffers

GET /Campaign/api/interact/rest/v2/channels/{icldOrName}/flexoffers

Parameters

Name	Type	In	Description
icldOr-Name	string	path	Interactive Channel id or name
page	number	query	nth page to retrieve records. Default is 0 (first page).
size	number	query	Number of records per page. Default is 10.

RESPONSE (Status code: 200)

For <flex-offer-object>, see the [FlexOffers - object \(on page 109\)](#) topic.

```
{
  "content": [
    <flex-offer-object>
  ],
  "page": {
    "hasNext": true,
    "hasPrev": true,
    "pageNumber": 0,
    "size": 0,
    "totalElements": 0,
    "totalPages": 0
  }
}
```

Get FlexOffers

GET /Campaign/api/interact/rest/v2/channels/{icldOrName}/flexoffers/
{flexofferIdOrName}

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
flexofferIdOr- Name	string	path	Flex Offer id or name

RESPONSE (Status code: 200)

[FlexOffers](#) - object ([on page 109](#)) topic.

Create FlexOffers

POST /Campaign/api/interact/rest/v2/channels/{icldOrName}/flexoffers

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name

RESPONSE (Status code: 201)

[FlexOffers](#) - object ([on page 109](#)).

Create FlexOffers from Imported Csv

POST /Campaign/api/interact/rest/v2/channels/{icldOrName}/flexoffers/
uploadfile

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
file	multipart-file	form-data	CSV File

REQUEST

[FlexOffers - object \(on page 109\)](#)

RESPONSE (Status code: 201)

[FlexOffers - object \(on page 109\)](#)

Update FlexOffers

PUT /Campaign/api/interact/rest/v2/channels/{icldOrName}/flexoffers//
{flexofferIdOrName}

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
flexofferIdOr- Name	string	path	Flex Offer id or name
targetServerGroup	string	query	Target Server Group name. (Optional)

REQUEST

[FlexOffers - object \(on page 109\)](#)

RESPONSE (Status code: 202)

[FlexOffers - object \(on page 109\)](#)

Copy FlexOffers

PUT /Campaign/api/interact/rest/v2/channels/{icldOrName}/flexoffers//
{flexofferIdOrName}

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
flexofferIdOr- Name	string	path	Flex Offer id or name
targetServerGroup	string	query	Target Server Group name

REQUEST

[FlexOffers - object \(on page 109\)](#)

RESPONSE (Status code: 202)

[FlexOffers - object \(on page 109\)](#)

Delete FlexOffers

DELETE /Campaign/api/interact/rest/v2/channels/{icldOrName}/flexoffers//
{flexofferIdOrName}

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
flexofferIdOr- Name	string	path	Flex Offer id or name

RESPONSE (Status code: 200)

No content

Get All Server Groups

GET /Campaign/api/interact/rest/v2/servergroups

Parameters

Name	Type	In	Description
all	bool	query	Get all server group flag. (Default: false) (Optional)

RESPONSE (Status code: 200)

```
[  
  "SG1",  
  "SG2"  
]
```

Get Server Group Details

GET /Campaign/api/interact/rest/v2/servergroups/{servergroupname}

Parameters

Name	Type	In	Description
serverGroup- Name	string	path	Server Group name

RESPONSE (Status code: 200)

```
{  
  "dataSource": "string",  
  "instanceURLs": [  
    "string"  
  ],  
  "serverGroupName": "string"  
}
```

Get All Tables by Server Group

GET /Campaign/api/interact/rest/v2/tables

Parameters

Name	Type	In	Description
serverGroup-Name	string	path	Server Group name

RESPONSE (Status code: 200)

```
[
  "SG1",
  "SG2"
]
```

FlexOffers Rules

These APIs are used to perform CRUD operations on FlexOffers rules.

Objects

For abbreviations, see the [Abbreviations \(on page 4\)](#) topic.

FlexOffers Rule Object

Attribute Name	Type	Description	Required Cr Up	
offerMappingRowID	number	Unique id		

cellId	number	Cell id	✓	
cellCode	string	Cell code		
zoneId	number	Zone id		
zoneName	string	Zone name		
offerId	number	Offer id	✓	✓
offerCode	string	Offer name		
offerName	string	Offer code		
parameterizedOffer- Attribute	string	Parameterized Offer Attribute	x	
enabled	bool	Enable / Disable rule		
eligibilityPredicateEn- abled	bool	Enable / Disable eligibility predicate		
eligibilityPredicateId	number	Predicate id for eligibility	x	
eligibilityPredicate	string	Predicate to define eligibility		
effectiveDate	number	Effective date in Millis		
expirationDate	number	Expiration date in Millis		
score	number	Score	✓	✓
scorePredicate	string	Predicate to calculate score		
scorePredicateEn- abled	bool	Enable / Disable score predicate		
scorePredicateId	number	Predicate id for score	x	
learningMode	number	Learning mode 1: Learning mode not set at this level; inherit setting		

		2: Use Marketer score 3: Use Learning score		
learningModelId	number	Learning model id		
lmName	string	Learning model name		
offerAttrExpressions	array-object	List of Offer Attribute Expression Object		
userdefinedFields	array-object	List of Offer Mapping Attribute Object		
userdefinedFields-Map	map	Offer Attribute map	x	
createBy	number	Created by user	x	x
createDate	number	Created date in Millis	x	x
updateBy	number	Updated by user	x	x
updateDate	number	Update date in Millis	x	x

Offers Attribute Expression Object

Attribute Name	Type	Description	Re-quired Cr	Re-quired Up
attrId	number	Unique id	✓	✓
attrName	string	Attribute name		
expression	string	Expression to calculate value for attribute	✓	✓

Offer Mapping Attribute Object

Attribute Name	Type	Description	Required Cr Up	
name	string	Attribute name		
displayName	string	Display name for attribute		
relation	string	Relational operator • EQUAL • GREATER • GREATEREQUAL • LESS • LESSSQUEAL • NOTEQUAL • STARTSWITH • ENDSWITH • CONTAINS		
size	number	Size		
type	string	Data type • STRING • LONG • BIT • INTEGER • DATE • FLOAT • DOUBLE		
dateFormat	string	Date format		
value	object	Attribute Value		

FlexOffers Rule - object

For details, see the [Objects \(on page 116\)](#) topic.

FlexOffers Rule<flexoffers-rule-object>

```
{
  "cellCode": "string",
  "cellId": 0,
  "createBy": 0,
  "createDate": "2021-05-19T08:19:46.467Z",
  "effectiveDate": 0,
  "eligibilityPredicate": "string",
  "eligibilityPredicateEnabled": true,
  "eligibilityPredicateId": 0,
  "enabled": true,
  "expirationDate": 0,
  "learningMode": 0,
  "learningModelId": 0,
  "lmName": "string",
  "offerAttrExpressions": [
    <offer-attribute-expression-object>
  ],
  "offerCode": "string",
  "offerId": 0,
  "offerMappingRowID": 0,
  "offerName": "string",
  "parameterizedOfferAttribute": "string",
  "score": 0,
  "scorePredicate": "string",
  "scorePredicateEnabled": true,
  "scorePredicateId": 0,
  "updateBy": 0,
  "updateDate": "2021-05-19T08:19:46.467Z",
```

```

    "userdefinedFields": [
      <offer-mapping-attribute-object>
    ],
    "userdefinedFieldsMap": {},
    "zoneId": 0,
    "zoneName": "string"
  }

```

Offer Attribute Expression <offer-attribute-expression-object>

```

{
  "attrId": 0,
  "attrName": "string",
  "expression": "string"
}

```

Offer Mapping Attribute <offer-mapping-attribute-object>

```

{
  "dateFormat": "string",
  "displayName": "string",
  "name": "string",
  "relation": "EQUAL",
  "size": 0,
  "type": "STRING",
  "value": {}
}

```

Get All FlexOffer Rules

GET / Campaign/api/interact/rest/v2/channels/{icldOrName}/flexoffers/
{flexofferIdOrName}/rules

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
flexofferIdOr- Name	string	path	Flex Offer id or name
condition	map	query	Key-Value pair • Ex. OfferName=eq;OfferA
page	num- ber	query	nth page to retrieve records. Default is 0 (first page).
size	num- ber	query	Number of records per page. Default is 10.

RESPONSE (Status code: 200)

For <flex-offer-rule-object>, see the [FlexOffers Rule - object \(on page 120\)](#).

```
{
  "content": [
    <flex-offer-rule-object>
  ],
  "page": {
    "hasNext": true,
    "hasPrev": true,
    "pageNumber": 0,
    "size": 0,
    "totalElements": 0,
    "totalPages": 0
  }
}
```

Get FlexOffer Rules

GET / Campaign/api/interact/rest/v2/channels/{icldOrName}/flexoffers/
{flexofferIdOrName}/rules/{ruleIdOrName}

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
flexofferIdOr- Name	string	path	FlexOffers id or name
ruleIdOrName	string	path	FlexOffers Rule id or name

RESPONSE (Status code: 200)

[FlexOffers Rule - object \(on page 120\)](#)

Save FlexOffer Rules

POST /Campaign/interact/api/v2/channels/{icldOrName}/flexoffers/
{flexofferIdOrName}/rules

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
flexofferIdOr- Name	string	path	FlexOffers id or name

REQUEST

For <flex-offer-rule-object> and <offer-mapping-attribute-object>, see the [FlexOffers Rule - object \(on page 120\)](#) topic.

```
{
  "newColumns": [
    <offer-mapping-attribute-object>
  ],
  "toAdd": [
    <flex-offer-rule-object>
  ],
  "toDelete": [
    0
  ],
  "toUpdate": [
    <flex-offer-rule-object>
  ]
}
```

RESPONSE (Status code: 202)

No content

Delete FlexOffer Rules

DELETE /Campaign/interact/api/v2/channels/{icIdOrName}/flexoffers/
{flexofferIdOrName}/rules

Parameters

Name	Type	In	Description
icIdOrName	string	path	Interactive Channel id or name
flexofferIdOr- Name	string	path	FlexOffers id or name
ids	string	query	Comma separated rule IDs to be deleted.

RESPONSE (Status code: 200)

No content

Preview of System Table columns

GET /Campaign/interact/api/v2/preview/systemcolumns

RESPONSE (Status code: 200)

For <offer-mapping-attribute-object>, see the [FlexOffers Rule - object \(on page 120\)](#) topic.

```
{
  "content": [
    <offer-mapping-attribute-object>
  ],
  "page": {
    "hasNext": true,
    "hasPrev": true,
    "pageNumber": 0,
    "size": 0,
    "totalElements": 0,
    "totalPages": 0
  }
}
```

FlexOffers Filters

These APIs are used to perform CRUD operations on FlexOffers filters.

Objects

For abbreviations, see the [Abbreviations \(on page 4\)](#) topic.

FlexOffers Filter Object

Attribute Name	Type	Description	Re-quired Cr	Re-quired Up
filterID	number	Unique id	x	x
name	string	Filter name	✓	
description	string	Description of the Filter		
isDefault	bool	Is default filter?		
offerMappingId	number	Flex Offer id	x	x
filters	array-object	List of Flex Offer Attribute Object	✓	
createBy	number	Created by user	x	x
createDate	number	Created date in Millis	x	x
updateBy	number	Updated by user	x	x
updateDate	number	Update date in Millis	x	x

FlexOffers Attribute Object

Attribute Name	Type	Description	Re-quired Cr	Re-quired Up
name	string	Attribute name	✓	✓
displayName	string	Display name for attribute	x	x
dynamic	bool	Is attribute dynamic?		

relation	string	Relational operator • EQUAL • GREATER • GREATEREQUAL • LESS • LESSQUEAL • NOTEQUAL • STARTSWITH • ENDSWITH • CONTAINS	ü	ü
size	number	Size		
type	string	Data type • STRING • LONG • BIT • INTEGER • DATE • FLOAT	✓	✓
dateFormat	string	Date format	x	x
value	object	Attribute Value		

FlexOffers Filter - object

For details, see the [Objects \(on page 125\)](#) topic.

FlexOffers Filter<flexoffers-filter-object>

```
{
  "createBy": 0,
  "createDate": "2021-05-19T08:19:46.324Z",
  "description": "string",
```

```

"filterID": 0,
"filters": [
  <flex-offer-attribute-object>
],
"isDefault": true,
"name": "string",
"offerMappingId": 0,
"updateBy": 0,
"updateDate": "2021-05-19T08:19:46.324Z"
}

```

FlexOffers Attribute <flex-offer-attribute-object>

```

{
  "dateFormat": "string",
  "displayName": "string",
  "dynamic": true,
  "name": "string",
  "relation": "string",
  "size": 0,
  "type": "string",
  "value": {}
}

```

Get All FlexOffers Filters

GET / Campaign/api/interact/rest/v2/channels/{icldOrName}/flexoffers/
{flexofferIdOrName}/filters

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name

flexofferIdOr-Name	string	path	Flex Offer id or name
condition	map	query	Key-Value pair • Ex. OfferName=eq;OfferA
page	number	query	nth page to retrieve records. Default is 0 (first page).
size	number	query	Number of records per page. Default is 10.

RESPONSE (Status code: 200)

For <flex-offer-filter-object>, see the [FlexOffers Filter - object \(on page 127\)](#).

```
{
  "content": [
    <flex-offer-filter-object>
  ],
  "page": {
    "hasNext": true,
    "hasPrev": true,
    "pageNumber": 0,
    "size": 0,
    "totalElements": 0,
    "totalPages": 0
  }
}
```



Note: This output does not include conditions.

Get FlexOffers Filters

GET/Campaign/api/interact/rest/v2/channels/{icldOrName}/flexoffers/
{flexofferIdOrName}/filters/ {filterByIdOrName}

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
flexofferIdOr- Name	string	path	FlexOffers id or name
filterByIdOrName	string	path	FlexOffers Filter id or name

RESPONSE (Status code: 200)

[FlexOffers Filter - object \(on page 127\)](#).

Create FlexOffers Filters

POST/Campaign/api/interact/rest/v2/channels/{icldOrName}/flexoffers/
{flexofferIdOrName}/filters

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
flexofferIdOr- Name	string	path	FlexOffers id or name

REQUEST

[FlexOffers Filter - object \(on page 127\)](#)

RESPONSE (Status Code: 200)

[FlexOffers Filter - object \(on page 127\)](#)

Update FlexOffers Filters

PUT/Campaign/api/interact/rest/v2/channels/{icldOrName}/flexoffers/
{flexofferIdOrName}/filters/{filterIdOrName}

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
flexofferIdOr- Name	string	path	Flex Offer id or name
filterByIdOrName	string	path	Flex Offer Filter id or name
mode[ML1]	string	query	Filter mode (Optional) • copy

REQUEST

[FlexOffers Filter - object \(on page 127\)](#)

RESPONSE (Status Code: 202)

[FlexOffers Filter - object \(on page 127\)](#)

Delete FlexOffers Filters

DELETE/Campaign/api/interact/rest/v2/channels/{icldOrName}/flexoffers/
{flexofferIdOrName}/filters/{filterIdOrName}

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name

flexofferIdOr- Name	string	path	Flex Offer id or name
filterByIdOrName	string	path	Flex Offer Filter id or name

RESPONSE (Status Code: 200)

No content

FlexOffers Deployment

These APIs are used to perform CRUD operations on the FlexOffers for deployment.

Objects

For abbreviations, see the [Abbreviations \(on page 4\)](#) topic.

FlexOffers Deployment Object

Attribute Name	Type	Description	Re- quired Cr	Re- quired Up
deployAction	string	Deployment action • markDeploy • markUnDeploy • cancelDeploy • cancelUnDeploy	✓	✓
state	num- ber	State • 0: Ready for Deployment • 1: Ready for Undeployment	x	x

		• 2: Mark for Deployment • 3: Mark for Undeployment		
deployedState	number	Deployed state • 10: Not Yet Deployed • 11: Deployed • 12: Undeployed	x	x
dirty	bool	Dirty deployment flag	x	x
lastProdDepTime	date	Last production deployment time	x	x
lastMarkTime	date	Last (un) marked for (un) deployment time	x	x
deploymentStatus-Text	string	Status text	x	x
deploymentWaitMessage	string	Waiting message	x	x

FlexOffers Deployment - object

For details, see the [Objects \(on page 132\)](#) topic.

FlexOffers Deployment <flexoffers-deployment-object>

```
{
  "deployAction": "string",
  "deployedState": 0,
  "deploymentStatusText": "string",
  "deploymentWaitMessage": "string",
  "dirty": true,
  "lastMarkTime": "2021-01-01T01:02:03.456Z",
  "lastProdDepTime": "2021-01-01T01:02:03.456Z",
  "state": 0
}
```

}

Get Deployment State

GET /Campaign/api/interact/rest/v2/channels/{icldOrName}/flexoffers/
{flexofferIdOrName}/deployment

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
flexofferIdOr- Name	string	path	Flex Offer id or name

RESPONSE (Status Code: 200)

[FlexOffers Deployment - object \(on page 133\)](#)

Mark for (Un) Deployment

PUT /Campaign/api/interact/rest/v2/channels/{icldOrName}/flexoffers/
{flexofferIdOrName}/deployment

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
flexofferIdOr- Name	string	path	Flex Offer id or name

REQUEST

[FlexOffers Deployment - object \(on page 133\)](#)

RESPONSE (Status code: 202)[FlexOffers Deployment - object \(on page 133\)](#)

Cancel mark for (Un) Deployment

DELETE /Campaign/api/interact/rest/v2/channels/{icldOrName}/flexoffers/
 {flexofferIdOrName}/deployment

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
flexofferIdOr- Name	string	path	Flex Offer id or name

REQUEST[FlexOffers Deployment - object \(on page 133\)](#)**RESPONSE (Status Code: 200)**[FlexOffers Deployment - object \(on page 133\)](#)

Triggered Action

Description

These APIs are used to perform CRUD operations on the triggered action.

Objects

For abbreviations, see the [Abbreviations \(on page 4\)](#) topic.

Triggered Action Object

Attribute Name	Type	Description	Re- quired Cr	Re- quired Up
id	number	Unique id	x	x
name	string	Triggered Action name	✓	✓
description	string	Triggered Action description		
icld	number	Interactive channel id		
effectiveDate	number	Effective date is ms		
expirationDate	number	Expiration date is ms		
trigger	Object	Trigger object	✓	✓
branches	array-Object	List of Triggered Action Branch Object	✓	✓

Trigger Object

Attribute Name	Type	Description	Re- quired Cr	Re- quired Up
id	number	Unique id	✓	✓
name	string	Trigger name	✓	✓
type	string	type field will be 'Other' for event and 'Pattern' for event pattern	✓	✓

Trigger Action Branch Object

Attribute Name	Type	Description	Re- quired Cr	Re- quired Up
eligibility	Object	Eligibility Object	✓	✓
offer	Object	Triggered Action Offer Object	✓	✓
channels	array- ob- ject	List of Triggered Action Channel Ob- ject	✓	✓

Eligibility object

Attribute Name	Type	Description	Re- quired Cr	Re- quired Up
audienceLev- el	string	Audience Level	✓	✓
conditions	array- ob- ject	List of Triggered Action Condition Object	✓	✓

Triggered Action Condition Object

Attribute Name	Type	Description	Re- quired Cr	Re- quired Up
attrType	string	Type of attribute • Profile Attribute • Segment Attribute	✓	✓

		• Real-time attributes • Session Parameter		
attrName	string	Name of the attribute		
operator	string	Type of Operator • Eq • Ne • Lt • Lte • Gt • Gte • Sw • Ew • Con • Inc • Ninc	✓	✓
value	string	Attribute value		
valueType	string	Type of value • string • numeric • datetime	✓	✓
condition	string	Type of relational operator • AND • OR	✓	✓

Triggered Action Offer Object

Attribute Name	Type	Description	Re- quired Cr	Re- quired Up
selectionType	string	Offer selection type • Offer • Zone	✓	✓
zoneSelected	Object	Zone object		
offerSelected	Object	Offer object		
offerType	Number	offerType • 0 for offer • 1 for offerlist	✓	✓
offerSelection	Object	Offer Selection Policy Object		
cellId	number	Cell id		
score	number	Score		
scorePredicateEnabled	boolean	Enable / Disable score predicate		
scorePredicate	string	Predicate to define score		
eligibilityPredicateEnabled	boolean	Enable / Disable eligibility predicate		
eligibilityPredicate	string	Predicate to define eligibility		
effectiveDate	number	Effective date in Millis		
expirationDate	number	Expiration date in Millis		

learningMode	number	Learning mode • 1: Learning mode not set at this level; inheritsetting • 2: Use Marketerscore • 3: Use Learningscore		
ImName	string	Learning model name		
learningModelId	number	Learning model id		
offerAttrExpressions	Array-Object	List of Offer Attribute Expression Object		

Triggered Action Channel Object

Attribute Name	Type	Description	Required Cr	Required Up
delayMode	string	mode for delay • Delay • NoDelay • Date	✓	✓
name	string	Name of the touchpoint	✓	✓
type	string	Type of the touchpoint • Channel • Gateway	✓	✓

delayType	string	Delay type • Sec • Min • Hr • Day • date	✓	✓
delayValue	number	Delay value		
selectedDate	number	Selected date value in millisecond		

Offer object

Attribute Name	Type	Description	Re-quired Cr	Re-quired Up
id	number	Offer id	✓	✓
name	string	Offer name	✓	✓
description	string	Offer description		
offerCode	string	Offer code	✓	✓

Zone Object

Refer the Zone - [Objects \(on page 46\)](#)

Offer Selection policy Object

Attribute Name	Type	Description	Re-quired Cr	Re-quired Up
num	number	Number of offers to return from offer list		
opt	number	Allowed offer selection policy		
param	string	Parameter	x	x
sort	string	Sort by	x	x

Offer Attribute Expression Object

Attribute Name	Type	Description	Re-quired Cr	Re-quired Up
attrId	number	Unique id	✓	✓
attrName	string	Attribute name		
expression	string	Expression to calculate value for attribute	✓	✓

Triggered Action - object

For details, see the [Objects \(on page 135\)](#) topic.

Triggered Action Object <triggered-action-object>

```
{
  "id":0,
  "name":"string",
  "description":"string",
  "icId":0,
  "effectiveDate":0,
  "expirationDate":0,
  "trigger":<trigger-object>,
  "branches":[<trigger-action-branch-object>]
}
```

Trigger Object <trigger-object>

```
{
  "id":0,
  "name":"string",
  "type":"string"
}
```

Trigger Action Branch Object <trigger-action-branch-object>

```
{
  "eligibility":<eligibility-object>,
  "offer":<triggered-action-offer-object>,
  "channels":[<triggered-action-channel-object>]
}
```

Eligibility Object <eligibility-object>

```
{
  "audienceLevel":"string",
  "conditions":[<triggered-action-condition-object>]
}
```

Triggered Action Condition Object <triggered-action-condition-object>

```
{
  "attrType": "string",
  "attrName": "string",
  "operator": "string",
  "value": "string",
  "valueType": "string",
  "condition": "string"
}
```

Triggered Action Offer Object <triggered-action-offer-object>

```
{
  "selectionType": "string",
  "zoneSelected": <zone-object>,
  "offerSelected": <offer-object>,
  "offerType": 0,
  "offerSelection": <offer-selection-policy-object>,
  "cellId": 0,
  "score": 0,
  "scorePredicateEnabled": true,
  "scorePredicate": "string",
  "eligibilityPredicateEnabled": true,
  "eligibilityPredicate": "string",
  "effectiveDate": 0,
  "expirationDate": 0,
  "learningMode": 0,
  "lmName": "string",
  "learningModelId": 0,
  "offerAttrExpressions": [<offer-attribute-expression-object>]
}
```

Triggered Action Channel Object <triggered-action-channel-object>

```
{
  "delayMode": "string",
  "name": "string",
  "type": "string",
  "delayType": "string",
  "delayValue": 0,
  "selectedDate": 0
}
```

Offer Object <offer-object>

```
{
  "id": 0
  "name": " string"
  "description": " string"
  "offerCode": " string"
}
```

Zone Object <zone-object>

[Zone - object \(on page 47\)](#)

Offer Selection Policy <offer-selection-policy-object>

```
{
  "num": 0,
  "opt": 0,
  "param": "string",
  "sort": "string"
}
```

Offer Attribute Expression <offer-attribute-expression-object>

```
{
  "attrId": 0,
  "attrName": "string",
}
```

```
"expression": "string"
}
```

Get Triggered Actions

GET /Campaign/api/interact/rest/v2/channels/{icldOrName}/triggeredActions

Parameters

Name	Type	In	Description
icldOr-Name	string	path	Interactive Channel id or name
Page	number	query	nth page to retrieve records. Default is 0 (first page).
Size	number	query	Number of records per page. Default is 10.
query-Params	string	query	Search based on triggered action name, trigger name, offer name and touchpoint name. (Optional) • "name=like;triggeredAction" search for triggeredAction name • "trigger=like;trigger" search for trigger name • "channelName=like;touchpoint" search for touch point name • "channelName=like;touchpoint" search for touch point name

RESPONSE (Status Code: 200)

For <triggered-action-object>, see the [Triggered Action - object \(on page 142\)](#) topic.

```
{
  "content": [<triggered-action-object>],
  "page": {
    "pageNumber": 0,
    "totalElements": 0,
    "totalPages": 0,
    "size": 0,
    "hasNext": true,
    "hasPrev": true
  }
}
```

Get Triggered Action

GET /Campaign/api/interact/rest/v2/channels/{icIdOrName} /
triggeredActions/{triggeredActionIdOrName}

Parameters

Name	Type	In	Description
icIdOrName	string	path	Interactive Channel id or name
triggeredActionIdOr- Name	string	path	Triggered action id or name

RESPONSE (Status Code: 200)

For <triggered-action-object>, see the [Triggered Action - object \(on page 142\)](#) topic.

Save Triggered Actions

Create, Update, and delete Triggered Actions

POST /Campaign/api/interact/rest/v2/channels/{icIdOrName}/
triggeredActions/save

Parameters

Name	Type	In	Description
icIdOrName	string	path	Interactive Channel id or name

REQUEST

For <triggered-action-object>, see the [Triggered Action - object \(on page 142\)](#) topic.

```
{
  "toAdd": [<triggered-action-object>]
  "toUpdate": [<triggered-action-object>]
  "toDelete": [0]
}
```

RESPONSE (Status Code: 202)

No content.

Add Triggered Action

POST /Campaign/api/interact/rest/v2/channels/{icIdOrName}/
triggeredActions

Parameters

Name	Type	In	Description
icIdOrName	string	path	Interactive Channel id or name

REQUEST

For <triggered-action-object>, see the [Triggered Action - object \(on page 142\)](#) topic.

RESPONSE (Status Code: 201)

For <triggered-action-object>, see the [Triggered Action - object \(on page 142\)](#) topic.

Update Triggered Action

PUT /Campaign/api/interact/rest/v2/channels/{icldOrName}/
triggeredActions/ /{triggeredActionIdOrName}

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
triggeredActionIdOr- Name	string	path	Triggered action id or name

REQUEST

For <triggered-action-object>, see the [Triggered Action - object \(on page 142\)](#) topic.

RESPONSE (Status Code: 202)

For <triggered-action-object>, see the [Triggered Action - object \(on page 142\)](#) topic.

Copy Triggered Action

POST /Campaign/api/interact/rest/v2/channels/{icldOrName}/
triggeredActions/ /{triggeredActionIdOrName}

Parameters

Name	Type	In	Description
------	------	----	-------------

icldOrName	string	path	Interactive Channel id or name
triggeredActionIdOr- Name	string	path	Triggered action id or name

REQUEST

For <triggered-action-object>, see the [Triggered Action - object \(on page 142\)](#) topic.

RESPONSE (Status Code: 201)

For <triggered-action-object>, see the [Triggered Action - object \(on page 142\)](#) topic.

Delete Triggered Action

DELETE /Campaign/api/interact/rest/v2/channels {icldOrName}/
triggeredActions/{triggeredActionIdOrName}

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
triggeredActionIdOr- Name	string	path	Triggered action id or name

RESPONSE (Status Code: 202)

No content.

Gateway Groups (Outbound Channel)

Description

These APIs are used to perform CRUD operations on the gateway group.

Objects

For abbreviations, see the [Abbreviations \(on page 4\)](#) topic.

Gateway Groups Object

Attribute Name	Type	Description	Re- quired Cr	Re- quired Up
id	number	Unique id of gateway group	x	x
Name	string	Gateway groups' name	✓	✓
Description	string	Gateway groups' description		
icld	number	Interactive channel id		
selectedGateway-Names	Array-object	<selected- gateway-object>	✓	✓

Selected Gateway Object

Attribute Name	Type	Description	Re- quired Cr	Re- quired Up
Name	string	Gateway names	✓	✓

Gateway Groups - object

For details, see the [Objects \(on page 151\)](#) topic.

Gateway Groups Object <gateway-groups-object>

```
{
  "id":0,
  "name":"string",
  "description":"string",
  "icId":0,
  "selectedGatewayNames": [<selected-gateway-object>]
}
```

Selected Gateway Object <selected-gateway-object>

```
{
  "name":"string"
}
```

Get All Gateway Groups (Get Outbound Channels)

GET /Campaign/api/interact/rest/v2/channels/{icIdOrName}/
outboundChannels

Parameters

Name	Type	In	Description
icIdOr- Name	string	path	Interactive Channel id or name
query- Params	string	query	Search based on gateway name. (Optional) • "gateway=like;gatewayName" search for gateway name

RESPONSE (Status Code: 200)

For <gateway-groups-object>, see the [Gateway Groups - object \(on page 151\)](#) topic.

```
{
  "content": [<gateway-groups-object>],
  "page": {
    "pageNumber": 0,
    "totalElements": 0,
    "totalPages": 0,
    "size": 0,
    "hasNext": true,
    "hasPrev": true
  }
}
```

Get Gateway Groups (Get Outbound Channels)

GET /Campaign/api/interact/rest/v2/channels/{icIdOrName} /
outboundChannels/{outboundChannelIdOrName}

Parameters

Name	Type	In	Description
icIdOrName	string	path	Interactive Channel id or name
outboundChannelIdOr- Name	string	path	Gateway groups id or name

RESPONSE (Status Code: 200)

For <gateway-groups-object>, see the [Gateway Groups - object \(on page 151\)](#) topic.

Add Gateway Groups (Add Outbound Channels)

POST /Campaign/api/interact/rest/v2/channels/{icIdOrName}/
outboundChannels

Parameters

Name	Type	In	Description
------	------	----	-------------

icldOrName	string	path	Interactive Channel id or name
------------	--------	------	--------------------------------

REQUEST

For <gateway-groups-object>, see the [Gateway Groups - object \(on page 151\)](#) topic.

RESPONSE (Status Code: 201)

For <gateway-groups-object>, see the [Gateway Groups - object \(on page 151\)](#) topic.

Update Gateway Groups (Update Outbound Channels)

PUT /Campaign/api/interact/rest/v2/channels/{icldOrName}/
outboundChannels/{outboundChannelIdOrName}

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
outboundChannelIdOr- Name	string	path	Gateway Groups id or name

REQUEST

For <gateway-groups-object>, see the [Gateway Groups - object \(on page 151\)](#) topic.

RESPONSE (Status Code: 202)

For <gateway-groups-object>, see the [Gateway Groups - object \(on page 151\)](#) topic.

Copy Gateway Groups (Copy Outbound Channel)

POST /Campaign/api/interact/rest/v2/channels/{icldOrName}/
outboundChannels/{outboundChannelIdOrName}

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
outboundChannelIdOr- Name	string	path	Gateway groups id or name

REQUEST

For <gateway-groups-object>, see the [Gateway Groups - object \(on page 151\)](#) topic.

RESPONSE (Status Code: 201)

For <gateway-groups-object>, see the [Gateway Groups - object \(on page 151\)](#) topic.

Delete Gateway Groups (Delete Outbound Channel)

DELETE /Campaign/api/interact/rest/v2/channels {icldOrName}/
outboundChannels/{outboundChannelIdOrName}

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
outboundChannelIdOr- Name	string	path	Gateway groups id or name

RESPONSE (Status Code: 202)

No content.

Gateway

Description

These APIs are used to perform CRUD operations on Gateway.

Objects

For abbreviations, see the [Abbreviations \(on page 4\)](#) topic.

Gateway Object

Attribute Name	Type	Description	Re- quired Cr	Re- quired Up	Re- quired Cp
Id	number	Unique id	x	x	x
Name	string	Gateway name	✓		✓
Description	string	Description of the Gateway			
icld	number	Interactive Channel id			ü
audienceLevel	string	Audience Level	✓		✓
Type	number	Gateway type • 1: Generic Outbound • 2: Generic Inbound • 3: Journey Outbound • 4: Deliver Outbound	✓		✓
priority	number	Gateway priority	✓		✓

noOfMes-sages	number	Number of messages			
defaultCellID	number	Default Cell ID			
defaultCell-Code	string	Default Cell Code	x	x	x
contentMap-ping	array-ob-ject	List of Content Mapping Ob-ject			
eventMapping	array-ob-ject	List of Event Mapping Ob-ject			
effectiveDate	number	Effective date in Millis			
expirationDate	number	Expiration date in Millis			
templateId	string	Deliver Template Id			
template-Name	string	Deliver Template Name			
templateType	string	Deliver Template Type			
appId	number	Mobile App Id			
appName	string	Mobile App Name			
createBy	number	Created by user	x	x	x
createDate	number	Created date in Millis	x	x	x
updateBy	number	Updated by user	x	x	x
updateDate	number	Update date in Millis	x	x	x

Content Mapping Object

Attribute Name	Type	Description	Re-quired	Re-quired	Re-quired
----------------	------	-------------	-----------	-----------	-----------

			Cr	Up	Cp
interactFieldName	string	Interact field name			
endpointFieldName	string	Endpoint field name			
type	string	Content Mapping type • string • numeric • datetime			
mandatory	bool	Is mandatory mapping?			
defaultValue	object	Default Value			
size	number	Size of value			
expression	bool	Is an expression?			
custom	bool	Is custom attribute?			
dateFormat	string	Date Format			

Event Mapping Object

Attribute Name	Type	Description	Required		
			Cr	Up	Cp
endpointEvent	string	Endpoint event name	✓	✓	✓
interactEvent	string	Interact event nam	✓	✓	✓
contentMapping	array-object	List of Content Mapping Object			

Gateway - object

For details, see the [Objects \(on page 156\)](#) topic.

Gateway <gateway-object>

```
{
  "audienceLevel": "string",
  "contentMapping": [
    <content-mapping-object>
  ],
  "createBy": 0,
  "createDate": "2021-05-19T08:19:46.328Z",
  "defaultCellCode": "string",
  "defaultCellID": 0,
  "description": "string",
  "effectiveDate": 0,
  "eventMapping": [
    <event-mapping-object>
  ],
  "expirationDate": 0,
  "icId": 0,
  "id": 0,
  "name": "string",
  "noOfMessages": 0,
  "priority": 0,
  "templateId": "string",
  "templateName": "string",
  "templateType": "string",
  "type": 0,
  "updateBy": 0,
  "updateDate": "2021-05-19T08:19:46.328Z"
}
```

Content Mapping <content-mapping-object>

```
{
  "custom": true,
```

```

    "dateFormat": "string",
    "defaultValue": {},
    "endpointFieldName": "string",
    "expression": true,
    "interactFieldName": "string",
    "mandatory": true,
    "size": 0,
    "type": "string"
  }

```

Event Mapping <event-mapping-object>

```

{
  "contentMapping": [
    <content-mapping-object>
  ],
  "endpointEvent": "string",
  "interactEvent": "string"
}

```

Get All Gateways

GET /Campaign/api/interact/rest/v2/channels/{icldOrName}/gateways

Parameters

Name	Type	In	Description
icldOr-Name	string	path	Interactive Channel id or name
typeld	number	query	Gateway type • 1: Generic Outbound • 2: Generic Inbound • Journey Inbound

page	number	query	nth page to retrieve records. Default is 0 (first page).
size	number	query	Number of records per page. Default is 10.

RESPONSE (Status Code: 200)

For <gateway-object>, see the [Gateway - object \(on page 158\)](#) topic.

```
{
  "content": [
    <gateway-object>
  ],
  "page": {
    "hasNext": true,
    "hasPrev": true,
    "pageNumber": 0,
    "size": 0,
    "totalElements": 0,
    "totalPages": 0
  }
}
```

Get Gateway

GET /Campaign/api/interact/rest/v2/channels/{icIdOrName}/gateways/{gatewayId}

Parameters

Name	Type	In	Description
icIdOrName	string	path	Interactive Channel id or name

gatewayId	number	path	Gateway id
-----------	--------	------	------------

RESPONSE (Status Code: 200)

[Gateway - object \(on page 158\)](#)

Create Gateway

POST /channels/{icIdOrName}/gateways

Parameters

Name	Type	In	Description
icIdOrName	string	path	Interactive Channel id or name

REQUEST

[Gateway - object \(on page 158\)](#)

RESPONSE (Status code: 201)

[Gateway - object \(on page 158\)](#)

Copy Gateway

POST /Campaign/api/interact/rest/v2/channels/{icIdOrName}/gateways/{gatewayId}

Parameters

Name	Type	In	Description
icIdOrName	string	path	Interactive Channel id or name
gatewayId	number	path	Gateway id

REQUEST

[Gateway - object \(on page 158\)](#)

RESPONSE (Status code: 201)

[Gateway - object \(on page 158\)](#)

Update Gateway

PUT /Campaign/api/interact/rest/v2/channels/{icldOrName}/gateways/
{gatewayId}

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
gatewayId	number	path	Gateway id

REQUEST

[Gateway - object \(on page 158\)](#)

RESPONSE (Status code: 202)

[Gateway - object \(on page 158\)](#)

Delete Gateway

DELETE /Campaign/api/interact/rest/v2/channels/{icldOrName}/gateways/
{gatewayId}

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
gatewayId	number	path	Gateway id

RESPONSE (Status code: 200)

No content

Interactive Channel Deployment

This API is used to deploy interactive channel.

Objects

For abbreviations, see the [Abbreviations \(on page 4\)](#) topic.

Interactive Channel Deployment Object

Attribute Name	Type	Description	Re- quired Cr	Re- quired Up
icIdOrName	string	Interactive Channel id or name	✓	✓
rtUsername	string	Interact run time username	✓	✓
rtPassword	string	Interact run time user pass- word	✓	✓
serverGroup	string	Server Group name	✓	✓
serverGroup- Type	string	Server Group type • 1: Production • 2: Test	✓	✓

Deployment or Undeployment

POST /Campaign/api/interact/rest/v2/deployments

Parameters

Name	Type	In	Description
request	number	query	Task to perform: • 1: Deploy • 2: Undeploy
include-Global	bool	query	Include global data or not in the task. (Default: true)
globalOnly	bool	query	Only (un) deploy global data

REQUEST

```
{
  "icIdOrName": "string",
  "rtPassword": "string",
  "rtUsername": "string",
  "serverGroup": "string",
  "serverGroupType": 0
}
```

RESPONSE (Status Code: 200)

```
{
  "Deployment finished successfully"
}
```

Interactive Flowchart Process Box

These APIs are used to perform CRUD operations on Interactive flowchart process box.

Objects

For abbreviations, see the [Abbreviations \(on page 4\)](#) topic.

Interactive Flowchart Process Box

Attribute Name	Type	Description	Re- quired Cr	Re- quired Up
pblID	number	Process box id		
name	string	Process box name		
notes	string	Description of the process box		
upstreamPBNames	ar- ray-string	Upstream process box names		
downstreamPBNames	ar- ray-string	Downstream process box names		
processBoxConfigura- tion	object	Process Box Configuration Object • Interaction • Decision • PopulateSeg • Select		

Process Box - object

For details, see the [Objects \(on page 165\)](#) topic.

Process Box <process-box-object>

```
{
  "downstreamPBNames": [
    "string"
  ],
  "name": "string",
```

```

    "notes": "string",
    "pbID": 0,
    "processBoxConfiguration": {},
    "upstreamPBNames": [
        "string"
    ]
}

```

Process Box Configuration: Interaction

```

{
    "type": "Interaction",
    "selectAllIds": false,
    "maxSize": "eg: 5"
}

```

Process Box Configuration: Decision

```

{
    "input": [
        "<process-box-name>"
    ],
    "type": "Decision",
    "mutuallyExclusiveBranches": false,
    "branchDetails": [
        {
            "branchName": "<branch-name>",
            "selectAllIds": false,
            "expression": "expression eg: CUSTOMERID < 10",
            "tableName": "table name eg: dbo_CUST"
        },
    ]
}

```

Process Box Configuration: PopulateSeg

```
{
  "type": "PopulateSeg",
  "inputPBLList": [
    {
      "policyId": <policy-id>,
      "description": "<description>",
      "inputCell": "<input-cell>",
      "segmentName": "<segment-name>",
      "folderId": <folder-id>
    }
  ]
}
```

Process Box Configuration: Select

```
{
  "type": "Select",
  "selectInputTables": "table name eg: dbo_CUST1",
  "selectAllIds": false,
  "expression": "Expression is provided in case selectAllIds is false not otherwise eg: CUSTOMERID < 30"
}
```

Get All Process Box

GET /Campaign/api/interact/rest/v2/channels/{icldOrName}/flowcharts/{flowchartIdOrName}/processboxes

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name

flowchartIdOrName	string	path	Interactive Flowchart id or name
sessionId	number	query	Session id

RESPONSE (Status Code: 200)

For <process-box-object>, see the [Process Box - object \(on page 166\)](#) topic.

```
[
  <process-box-object>
]
```

Get Process Box

GET /Campaign/api/interact/rest/v2/channels/{icIdOrName}/flowcharts/{flowchartIdOrName}/processboxes/{pbIdOrName}

Parameters

Name	Type	In	Description
icIdOrName	string	path	Interactive Channel id or name
flowchartIdOrName	string	path	Interactive Flowchart id or name
pbIdOrName	string	path	Process Box id or name
sessionId	number	query	Session id

RESPONSE (Status Code: 200)

[Process Box - object \(on page 166\)](#)

Create Process Box

POST /Campaign/api/interact/rest/v2/channels/{icIdOrName}/flowcharts/{flowchartIdOrName}/processboxes

Parameters

Name	Type	In	Description
icIdOrName	string	path	Interactive Channel id or name
flowchartIdOrName	string	path	Interactive Flowchart id or name
sessionId	number	query	Session id

REQUEST

[Process Box - object \(on page 166\)](#)

RESPONSE (Status code: 201)

For <process-box-object>, see the [Process Box - object \(on page 166\)](#) topic.

```
[
  <process-box-object>
]
```

Update Process Box

PUT /Campaign/api/interact/rest/v2/channels/{icIdOrName}/flowcharts/{flowchartIdOrName}/processboxes/{pbIdOrName}

Parameters

Name	Type	In	Description
icIdOrName	string	path	Interactive Channel id or name
flowchartIdOrName	string	path	Interactive Flowchart id or name
pbIdOrName	string	path	Process Box id or name
sessionId	number	query	Session id

REQUEST

[Process Box - object \(on page 166\)](#)

RESPONSE (Status code: 200)

[Process Box - object \(on page 166\)](#)

Delete Process Box

DELETE /Campaign/api/interact/rest/v2/channels/{icldOrName}/flowcharts/{flowchartIdOrName}/processboxes

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
flowchartIdOr- Name	string	path	Interactive Flowchart id or name
pblds	string	query	Comma separated process box IDs to be deleted.
sessionId	num- ber	query	Session id

RESPONSE (Status code: 200)

No content

Interactive Flowchart

These APIs are used to perform CRUD operations on interactive flowcharts.

Objects

For abbreviations, see the [Abbreviations \(on page 4\)](#) topic.

Interactive Flowchart Option

Attribute Name	Type	Description	Re-quired Cr	Re-quired Up
audienceName	string	Audience name	ü	ü
flowchartName	string	Flowchart name	ü	ü
flowchartNote	string	Description of the Flowchart		

Interactive Flowchart Response

Attribute Name	Type	Description
flowchartId	number	Flowchart id
flowchartName	string	Flowchart name
displayName	string	Display name
name	string	Name
fileName	string	Flowchart File name
description	string	Description of the Flowchart
audienceName	string	Audience name
sessionId	number	Session id
sessionName	string	Session name
retired	bool	Is retired?
createBy	number	Created by user
createDate	string	Created date

Deployment Action

Attribute Name	Type	Description	Re- quired Cr	Re- quired Up
deployAction	string	Deployment Action • markDeploy: Mark for deployment • markUnDeploy: Mark for undeployment	✓	✓

Deployment Data Object

Attribute Name	Type	Description
state	number	State • 0: READY_FOR_DEPLOYMENT • 1: READY_FOR_UN_DEPLOYMENT • 2: MARK_FOR_DEPLOYMENT • 3: MARK_FOR_UN_DEPLOYMENT
deployedState	number	Deployed state • 10: NOT_YET_DEPLOYED • 11: DEPLOYED • 12: UN_DEPLOYED • 13: TO_BE_DEPLOYED • 14: TO_BE_UNDEPLOYED
dirty	bool	Dirty deployment flag
lastProdDep- Time	date	Last production deployment time

lastMarkTime	date	Last (un) marked for (un) deployment time
--------------	------	---

Interactive flowchart - object

For details, see the [Objects \(on page 171\)](#) topic.

Interactive Flowchart Option <interactive-flowchart-option-object>

```
{
  "audienceName": "string",
  "flowchartName": "string",
  "flowchartNote": "string"
}
```

Interactive Flowchart Response <interactive-flowchart-response-object>

```
{
  "audienceName": "string",
  "createBy": 0,
  "createDate": "2021-05-19T08:19:46.557Z",
  "description": "string",
  "displayName": "string",
  "fileName": "string",
  "flowchartId": 0,
  "flowchartName": "string",
  "name": "string",
  "retired": true,
  "sessionId": 0,
  "sessionName": "string"
}
```

Deployment Action <deployment-action-object>

```
{
  "deployAction": "string"
}
```

Deployment Data <deployment-data-object>

```
{
  "deployedState": 0,
  "dirty": true,
  "lastMarkTime": "2021-01-01T01:02:03.456Z",
  "lastProdDepTime": "2021-01-01T01:02:03.456Z",
  "state": 0
}
```

Create Interactive Flowchart

POST /Campaign/api/interact/rest/v2/channels/{icldOrName}/flowcharts

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
sessionId	number	query	Session id

REQUEST

[Interactive flowchart - object \(on page 174\)](#)

RESPONSE (Status code: 200)

[Interactive flowchart - object \(on page 174\)](#)

Validate Interactive Flowchart

GET /Campaign/api/interact/rest/v2/channels/{icIdOrName}/flowcharts/{flowchartIdOrName}/validation

Parameters

Name	Type	In	Description
icIdOrName	string	path	Interactive Channel id or name
flowchartIdOrName	string	path	Interactive Flowchart id or name
sessionId	number	query	Session id

RESPONSE (Status code: 200)

No content

Delete Interactive Flowchart

DELETE /Campaign/api/interact/rest/v2/channels/{icIdOrName}/flowcharts/{flowchartIdOrName}

Parameters

Name	Type	In	Description
icIdOrName	string	path	Interactive Channel id or name
flowchartIdOrName	string	path	Interactive Flowchart id or name
sessionId	number	query	Session id

RESPONSE (Status code: 200)

No content

Get Deployment State

GET /Campaign/api/interact/rest/v2/channels/{icIdOrName}/flowcharts/{flowchartIdOrName}/deployments

Parameters

Name	Type	In	Description
icIdOrName	string	path	Interactive Channel id or name
flowchartIdOrName	string	path	Interactive Flowchart id or name
sessionId	number	query	Session id

RESPONSE (Status code: 200)

See the <deployment-data-object> in the [Interactive flowchart - object \(on page 174\)](#) topic.

Mark for (Un) Deployment

PUT /Campaign/api/interact/rest/v2/channels/{icIdOrName}/flowcharts/{flowchartIdOrName}/deployments

Parameters

Name	Type	In	Description
icIdOrName	string	path	Interactive Channel id or name
flowchartIdOrName	string	path	Interactive Flowchart id or name
sessionId	number	query	Session id

REQUEST

See the <deployment-action-object> in the [Interactive flowchart - object \(on page 174\)](#) topic.

RESPONSE (Status code: 202)

See the <deployment-data-object> in the [Interactive flowchart - object \(on page 174\)](#) topic.

Cancel Mark for (Un) Deployment

DELETE /Campaign/api/interact/rest/v2/channels/{icldOrName}/flowcharts/{flowchartIdOrName}/deployments

Parameters

Name	Type	In	Description
icldOrName	string	path	Interactive Channel id or name
flowchartIdOrName	string	path	Interactive Flowchart id or name
sessionId	number	query	Session id

RESPONSE (Status code: 200)

No Content.