

## **Cloud Native Unica V12.1.9 Implementation Guide for Apache Tomcat®**



# Contents

<b>Chapter 1. Helm chart configuration.....</b>	<b>3</b>
<b>Chapter 2. FAQs and troubleshooting.....</b>	<b>4</b>
Frequently Asked Questions.....	4
Question 1.....	4
Question 2.....	4
Question 3.....	4
Question 4.....	5
Question 5.....	5
Question 6.....	5
Question 7.....	6
Troubleshooting Issues.....	6
Question 1.....	6
Question 2.....	6
Question 3.....	6
<b>Chapter 3. Appendix: Description of Helm chart parameters.....</b>	<b>7</b>
Common configurations.....	7
Audience Central configurations.....	15
Campaign configurations.....	17
Centralized Offer Management configurations.....	23
Collaborate configurations.....	25
Contact Central configurations.....	28
Content Integration configurations.....	31
Director configurations.....	33
Insights Reports configurations.....	34
Interact configurations.....	36
InteractDT configurations.....	45
Journey configurations.....	47
Journey web configurations.....	49
Kafka configurations.....	53
Plan configurations.....	54
Platform configurations.....	57
RTP configurations.....	60
Segment Central configurations.....	61
Sub-chart configuration in Helm charts.....	65
values.yaml driven configurations.....	65

# Chapter 1. Helm chart configuration

Before you start the installation or upgrade of Cloud Native Unica, you should configure the appropriate `configMap` `YAML` files.

To access the `configMap` `YAML` files, navigate to `/unica/templates/` in the Unica charts folder. Open one of the following files and modify the parameters in that file:

- `common-configMap.yaml`. For more information, see [Common configurations on page 7](#).
- `audiencecentral-configMap.yaml`. For more information, see [Audience Central configurations on page 15](#).
- `campaign-configMap.yaml`. For more information, see [Campaign configurations on page 17](#).
- `offer-configMap.yaml`. For more information, see [Centralized Offer Management configurations on page 23](#).
- `collaborate-configMap.yaml`. For more information, see [Collaborate configurations on page 25](#).
- `assetpicker-configMap.yaml`. For more information, see [Content Integration configurations on page 31](#).
- `contactcentral-configMap.yaml`. For more information, see [Contact Central configurations on page 28](#).
- `director-configMap.yaml`. For more information, see [Director configurations on page 33](#).
- `birt-configMap.yaml`. For more information, see [Insights Reports configurations on page 34](#).
- `interact-configMap.yaml`. For more information, see [Interact configurations on page 36](#).
- `interactdt-configMap.yaml`. For more information, see [InteractDT configurations on page 45](#).
- `journey-configMap.yaml`. For more information, see [Journey configurations on page 47](#).
- `journeyweb-configMap.yaml`. For more information, see [Journey web configurations on page 49](#).
- `kafka-configMap.yaml`. For more information, see [Kafka configurations on page 53](#).
- `plan-configMap.yaml`. For more information, see [Plan configurations on page 54](#).
- `platform-configMap.yaml`. For more information, see [Platform configurations on page 57](#).
- For RTP configurations, see [RTP configurations on page 60](#).
- `segmentcentral-configMap.yaml`. For more information, see [Segment Central configurations on page 61](#).

## Chapter 2. FAQs and troubleshooting

This section covers the frequently asked questions and troubleshooting issues.

To view the list of FAQs, see [Frequently Asked Questions on page 4](#)

For information related to Troubleshooting, see [Troubleshooting Issues on page 6](#)

### Frequently Asked Questions

This topic contains the list of FAQs related to Cloud Native Unica release.

The list of FAQs are as follows:

- [Question 1 on page 4](#)
- [Question 2 on page 4](#)
- [Question 3 on page 4](#)
- [Question 4 on page 5](#)
- [Question 5 on page 5](#)
- [Question 6 on page 5](#)
- [Question 7 on page 6](#)

#### Question 1

How do I configure Campaign Docker image to support non-ASCII data?

To configure non-ASCII data support for the Campaign Docker image, execute the same steps used for configuring non-ASCII data support on on-premises Campaign. For more details, see the topic **Non-ASCII data in Campaign** in the *Unica Campaign Administrator's Guide*.

#### Question 2

How to install products on locations other than default location mentioned in the `common-configMap.yaml` file?

##### **About this task**

To install products on location other than the default location configured in the `common-configMap.yaml` file, complete the following steps.

1. Mount the directory.
2. Open the `common-configMap.yaml` file and update the default path to the required path.
3. Ensure that the `JDBCDrivers` folder exists in the provided path.

#### Question 3

Why has Cloud Native Unica installed `JRE9` and `JDK8` on my system?

Cloud Native Unica is bundled with `JRE9` and `JRE8`. In the `common-configMap.yaml` file:

- Provide the path of `JRE9` for the parameter **DOCKER\_JAVA\_HOME**. Cloud Native Unica uses `JRE9` for installation tasks.
- Provide the path of `JDK8` for the parameter **JAVA\_HOME**. The products of Unica uses `JDK8`.

## Question 4

Should the passwords in the `jdbc.properties` file be encrypted?

Yes. The passwords in the `jdbc.properties` file should be encrypted. Configure the passwords using the helm commands similar to configuring the host name. You do not have to store the passwords anywhere for reuse. Once you configure the passwords, it will be set in the application.

For Cloud Native Unica, the `jdbc.properties` file is available in the following locations:

- `/Interact/PatternStateETL/bin/jdbc.properties`
- `/Interact/tools/bin/jdbc.properties`
- `/ContactOptimization/install/jdbc.properties`
- `/Platform/tools/bin/jdbc.properties`
- `/install/jdbc.properties`
- `/Campaign/bin/jdbc.properties`
- `/Campaign/deliver/conf/jdbc.properties`
- `/Campaign/install/jdbc.properties`

## Question 5

List the default `JDBC` drivers provided with the Listener container.

On the Listener container, the `JDBC` drivers exist in the following path: `Docker_Home/JdbcDrivers/`. The list of default `JDBC` drivers available with the Listener container are as follows:

- `db2jcc4.jar`
- `mariadb-java-client-2.4.1.jar`
- `ojdbc8_docker.jar`

## Question 6

What should I do to make `/ACOOptAdmin.sh` work?

For `/ACOOptAdmin.sh` to work, update the following parameters in the `/ACOOptAdmin.sh` file:

- `JAVA_HOME`
- `OPTIMIZE_HOME`
- `JDBCDRIVER_CLASSPATH`

Use the `-async` option while running `ACOOptAdmin` utility on Cloud Native environments.

Using the `-async` utility triggers the desired operation on an Optimize session in the background before exiting.

**Example:** `./ACOOptAdmin.sh -u "user_name" -p "password" -sn "OptimizeSessionName" -async`



**Note:** Not using `-async` may trigger an Optimize session run, but the polling, related to the session run progress, will fail.

## Question 7

How are the Security Vulnerabilities are fixed?

### Answer

- Unica fixes security vulnerabilities with the every new release.
- Upon request, interim fixes are also provided with new set of docker images.

## Troubleshooting Issues

This topic contains the list of Troubleshooting issues related to Cloud Native Unica release.

The list of issues are as follows:

- [Question 1 on page 6](#)
- [Question 2 on page 6](#)
- [Question 3 on page 6](#)

## Question 1

Stopping and Restarting an Application Server

### About this task

Sometimes, you might have to stop and restart the application server. For example, if you have modified some settings and these modified settings require restarting the application server.

## Question 2

Cannot select supported locales for Plan.

When installing Plan using Cloud Native environment, you cannot select specific supported locales from the available list of supported locales. The system will automatically accept all available locales as the supported locales.

## Question 3

`ActiveMQ` URL does not work.

The `ActiveMQ` URL `http://unica-omnix-unica-activemq:8161/admin/queues.jsp`, which provides information about the `flowchartInfo-campaign` events count, will not work. This is a Known Issue and will be fixed in the next release.

# Chapter 3. Appendix: Description of Helm chart parameters

The following topics contain description of the parameters present in the `configMap` YAML files:

## Common configurations

To configure the common configurations, make the necessary modifications to the `common-configMap.yaml` file.

To access the `common-configMap.yaml` file, navigate to `/unica/templates/` in the Unica charts folder. Open the file and make modifications to the following parameters:

**Table 1. Data Parameters**

Parameter name	Parameter description
<code>WAIT_TIME</code>	Idle wait time in minutes.
<code>VERSION</code>	Version number of Unica.
<code>HOME_DIR</code>	Home directory of Cloud Native Unica.
<code>JAVA_HOME</code>	The location of Java Development Kit on the system. <b>Example:</b> <code>/docker/unica/jre</code>
<code>CERTIFICATE_IMPORT_DIR</code>	The location of the Unica certificates.
<code>TYPE</code>	Specify if it is a new installation or an upgrade. Valid values are <code>INSTALL</code> or <code>UPGRADE</code> .
<code>APPLICATION_DOMAIN</code>	The application domain.
<code>HOST</code>	Host ID of the Docker host.
<code>HOST_NAME</code>	Host name of the Docker host.
<code>DEFAULT_LOCALE</code>	The default locale to be used.
<code>DOCKER_JAVA_HOME</code>	The path of the Docker Java Home.
<code>MODE</code>	Specify the products that you will install on the Cloud Native Unica environment. The abbreviated values for each product are as follows: <ul style="list-style-type: none"><li>• Platform – <code>PLT</code></li><li>• Campaign – <code>CMP</code></li><li>• Optimize – <code>OPT</code></li><li>• Director – <code>DIR</code></li><li>• Plan – <code>PLN</code></li><li>• Interact – <code>INT</code></li><li>• Centralized Offer Management - <code>OFFER</code></li></ul>

**Table 1. Data Parameters (continued)**

Parameter name	Parameter description
	<ul style="list-style-type: none"> <li>• Insights Reports - <code>BIRT</code></li> <li>• Realtime Personalization - <code>RTP</code></li> </ul> <p>If you want to install all products you should provide the value as follows:</p> <p><code>PLT_CMP_INT_PLN_OPT_DIR</code></p> <p>If your database is MariaDB, Director will not work on MariaDB. In this case, you must provide the following value:</p> <p><code>PLT_CMP_INT_PLN_OPT</code></p>
<b>TOMCAT_FACTORY</b>	<b>Example:</b> <code>"com.unica.manager.tomcat.utils.TomcatDSFactory"</code>
<b>SERVER_TYPE</b>	The application server installed.
<b>IS_UNICODE</b>	Set <code>TRUE</code> if Unica is installed to support Unicode. Set <code>FALSE</code> if Unica is installed without support for Unicode
<b>JRE_HOME</b>	The path of the Docker Java Runtime Environment.
<b>SUPPORTED_LOCALES</b>	<p>The supported locales. Valid values are:</p> <ul style="list-style-type: none"> <li>• <code>en_US</code></li> <li>• <code>zh_TW</code></li> <li>• <code>fr_FR</code></li> <li>• <code>de_DE</code></li> <li>• <code>ja_JP</code></li> <li>• <code>ko_KR</code></li> <li>• <code>pt_BR</code></li> <li>• <code>es_ES</code></li> <li>• <code>zh_CN</code></li> <li>• <code>it_IT</code></li> </ul>
<b>UPGRADE_FROM_TO</b>	<code>11.1+To12.1</code>
<b>AC_VERSION</b>	<code>"12.1.x"</code>
<b>ACI_UNICODE</b>	<code>"No"</code>
<b>CONFIGURE_ON_ERROR_PROMPT</b>	<code>"Yes"</code>



Table 2. Miscellaneous Parameters

Parameter name	Parameter description
SOURCE_SCHEMA	"CAMP86"
TARGET_SCHEMA	"DBO"
DB_DRIVER_CLASS	<code>com.microsoft.sqlserver.jdbc.SQLServerDriver</code>
DB_TYPE	The name of the database used in the system. For example, Oracle.
DB_TYPE_UTILS	The name of the database utilities used in the system. For example, Oracle.
DB_DRIVER_CLASS	The class name of the database drivers.
DIALECT	The Hibernate dialect. Each database has a different dialect. For example, the Oracle database dialect is <code>org.hibernate.dialect.Oracle10gDialect</code> .
DB_DRIVER_JAR	The location of the database driver JAR file.
REPLACE_CONNECTION_URL_PREFIX	The prefix used when forming a URL to the database. Each database has a different prefix. For example, the Oracle database prefix is <code>jdbc:oracle:thin</code> .
JDBC_DRIVER_JAR_LOCATION	The location of the JDBC driver JAR file.
TABLE_SPACE	The table space name for the database.
DB_ROOT_USER	The database root username.
DB_ROOT_PASSWORD	The database root password.
DB_HOST_NAME	The host name of the database system.
DB_PORT	The port number of the database system.
DB2INST1_PASSWORD	The password for the DB2 instance.
LICENSE	<code>ACCEPT</code> if you accept the license or <code>DECLINE</code> if you do not accept the license.
DB_PLAT	The database name for Platform.
DB_PLAN_HOST	The host details of the database in the Plan system.
DB_PLAN_HOST_NAME	The database host name of the Plan system.
DB_PLAN_PORT	The database port number of the Plan system.
DB_PLAN	The database name for Plan.
DB_DRIVER	The database driver file name.

**Table 2. Miscellaneous Parameters (continued)**

Parameter name	Parameter description
PROTOCOL	The protocol used. For example, <code>HTTP</code> or <code>HTTPS</code> .
MDB_ENCODING	The encoding format used for MariaDB.
MDB_COLLATION	Valid values are <code>utf8_general_ci</code> and <code>utf8_unicode_ci</code> .
MAX_CONNECTIONS	The maximum concurrent connections supported.
IS_BASEVERSION_INSTALLED	Set to <code>TRUE</code> if the base version of Unica is installed during a Docker to Docker upgrade.
INSTALLATION_FLAG_CHECK_DIR	Directory path for installation flag files, used to determine if a specific version of Unica is already installed.
TARGET_VERSIONS	Comma-separated list of target versions of Unica to be installed ( <b>Example:</b> <code>12.1.4,12.1.5,12.1.6,12.1.7,12.1.8</code> ).
ENABLE_LISTENER_FS_TO_PV	Set to <code>TRUE</code> to copy the listener file system (FS) to the persistent volume (PV), or <code>FALSE</code> to copy it to <code>/opt</code> inside the container.
IMPORT_DB2_USER_DB	Set to <code>TRUE</code> to import the user database for DB2.
IMPORT_NETEZZA_USER_DB	Set to <code>TRUE</code> to import the user database for Netezza.
IMPORT_ORACLE_USER_DB	Set to <code>TRUE</code> to import the user database for Oracle.

**Table 3. Apache Tomcat Server restart-related parameters**

Parameter name	Parameter description
PLAN_TOMCAT_CHECK_SERVICE	<code>TRUE</code>
INTERACT_TOMCAT_CHECK_SERVICE	<code>TRUE</code>
CAMPAIGN_TOMCAT_CHECK_SERVICE	<code>TRUE</code>
PLATFORM_TOMCAT_CHECK_SERVICE	<code>TRUE</code>
ASSET_TOMCAT_CHECK_SERVICE	<code>TRUE</code>
ASSET_TOMCAT_CHECK_SERVICE	<code>TRUE</code>
CENTRALIZEDOFFER_TOMCAT_CHECK_SERVICE	<code>TRUE</code>
INSIGHTS_TOMCAT_CHECK_SERVICE	<code>TRUE</code>
JOURNEY_TOMCAT_CHECK_SERVICE	<code>TRUE</code>
AudienceCentral_TOMCAT_CHECK_SERVICE	<code>TRUE</code>
ContactCentral_TOMCAT_CHECK_SERVICE	<code>TRUE</code>

**Table 3. Apache Tomcat Server restart-related parameters (continued)**

Parameter name	Parameter description
SegmentationEngine_TOMCAT_CHECK_SERVICE	TRUE
SegmentCentral_TOMCAT_CHECK_SERVICE	TRUE
INTERACTDT_TOMCAT_CHECK_SERVICE	TRUE
AUDIENCECENTRAL_TOMCAT_WAIT_TIME	90
CONTACTCENTRAL_TOMCAT_WAIT_TIME	90
SEGMENTATIONENGINE_TOMCAT_WAIT_TIME	90
SEGMENTCENTRAL_TOMCAT_WAIT_TIME	90
PLATFORM_TOMCAT_WAIT_TIME	90
PLAN_TOMCAT_WAIT_TIME	90
INTERACT_TOMCAT_WAIT_TIME	90
CAMPAIGN_TOMCAT_WAIT_TIME	90
ASSET_TOMCAT_WAIT_TIME	90
CENTRALIZEDOFFER_TOMCAT_WAIT_TIME	90
INSIGHTS_TOMCAT_WAIT_TIME	90
JOURNEY_TOMCAT_WAIT_TIME	90
INTERACTDT_TOMCAT_WAIT_TIME	90

If the JDBC URL contains additional properties, please use the parameters mentioned in the [Table 4: JDBC Parameters on page 11](#) table using the format provided in the following example:

```
jdbc:sqlserver://localhost;databaseName=AdventureWorks;MultiSubnetFailover=true;
```

**Table 4. JDBC Parameters**

Parameter name	Parameter description
JDBC_URL_PROD	JDBC URL of the Prod datasource of Interact. You can provide custom JDBC URL with JDBC properties.
JDBC_URL_TEST	JDBC URL of the Prod datasource of Test. You can provide custom JDBC URL with JDBC properties.
JDBC_URL_LRN	JDBC URL of the Prod datasource of learning. You can provide custom JDBC URL with JDBC properties.
JDBC_URL_INT05	JDBC URL of the Prod datasource of Interact. You can provide custom JDBC URL with JDBC properties.

**Table 4. JDBC Parameters (continued)**

Parameter name	Parameter description
<b>JDBC_URL_INT</b>	JDBC URL of the Prod datasource of Interact runtime.You can provide custom JDBC URL with JDBC properties.
<b>JDBC_URL_PLATFORM</b>	JDBC URL of the Prod datasource of platform.You can provide custom JDBC URL with JDBC properties.
<b>JDBC_URL_CAMPAIGN</b>	JDBC URL of the Prod datasource of Campaign.You can provide custom JDBC URL with JDBC properties.
<b>JDBC_URL_PLAN</b>	JDBC URL of the Prod datasource of Plan.You can provide custom JDBC URL with JDBC properties.
<b>JDBC_URL_CONTACTCENTRAL</b>	JDBC URL of the Prod datasource of Contact Central.You can provide custom JDBC URL with JDBC properties.
<b>JDBC_URL_JOURNEY</b>	JDBC URL of the Prod datasource of Journey.You can provide custom JDBC URL with JDBC properties.
<b>JDBC_URL_JOURNEYREPORT</b>	JDBC URL of the Prod datasource of Journey Report.You can provide custom JDBC URL with JDBC properties.

**Table 5. Parameters when Installing 12.1.4 or Upgrading to 12.1.4**

Parameter name	Parameter description
<b>Details</b>	<code>removeAbandoned</code> is a Flag to remove abandoned connections if they exceed the <code>removeAbandonedTimeout</code> .
<b>testOnBorrow</b>	Indicates whether objects are validated before being borrowed from the pool. For an efficient validation, if objects fail validation, they are dropped from the pool and the system attempts to borrow another object.
<b>PLATFORM_DATA_SOURCE_PARAMETERS</b>	<code>removeAbandonedTimeout='300';removeAbandoned='true';testOnBorrow='true'</code>
<b>PLAN_DATA_SOURCE_PARAMETERS</b>	<code>removeAbandonedTimeout='300';removeAbandoned='true';testOnBorrow='true'</code>
<b>JOURNEYWEB_DATA_SOURCE_PARAMETERS</b>	<code>removeAbandonedTimeout='300';removeAbandoned='true';testOnBorrow='true'</code>
<b>JOURNEYREPORT_DATA_SOURCE_PARAMETERS</b>	<code>removeAbandonedTimeout='300';removeAbandoned='true';testOnBorrow='true'</code>

Table 5. Parameters when Installing 12.1.4 or Upgrading to 12.1.4

(continued)

Parameter name	Parameter description
CAMPAIGN_DATA_SOURCE_PARAMETERS	<code>removeAbandonedTimeout='300';removeAbandoned='true';testOnBorrow='true'</code>
INTERACT_DATA_SOURCE_PARAMETERS	<code>removeAbandonedTimeout='300';removeAbandoned='true';testOnBorrow='true'</code>
INTERACT_PROD_DATA_SOURCE_PARAMETERS	<code>removeAbandonedTimeout='300';removeAbandoned='true';testOnBorrow='true'</code>
INTERACT_TEST_DATA_SOURCE_PARAMETERS	<code>removeAbandonedTimeout='300';removeAbandoned='true';testOnBorrow='true'</code>
INTERACT_LEARNING_DATA_SOURCE_PARAMETERS	<code>removeAbandonedTimeout='300';removeAbandoned='true';testOnBorrow='true'</code>
INTERACT_CHRH_DATA_SOURCE_PARAMETERS	<code>removeAbandonedTimeout='300';removeAbandoned='true';testOnBorrow='true'</code>
COLLABORATE_DATA_SOURCE_PARAMETERS	<code>removeAbandonedTimeout='300';removeAbandoned='true';testOnBorrow='true'</code>
CONTACTCENTRAL_DATA_SOURCE_PARAMETERS	<code>removeAbandonedTimeout='300';removeAbandoned='true';testOnBorrow='true'</code>

Table 6. JRE-related Parameters

Parameter name	Parameter description
INSTALL_COMMAND1	<code>"yum install java-<i>n.n.n</i>-openjdk -y"</code>  where <i>n.n.n</i> is the JRE version. For example, if your JRE version is 1.8.0, replace <i>n.n.n</i> by 1.8.0.
INSTALL_COMMAND2	<code>"cp -Lrf &lt;jre-default-install-location&gt; / docker/unica/JdbcDrivers"</code>  where <i>&lt;jre-default-install-location&gt;</i> is the default install location of JRE. For example, if your default JRE installation location is <code>/usr/lib/jvm/jre</code> , replace <i>&lt;jre-default-install-location&gt;</i> by <code>/usr/lib/jvm/jre</code> .
DIRECTOR_JAVA_HOME	<code>"&lt;Target-JRE-Path&gt;"</code>

**Table 6. JRE-related Parameters (continued)**

Parameter name	Parameter description
	For example, if your target path of JRE is /docker/unica/jre, replace <Target-JRE-Path> by /docker/unica/jre.

**Table 7. Enabling Auto-restart of Services**

Parameter name	Parameter description
PLATFORM_TOMCAT_CHECK_SERVICE	TRUE
ASSET_TOMCAT_CHECK_SERVICE	TRUE

The auto process restart scripts are integrated in the containers. If required, you can customize these scripts.

**Table 8. Defining Wait Time for Unica Products**

Unica application	Parameter	Value	Description
Unica Platform	PLATFORM_TOMCAT_WAIT_TIME	90	The wait time in seconds for Apache Tomcat server to start.
Unica Plan	PLAN_TOMCAT_WAIT_TIME	90	
Unica Interact	INTERACT_TOMCAT_WAIT_TIME	90	
Unica Campaign	CAMPAIGN_TOMCAT_WAIT_TIME	90	
Unica Content Integration	ASSET_TOMCAT_WAIT_TIME	90	
Unica Centralized Offer Management	CENTRALIZEDOFFER_TOMCAT_WAIT_TIME	90	
Unica Insights Reports	INSIGHTS_TOMCAT_WAIT_TIME	90	
Unica Journey	JOURNEY_TOMCAT_WAIT_TIME	90	

**Example:**

```
JOURNEY_TOMCAT_WAIT_TIME: "90"
```

## Audience Central configurations

To configure Audience Central for Cloud Native Unica, make the necessary modifications to the `audiencecentral-configMap.yaml` file.

To access the `audiencecentral-configMap.yaml` file, navigate to `/unica/templates/` in the Unica charts folder. Open the file and make modifications to the following parameters:

**Table 9. Common parameters for Audience Central**

Parameter name	Parameter description
<code>AUDIENCECENTRAL_PRODUCT_NAME</code>	<code>Audiencecentral</code>
<code>AUDIENCE_CENTRAL_WAR_NAME</code>	<code>AudienceCentral.war</code>
<code>AUDIENCECENTRAL_APPLICATION_NAME</code>	<code>audiencecentral</code>
<code>AUDIENCECENTRAL_DOMAIN_USERNAME</code>	<code>root</code>
<code>AUDIENCECENTRAL_DOMAIN_PASSWORD</code>	<code>unica*03</code>

**Table 10. Application Server-related parameters for Audience Central**

Parameter name	Parameter description
<code>AUDIENCECENTRAL_HOST_NAME</code>	<code>{{ .Release.Name }}-unica-audiencecentral</code>
<code>AUDIENCECENTRAL_MANAGEMENT_PORT</code>	<code>9065</code>
<code>AUDIENCECENTRAL_MANAGEMENT_HTTPS_PORT</code>	<code>9994</code>
<code>AUDIENCECENTRAL_AJP_PORT</code>	<code>8009</code>
<code>AUDIENCECENTRAL_HTTP_PORT</code>	<code>9139</code>
<code>AUDIENCECENTRAL_HTTPS_PORT</code>	<code>9445</code>
<code>AUDIENCECENTRAL_RECOVERY_ENV_PORT</code>	<code>4713</code>
<code>AUDIENCECENTRAL_STATUS_MANAGER_PORT</code>	<code>4714</code>
<code>AUDIENCECENTRAL_MIN_HEAP</code>	<code>1024m</code>
<code>AUDIENCECENTRAL_MAX_HEAP</code>	<code>2048m</code>
<code>AUDIENCECENTRAL_URL</code>	<code>{{ include ip.protocol . }}://{{ .Values.service.hostname }}/AudienceCentral</code>
<code>AUDIENCECENTRAL_INTERNAL_URL</code>	<code>http://{{ .Release.Name }}-unica-audiencecentral:9139/AudienceCentral</code>
<code>PRODUCT_OPTS_AUDIENCECENTRAL</code>	<code>-DAUDIENCE_CENTRAL_HOME=/docker/unica/AudienceCentral/ -DENABLE_NON_PROD_MODE=true</code>

**Table 11. Database-related parameters for Audience Central**

Parameter name	Parameter description
<b>AUDIENCECENTRAL_USER_JNDI_NAME</b>	{{ .Values.audiencecentralData.audiencecentralConfigMapData.AUDIENCECENTRAL_USER_JNDI_NAME }}
<b>AUDIENCECENTRAL_USER_POOL_NAME</b>	{{ .Values.audiencecentralData.audiencecentralConfigMapData.AUDIENCECENTRAL_USER_POOL_NAME }}
<b>AUDIENCECENTRAL_USER_DATABASE_HOST</b>	{{ .Values.audiencecentralData.audiencecentralConfigMapData.AUDIENCECENTRAL_USER_DATABASE_HOST }}
<b>AUDIENCECENTRAL_USER_DATABASE_PORT</b>	{{ .Values.audiencecentralData.audiencecentralConfigMapData.AUDIENCECENTRAL_USER_DATABASE_PORT }}
<b>AUDIENCECENTRAL_USER_DATABASE_NAME</b>	{{ .Values.audiencecentralData.audiencecentralConfigMapData.AUDIENCECENTRAL_USER_DATABASE_NAME }}
<b>AUDIENCECENTRAL_USER_DATABASE_USERNAME</b>	{{ .Values.audiencecentralData.audiencecentralConfigMapData.AUDIENCECENTRAL_USER_DATABASE_USERNAME }}
<b>AUDIENCECENTRAL_USER_DATABASE_PASSWORD</b>	{{ .Values.audiencecentralData.audiencecentralConfigMapData.AUDIENCECENTRAL_USER_DATABASE_PASSWORD }}
<b>AUDIENCECENTRAL_USER_DS_INITIAL_SIZE</b>	{{ .Values.audiencecentralData.audiencecentralDSMData.AUDIENCECENTRAL_USER_DS_INITIAL_SIZE }}
<b>AUDIENCECENTRAL_USER_DS_MIN_IDLE</b>	{{ .Values.audiencecentralData.audiencecentralDSMData.AUDIENCECENTRAL_USER_DS_MIN_IDLE }}
<b>AUDIENCECENTRAL_USER_DS_MAX_IDLE</b>	{{ .Values.audiencecentralData.audiencecentralDSMData.AUDIENCECENTRAL_USER_DS_MAX_IDLE }}
<b>AUDIENCECENTRAL_USER_DS_MAX_TOTAL</b>	{{ .Values.audiencecentralData.audiencecentralDSMData.AUDIENCECENTRAL_USER_DS_MAX_TOTAL }}
<b>AUDIENCECENTRAL_USER_DS_STATEMENT_CACHE_SIZE</b>	{{ .Values.audiencecentralData.audiencecentralDSMData.AUDIENCECENTRAL_USER_DS_STATEMENT_CACHE_SIZE }}
<b>AUDIENCECENTRAL_USER_DATA_SOURCE_PARAMETERS</b>	{{ .Values.audiencecentralData.audiencecentralDSMData.AUDIENCECENTRAL_USER_DATA_SOURCE_PARAMETERS }}

**Installation parameters for Audience Central**

Parameter name	Parameter description
<b>AUDIENCECENTRAL_INSTALL_COMMAND1</b>	Parameters used for Installation commands and scripts that can be used for customization.
<b>AUDIENCECENTRAL_INSTALL_COMMAND2</b>	
<b>AUDIENCECENTRAL_INSTALL_COMMAND3</b>	



Parameter name	Parameter description
AUDIENCECENTRAL_INSTALL_COMMAND4	
AUDIENCECENTRAL_INSTALL_COMMAND5	
AUDIENCECENTRAL_INSTALL_COMMAND6	
AUDIENCECENTRAL_INSTALL_COMMAND7	
AUDIENCECENTRAL_INSTALL_COMMAND8	
AUDIENCECENTRAL_INSTALL_COMMAND9	
AUDIENCECENTRAL_INSTALL_COMMAND10	
AUDIENCECENTRAL_INSTALL_SCRIPT1	
AUDIENCECENTRAL_INSTALL_SCRIPT2	

## Campaign configurations

To configure Campaign for Cloud Native Unica, make the necessary modifications to the `campaign-configMap.yaml` file.

To access the `campaign-configMap.yaml` file, navigate to `/unica/templates/` in the Unica charts folder. Open the file and make modifications to the following parameters:

**Table 12. Common Campaign parameters**

Parameter name	Parameter description
CAMPAIGN_JNDI_NAME	JNDI name for Campaign.
CAMPAIGN_POOL_NAME	Pool name for Campaign.
PRODUCT_OPTS_CAMPAIGN	Product specific options for Campaign.
CAMPAIGN_PRODUCT_NAME	The name assigned for Campaign.
CAMPAIGN_WAR_NAME	The name of the <code>WAR</code> file.
CAMPAIGN_APPLICATION_NAME	The name of the main application. For example, <code>Unica</code> .
CAMPAIGN_DOMAIN_USERNAME	The domain username for Campaign.
CAMPAIGN_DOMAIN_PASSWORD	The domain password for Campaign.
USER_DB2_HOST_NAME	The host name of the DB2 user.
CAMP_MAX_HEADER_SIZE	The maximum size allowed for the header. For example, <code>8192</code> .

**Table 12. Common Campaign parameters (continued)**

Parameter name	Parameter description
WAR_SCRIPT_CAMPAIGN	The location of the WAR script for Campaign. <b>Example:</b> "/docker/unica/camp_deployment.sh"

**Table 13. Database-related parameters for Campaign**




Parameter name	Parameter description
CAMPAIGN_DATABASE_HOST	Host system details of the system hosting the Campaign database.
CAMPAIGN_DATABASE_PORT	Port number of the Campaign database.
CAMPAIGN_DATABASE_NAME	Name of the Campaign database.
CAMPAIGN_DATABASE_USERNAME	Username to access the Campaign database.
CAMPAIGN_DATABASE_PASSWORD	Password to access the Campaign database.
DB2_CLIENT_INSTALL_COMMAND	Command to install the DB2 client on listener pod.
DB2_CLIENT_INSTALL_COMMAND_SCRIPT	 <b>Note:</b> Use the scripts configured on Unica helm charts to install any other database clients automatically and seamlessly.  Path of the test scripts to install client on listener pod (/bin/sh/db2.sh).
DB2_SETUP_FILE	Path of the tar/gz file of client
DB2_RESPONSE_FILE	Path of response file to install client.
LD_LIB_PATH	Path to the required shared libraries in the environment configuration script, setenv.sh, for Campaign.
SETENV_COMMAND1	Setting the variables for setenv.sh in the listener you can provide the command.
SETENV_COMMAND2	Setting the variables for setenv.sh in the listener you can provide the command.
SETENV_COMMAND3	Setting the variables for setenv.sh in the listener you can provide the command.
SETENV_SCRIPT	The location of the set environment script. Example: /docker/unica/setenv_script.sh.
CAMPAIGN_DS_INITIAL_SIZE	The initial size of the Campaign datasource connection pool.

Table 13. Database-related parameters for Campaign (continued)

Parameter name	Parameter description
CAMPAIGN_DS_MIN_IDLE	The minimum number of idle connections (not connected to a database) in the Campaign datasource connection pool.
CAMPAIGN_DS_MAX_IDLE	The maximum number of idle connections (not connected to a database) in the Campaign datasource connection pool. Any idle connections, which exceeds the configured value, will be removed from the pool.
CAMPAIGN_DS_MAX_TOTAL	The maximum number of connections that the Campaign datasource can hold. If the number of connection requests exceed the configured value, the connection will be refused.
CAMPAIGN_DS_STATEMENT_CACHE_SIZE	Maximum number of statements that can be cached in the Campaign datasource. Statement caching improves performance by caching executable statements that are used repeatedly.
MARIADB_CLIENT_INSTALL_COMMAND	Command to install the MariaDB client on the listener pod.
MARIADB_CLIENT_INSTALL_SCRIPT	<p> <b>Note:</b> Use the scripts configured on Unica helm charts to install any other database clients automatically and seamlessly.</p> <p>Path of the test scripts to install database client on the listener pod (<code>/docker/unica/mariadb.sh</code>). You can write the set of command in this file to install the client and it is executed during the startup of the listener pod.</p> <p><b>Example</b></p> <pre>install /docker/unica/libmaodbc.so /usr/lib64/ yum install -y unixODBC yum install -y compat-openssl10</pre>
ORACLE_CLIENT_INSTALL_SCRIPT	<p> <b>Note:</b> Use the scripts configured on Unica helm charts to install any other database clients automatically and seamlessly.</p> <p>Path of the test scripts to install database client on the listener pod (<code>/docker/unica/oracle.sh</code>). You can write the set of command in this file to install the client and it is executed during the startup of the listener pod.</p>

**Table 13. Database-related parameters for Campaign (continued)**


Parameter name	Parameter description
	<p><b>Example</b></p> <pre>yum install -y libaio cp /usr/lib64/libnsl.so.2.0.0 /usr/lib64/libnsl.so.1</pre>
SQLSERVER_CLIENT_INSTALL_SCRIPT	<p> <b>Note:</b> Use the scripts configured on Unica helm charts to install any other database clients automatically and seamlessly.</p> <p>Path of the test scripts to install client on listener pod (/bin/sh/sqlserver.sh).</p>
USER_DB2_PORT	The port number to access the DB2 database.
USER_DB2_DB_NAME	The name of the DB2 database user.
USER_DB2_DB_USER	The username of the DB2 database user.
USER_DB2_DB_USER_PASSWORD	The password for the DB2 database user.
ASM_User_For_DB2_Credentials	The <code>asm_admin</code> credentials for DB2 datasource.
ASM_User_NZ_Data_Source_Name	The <code>asm_admin</code> user configured for the NZ datasource.
ASM_User_For_SQLSERVER_Credentials	The <code>asm_admin</code> credentials for SQL Server datasource.
ASM_User_SQLSERVER_Data_Source_Name	The <code>asm_admin</code> user configured for the SQL Server datasource.
ASM_User_DB2_Data_Source_Name	The <code>asm_admin</code> user configured for the DB2 datasource.
ASM_User_ORA_Data_Source_Name	The <code>asm_admin</code> user configured for the Oracle datasource.
ASM_User_For_ORA_Credentials	The <code>asm_admin</code> credentials for the Oracle datasource.
USER_ORA_DB_USERNAME	The username of the Oracle database user.
USER_ORA_DB_USER_PASSWORD	The password of the Oracle database user.
USER_ORA_PORT	The port number of the of the configured database user.
USER_ORA_SID	The SID details of the Oracle user.
ASM_User_NZ_Data_Source_Name	The <code>asm_admin</code> user configured for the NZ datasource.
ASM_User_For_NZ_Credentials	The <code>asm_admin</code> credentials for the NZ datasource.
USER_NZ_DB_USERNAME	The username of the NZ database user.
USER_NZ_DB_USER_PASSWORD	The password for the NZ database user.

Table 13. Database-related parameters for Campaign (continued)

Parameter name	Parameter description
USER_NZ_HOST_NAME	The host name of the NZ database user.
USER_NZ_PORT	The port number to access the NZ database.
USER_NZ_DB_NAME	The database name of the NZ database user.
USER_MARIA_HOST_NAME	The host name of the MariaDB database user.
USER_SQLSERVER_DB_NAME	The database name of the SQL Server database user.
USER_SQLSERVER_HOST_NAME	The host name of the SQL Server database user.
USER_SQLSERVER_PORT	The port number to access the SQL Server database.
USER_SQLSERVER_NAME	The host name of the SQL Server database user.
USER_SQLSERVER_USER	The username of the SQL Server database user.
CAMPAIGN_DSN_NAME	The <code>dbaname</code> value of the respective database.
ORACLE_ODBC_DRIVER	The path or the location of the Oracle ODBC driver on your system.
DB_TEMPLATE	The name of the database template used. This is used for configuring ODBC connection in Oracle.

Table 14. Application Server-related parameters for Campaign

Parameter name	Parameter description
CAMPAIGN_URL	The URL to access Campaign.
CAMP_HOST_NAME	The system host name of Campaign.
CAMP_MANAGEMENT_PORT	The management port number for the Campaign system.
CAMP_MANAGEMENT_HTTPS_PORT	The management HTTPS port number for the Campaign system.
CAMP_AJP_PORT	The AJP port number for the Campaign system.
CAMP_HTTP_PORT	The HTTP port number for the Campaign system.
CAMP_HTTPS_PORT	The HTTPS port number for the Campaign system.
CAMP_RECOVERY_ENV_PORT	The recovery environment port number of the Campaign system.
CAMP_STATUS_MANAGER_PORT	The status manager port number of the Campaign system.
CAMP_MIN_HEAP	The maximum heap size allocated for Campaign.

**Table 14. Application Server-related parameters for Campaign (continued)**

Parameter name	Parameter description
CAMP_MAX_HEAP	The maximum heap size allocated for Campaign.

**Table 15. Listener-related parameters for Campaign**

Parameter name	Parameter description
LISTENER_HOST_NAME	The hostname of the Listener.
LISTENER_PORT	The port number of the Listener.
LISTENER_TYPE	Specify the type of Listener.
CLUSTER_DOMAIN	Define the cluster domain. For example, <code>listener.default.svc.cluster.local</code> .
SSL_FOR_PORT2	SSL server port 2.
SERVER_PORT2	Server port 2.
MASTER_LISTENER_PRIORITY	Define the Listener priority.
LOAD_BALANCE_WEIGHT	The load balance weight of the Listener.
CAMP_HOSTNAME	The host name of the Campaign system.
CAMPPORT	The deployment port for Campaign.
CLUSTER_DEPLOYMENT	Set <code>TRUE</code> if clustered deployment is supported or <code>FALSE</code> if clustered deployment is not supported.
ORACLE_CLIENT_SETUP_FILE_EXTRACT_COMMAND	The command to extract the Oracle <code>tar/gz</code> client setup file
DB2_CLIENT_SETUP_FILE_EXTRACT_COMMAND	The command to extract the DB2 <code>tar/gz</code> client setup file
SETENV_SCRIPT	The command to set the environment. <code>setenv_script.sh</code> .

**Multicast parameters for Campaign**

Parameter name	Parameter description
CAMPAIGN_MULTICAST	<b>Example:</b> <code>"{{ .Values.campaignMultiCastData.CAMPAIGN_MULTICAST }}"</code>
CAMPAIGN_MULTICAST_HOST	<b>Example:</b> <code>"{{ .Values.campaignMultiCastData.CAMPAIGN_MULTICAST_HOST }}"</code>

Parameter name	Parameter description
CAMPAIGN_MULTICAST_PORT	<b>Example:</b> <pre>"{{ .Values.campaignMultiCastData.CAMPAIGN_MULTICAST_PORT   }}"</pre>

### Installation parameters for Campaign

Parameter name	Parameter description
CAMPAIGN_INSTALL_COMMAND1	Parameters used for Installation commands and scripts that can be used for customization.
CAMPAIGN_INSTALL_COMMAND2	
CAMPAIGN_INSTALL_COMMAND3	
CAMPAIGN_INSTALL_COMMAND4	
CAMPAIGN_INSTALL_COMMAND5	
CAMPAIGN_INSTALL_COMMAND6	
CAMPAIGN_INSTALL_COMMAND7	
CAMPAIGN_INSTALL_COMMAND8	
CAMPAIGN_INSTALL_COMMAND9	
CAMPAIGN_INSTALL_COMMAND10	
CAMPAIGN_INSTALL_SCRIPT1	
CAMPAIGN_INSTALL_SCRIPT2	

## Centralized Offer Management configurations

To configure Centralized Offer Management for Cloud Native Unica, make the necessary modifications to the `offer-configMap.yaml` file.

To access the `offer-configMap.yaml` file, navigate to `/unica/templates/` in the Unica charts folder. Open the file and make modifications to the following parameters:

**Table 16. Application server-related parameters of Centralized Offer Management**

Parameter name	Parameter definition
COM_HOST_NAME	The system host name of Centralized Offer Management.
COM_MANAGEMENT_PORT	The management port number for the Centralized Offer Management system.

**Table 16. Application server-related parameters of Centralized Offer Management (continued)**

Parameter name	Parameter definition
COM_MANAGEMENT_HTTPS_PORT	The management <code>HTTPS</code> port number for the Centralized Offer Management system.
COM_AJP_PORT	The <code>AJP</code> port number for the Centralized Offer Management system.
COM_HTTP_PORT	The <code>HTTP</code> port number for the Centralized Offer Management system.
COM_HTTPS_PORT	The <code>HTTPS</code> port number for the Centralized Offer Management system.
COM_RECOVERY_ENV_PORT	The recovery environment port number of the Centralized Offer Management system.
COM_STATUS_MANAGER_PORT	The status manager port number of the Centralized Offer Management system.
COM_MIN_HEAP	The minimum heap size allocated for Centralized Offer Management.
COM_MAX_HEAP	The maximum heap size allocated for Centralized Offer Management.
WAR_SCRIPT_OFFER	The location of the WAR script for Centralized Offer Management. <b>Example:</b> "/docker/unica/offer_deployment.sh"
Offer_URL	<b>Example:</b> <code>"{{ include "ip.protocol" . }}://{{ .Values.service.hostname }}/Offer"</code>

**Table 17. Common parameters of Centralized Offer Management**

Parameter name	Parameter description
PRODUCT_OPTS_COM	Product specific options for Centralized Offer Management.
COM_PRODUCT_NAME	The name assigned for Centralized Offer Management.
CENTRALIZED_OFFERS_WAR_NAME	The name of the <code>WAR</code> file.
COM_APPLICATION_NAME	The name of the main application. For example, <code>Unica</code> .
COM_DOMAIN_USERNAME	The domain username for Centralized Offer Management.
COM_DOMAIN_PASSWORD	The domain password for Centralized Offer Management.



## Installation parameters for Centralized Offer Management

Parameter name	Parameter description
OFFER_INSTALL_COMMAND1	Parameters used for Installation commands and scripts that can be used for customization.
OFFER_INSTALL_COMMAND2	
OFFER_INSTALL_COMMAND3	
OFFER_INSTALL_COMMAND4	
OFFER_INSTALL_COMMAND5	
OFFER_INSTALL_COMMAND6	
OFFER_INSTALL_COMMAND7	
OFFER_INSTALL_COMMAND8	
OFFER_INSTALL_COMMAND9	
OFFER_INSTALL_COMMAND10	
OFFER_INSTALL_SCRIPT1	
OFFER_INSTALL_SCRIPT2	

## Collaborate configurations

To configure the Collaborate for Cloud Native Unica, make the necessary modifications to the `collaborate-configMap.yaml` file.

To access the `collaborate-configMap.yaml` file, navigate to `/unica/templates/` in the Unica charts folder. Open the file and make modifications to the following parameters:

**Table 18. Common parameters of Collaborate configuration**

Parameter name	Parameter description
COLLABORATE_HOST	The name of the Collaborate host system.
COLLABORATE_PORT	The port number of the Collaborate host system.
COLLABORATE_JNDI_NAME	JNDI name for Collaborate.
COLLABORATE_POOL_NAME	Pool name for Collaborate.
COLLABORATE_USER_JNDI_NAME	JNDI name for the Collaborate user.
COLLABORATE_USER_POOL_NAME	Pool name for the Collaborate user.

**Table 18. Common parameters of Collaborate configuration (continued)**

Parameter name	Parameter description
<b>PRODUCT_OPTS_COLLABORATE</b>	Product-specific options for Collaborate.
<b>COLLABORATE_PRODUCT_NAME</b>	The name assigned for Collaborate.
<b>COLLABORATE_WAR_NAME</b>	The name of the <code>WAR</code> file.
<b>COLLABORATE_APPLICATION_NAME</b>	The name of the main application. For example, <code>Unica</code> .
<b>COLLABORATE_DOMAIN_USERNAME</b>	The domain username for Collaborate.
<b>COLLABORATE_DOMAIN_PASSWORD</b>	The domain password for Collaborate.
<b>COLLABORATE_HOME</b>	The home directory for the Collaborate system.

**Table 19. Database parameters of Collaborate configuration**

Parameter name	Parameter description
<b>COLLABORATE_DATABASE_HOST</b>	Host system details of the system hosting the Collaborate database.
<b>COLLABORATE_DATABASE_PORT</b>	Port number of the Collaborate database.
<b>COLLABORATE_DATABASE_USERNAME</b>	Username to access the Collaborate database.
<b>COLLABORATE_DATABASE_PASSWORD</b>	Password to access the Collaborate database.
<b>COLLABORATE_DATABASE_NAME</b>	Name of the Collaborate database.
<b>COLLABORATE_USER_DATABASE_HOST</b>	Host system details of the system hosting the Collaborate database user.
<b>COLLABORATE_USER_DATABASE_PORT</b>	Port number of the Collaborate database user.
<b>COLLABORATE_USER_DATABASE_USERNAME</b>	Username to access the Collaborate database user.
<b>COLLABORATE_USER_DATABASE_PASSWORD</b>	Password to access the Collaborate database user.
<b>COLLABORATE_USER_DATABASE_NAME</b>	Name of the Collaborate database user.
<b>COLLABORATE_DS_INITIAL_SIZE</b>	The initial size of the Collaborate datasource connection pool.
<b>COLLABORATE_DS_MIN_IDLE</b>	The minimum number of idle connections (not connected to a database) in the Collaborate datasource connection pool.
<b>COLLABORATE_DS_MAX_IDLE</b>	The maximum number of idle connections (not connected to a database) in the Collaborate datasource connection pool. Any idle connections, which exceeds the configured value, will be removed from the pool.

Table 19. Database parameters of Collaborate configuration (continued)

Parameter name	Parameter description
<b>COLLABORATE_DS_MAX_TOTAL</b>	The maximum number of connections that the Collaborate datasource can hold. If the number of connection requests exceed the configured value, the connection will be refused.
<b>COLLABORATE_DS_STATEMENT_CACHE_SIZE</b>	Maximum number of statements that can be cached in the Collaborate datasource. Statement caching improves performance by caching executable statements that are used repeatedly.
<b>COLLABORATE_USER_DS_INITIAL_SIZE</b>	The initial size of the Collaborate user datasource connection pool.
<b>COLLABORATE_USER_DS_MIN_IDLE</b>	The minimum number of idle connections (not connected to a database) in the Collaborate user datasource connection pool.
<b>COLLABORATE_USER_DS_MAX_IDLE</b>	The maximum number of idle connections (not connected to a database) in the Collaborate user datasource connection pool. Any idle connections, which exceeds the configured value, will be removed from the pool.
<b>COLLABORATE_USER_DS_MAX_TOTAL</b>	The maximum number of connections that the Collaborate user datasource can hold. If the number of connection requests exceed the configured value, the connection will be refused.
<b>COLLABORATE_USER_DS_STATEMENT_CACHE_SIZE</b>	Maximum number of statements that can be cached in the Collaborate user datasource. Statement caching improves performance by caching executable statements that are used repeatedly.

Table 20. Application server parameters of Collaborate configuration

Parameter name	Parameter description
<b>COLLABORATE_URL</b>	The <code>URL</code> to access Collaborate.
<b>COLLABORATE_HOST_NAME</b>	The system host name of Collaborate.
<b>COLLABORATE_MANAGEMENT_PORT</b>	The management port number for the Collaborate system.
<b>COLLABORATE_MANAGEMENT_HTTPS_PORT</b>	The management <code>HTTPS</code> port number for the Collaborate system.
<b>COLLABORATE_AJP_PORT</b>	The <code>AJP</code> port number for the Collaborate system.

**Table 20. Application server parameters of Collaborate configuration (continued)**

Parameter name	Parameter description
COLLABORATE_HTTP_PORT	The <code>HTTP</code> port number for the Collaborate system.
COLLABORATE_HTTPS_PORT	The <code>HTTPS</code> port number for the Collaborate system.
COLLABORATE_RECOVERY_ENV_PORT	The recovery environment port number of the Collaborate system.
COLLABORATE_STATUS_MANAGER_PORT	The status manager port number of the Collaborate system.
COLLABORATE_MIN_HEAP	The maximum heap size allocated for Collaborate.
COLLABORATE_MAX_HEAP	The maximum heap size allocated for Collaborate.

### Installation parameters for Collaborate

Parameter name	Parameter description
COLLABORATE_INSTALL_COMMAND1	Parameters used for Installation commands and scripts that can be used for customization.
COLLABORATE_INSTALL_COMMAND2	
COLLABORATE_INSTALL_COMMAND3	
COLLABORATE_INSTALL_COMMAND4	
COLLABORATE_INSTALL_COMMAND5	
COLLABORATE_INSTALL_COMMAND6	
COLLABORATE_INSTALL_COMMAND7	
COLLABORATE_INSTALL_COMMAND8	
COLLABORATE_INSTALL_COMMAND9	
COLLABORATE_INSTALL_COMMAND10	
COLLABORATE_INSTALL_SCRIPT1	
COLLABORATE_INSTALL_SCRIPT2	

## Contact Central configurations

To configure Contact Central for Cloud Native Unica, make the necessary modifications to the `contactcentral-configMap.yaml` file.

To access the `contactcentral-configMap.yaml` file, navigate to `/unica/templates/` in the Unica charts folder. Open the file and make modifications to the following parameters:

**Table 21. Common Contact Central parameters**

Parameter name	Parameter description
<code>CONTACTCENTRAL_JNDI_NAME</code>	JNDI name for Contact Central.
<code>CONTACTCENTRAL_POOL_NAME</code>	Pool name for Contact Central.
<code>CONTACTCENTRAL_URL</code>	The URL to access Contact Central.
<code>CONTACTCENTRAL_INTERNAL_URL</code>	The internal URL to access/link Contact Central from other applications.
<code>PRODUCT_OPTS_CONTACTCENTRAL</code>	Product specific options for Contact Central.
<code>CONTACTCENTRAL_PRODUCT_NAME</code>	The name assigned for Contact Central.
<code>CONTACT_CENTRAL_WAR_NAME</code>	The name of the <code>WAR</code> file.
<code>CONTACTCENTRAL_APPLICATION_NAME</code>	The name of the main application. For example, <code>Unica</code> .
<code>CONTACTCENTRAL_DOMAIN_USERNAME</code>	The domain username for Contact Central.
<code>CONTACTCENTRAL_DOMAIN_PASSWORD</code>	The domain password for Contact Central.

**Table 22. Database-related parameters for Contact Central**

Parameter name	Parameter description
<code>CONTACTCENTRAL_DATABASE_HOST</code>	Host system details of the system hosting the Contact Central database.
<code>CONTACTCENTRAL_DATABASE_PORT</code>	Port number of the Contact Central database.
<code>CONTACTCENTRAL_DATABASE_USERNAME</code>	Username to access the Contact Central database.
<code>CONTACTCENTRAL_DATABASE_PASSWORD</code>	Password to access the Contact Central database.
<code>CONTACTCENTRAL_DATABASE_NAME</code>	Name of the Contact Central database.
<code>CONTACTCENTRAL_DS_INITIAL_SIZE</code>	The initial size of the Contact Central datasource connection pool.
<code>CONTACTCENTRAL_DS_MIN_IDLE</code>	The minimum number of idle connections (not connected to a database) in the Contact Central datasource connection pool.
<code>CONTACTCENTRAL_DS_MAX_IDLE</code>	The maximum number of idle connections (not connected to a database) in the Contact Central datasource connection pool. Any idle connections, which exceeds the configured value, will be removed from the pool.

**Table 22. Database-related parameters for Contact Central (continued)**

Parameter name	Parameter description
<b>CONTACTCENTRAL_DS_MAX_TOTAL</b>	The maximum number of connections that the Contact Central datasource can hold. If the number of connection requests exceed the configured value, the connection will be refused.
<b>CONTACTCENTRAL_DS_STATEMENT_CACHE_SIZE</b>	Maximum number of statements that can be cached in the Contact Central datasource. Statement caching improves performance by caching executable statements that are used repeatedly.

**Table 23. Application Server-related parameters for Contact Central**

Parameter name	Parameter description
<b>CONTACTCENTRAL_HOST_NAME</b>	The system host name of Contact Central.
<b>CONTACTCENTRAL_MANAGEMENT_PORT</b>	The management port number for the Contact Central system.
<b>CONTACTCENTRAL_MANAGEMENT_HTTPS_PORT</b>	The management HTTPS port number for the Contact Central system.
<b>CONTACTCENTRAL_AJP_PORT</b>	The AJP port number for the Contact Central system.
<b>CONTACTCENTRAL_HTTP_PORT</b>	The HTTP port number for the Contact Central system.
<b>CONTACTCENTRAL_HTTPS_PORT</b>	The HTTPS port number for the Contact Central system.
<b>CONTACTCENTRAL_RECOVERY_ENV_PORT</b>	The recovery environment port number of the Contact Central system.
<b>CONTACTCENTRAL_STATUS_MANAGER_PORT</b>	The status manager port number of the Contact Central system.
<b>CONTACTCENTRAL_MIN_HEAP</b>	The maximum heap size allocated for Contact Central.
<b>CONTACTCENTRAL_MAX_HEAP</b>	The maximum heap size allocated for Contact Central.
<b>FORCE_INIT_TOMCAT</b>	Set whether you want to force initialize Apache Tomcat. <code>TRUE</code> to activate for initialization and <code>FALSE</code> to deactivate force initialization.
<b>TOMCAT_SHUTDOWN_PORT</b>	The <code>TCP/IP</code> port number of the Apache Tomcat server waiting for a shutdown command.
<b>TOMCAT_MAX_EXECUTOR_THREADS</b>	The maximum number of threads (based on the <code>maxThreads</code> property of Apache Tomcat) used for <code>HTTP</code> connections.

**Table 23. Application Server-related parameters for Contact Central (continued)**

Parameter name	Parameter description
<b>TOMCAT_MIN_EXECUTOR_THREADS</b>	The minimum number of threads (based on the <code>minSpareThreads</code> property of Apache Tomcat) that is always present in the thread pool.
<b>TOMCAT_REDIRECT_PORT</b>	The redirect port number ( <code>redirectPort</code> property) of the Apache Tomcat server handling <code>SSL</code> connections.

**Installation parameters for Contact Central**

Parameter name	Parameter description
<b>CONTACTCENTRAL_INSTALL_COMMAND1</b>	Parameters used for Installation commands and scripts that can be used for customization.
<b>CONTACTCENTRAL_INSTALL_COMMAND2</b>	
<b>CONTACTCENTRAL_INSTALL_COMMAND3</b>	
<b>CONTACTCENTRAL_INSTALL_COMMAND4</b>	
<b>CONTACTCENTRAL_INSTALL_COMMAND5</b>	
<b>CONTACTCENTRAL_INSTALL_COMMAND6</b>	
<b>CONTACTCENTRAL_INSTALL_COMMAND7</b>	
<b>CONTACTCENTRAL_INSTALL_COMMAND8</b>	
<b>CONTACTCENTRAL_INSTALL_COMMAND9</b>	
<b>CONTACTCENTRAL_INSTALL_COMMAND10</b>	
<b>CONTACTCENTRAL_INSTALL_SCRIPT1</b>	
<b>CONTACTCENTRAL_INSTALL_SCRIPT2</b>	

## Content Integration configurations

To configure Content Integration for Cloud Native Unica, make the necessary modifications to the `assetpicker-configMap.yaml` file.

To access the `assetpicker-configMap.yaml` file, navigate to `/unica/templates/` in the Unica charts folder. Open the file and make modifications to the following parameters:

**Table 24. Application server-related parameters of Content Integration**

Parameter name	Parameter description
ASSET_HOST_NAME	The system host name of Content Integration.
ASSET_MANAGEMENT_PORT	The management port number for the Content Integration system.
ASSET_MANAGEMENT_HTTPS_PORT	The management <code>HTTPS</code> port number for the Content Integration system.
ASSET_AJP_PORT	The <code>AJP</code> port number for the Content Integration system.
ASSET_HTTP_PORT	The <code>HTTP</code> port number for the Content Integration system.
ASSET_HTTPS_PORT	The <code>HTTPS</code> port number for the Content Integration system.
ASSET_RECOVERY_ENV_PORT	The recovery environment port number of the Content Integration system.
ASSET_STATUS_MANAGER_PORT	The status manager port number of the Content Integration system.
PRODUCT_OPTS_ASSET	Product specific options for Content Integration.

**Installation parameters for Content Integration**

Parameter name	Parameter description
CONTENTINTEGRATION_INSTALL_COMMAND1	Parameters used for Installation commands and scripts that can be used for customization.
CONTENTINTEGRATION_INSTALL_COMMAND2	
CONTENTINTEGRATION_INSTALL_COMMAND3	
CONTENTINTEGRATION_INSTALL_COMMAND4	
CONTENTINTEGRATION_INSTALL_COMMAND5	
CONTENTINTEGRATION_INSTALL_COMMAND6	
CONTENTINTEGRATION_INSTALL_COMMAND7	
CONTENTINTEGRATION_INSTALL_COMMAND8	
CONTENTINTEGRATION_INSTALL_COMMAND9	
CONTENTINTEGRATION_INSTALL_COMMAND10	
CONTENTINTEGRATION_INSTALL_SCRIPT1	



Parameter name	Parameter description
CONTENTINTEGRATION_INSTALL_SCRIPT2	

## Director configurations

To configure Director for Cloud Native Unica, make the necessary modifications to the `director-configMap.yaml` file.

To access the `director-configMap.yaml` file, navigate to `/unica/templates/` in the Unica charts folder. Open the file and make modifications to the following parameters:

**Table 25. Common parameters of Director**

Parameter name	Parameter description
<code>activemq_enableEvents</code>	Valid values are Yes Or No.
<code>activemq_url</code>	Active MQ URL. For example, <code>tcp://unica-omnix-unica-activemq:61616</code> .
<code>Data_Source_For_ActiveMQ_message_broker_credentials</code>	Data source for <code>ACTIVEMQ</code> . For example, <code>ACTIVEMQ_CRED_DS</code> .
<code>data_sources_for_activemq</code>	Platform username.
<code>activemq_queueName</code>	Flowchart information. For example, <code>campaign</code> .

**Table 26. Configuration parameters of Director**

Parameter name	Parameter description
<code>director_http_port</code>	Director server port. The default port is <code>9128</code> .
<code>director_file_down</code>	The download path used to store the downloaded log files from the Campaign server. For example, <code>/docker/unica/Director/Server/Downloads</code> .
<code>director_show_sql</code>	Valid values are <code>TRUE OR FALSE</code> .
<code>director_accesstoken_validityseconds</code>	Director application session timed out token. For example, <code>10800</code> seconds.
<code>director_listener_profile_data_days</code>	Campaign listener CPU and Memory consumption data retention to <code>7</code> Days.

**Table 27. Database-related parameters of Director**

Parameter name	Parameter description
<code>director_db_name</code>	Director DB name.
<code>director_datasource_username</code>	Director database name or username.

**Table 27. Database-related parameters of Director (continued)**

Parameter name	Parameter description
<code>director_datasource_password</code>	Director database password.
<code>director_db_host_ip</code>	Director database machine host IP address.
<code>director_host_name</code>	Director database machine host name.
<code>director_db_port</code>	Director database machine port number.
<code>director_datasource_driverClassName</code>	Database driver class name.
<code>director_jpa_hibernate</code>	Database driver dialect name.
<code>director_ddl_auto</code>	Director database mode like create, update, or validate.
<code>director_db_url</code>	Director database URL.

**Installation parameters for Director**

Parameter name	Parameter description
<code>DIRECTOR_INSTALL_COMMAND1</code>	Parameters used for Installation commands and scripts that can be used for customization.
<code>DIRECTOR_INSTALL_COMMAND2</code>	
<code>DIRECTOR_INSTALL_COMMAND3</code>	
<code>DIRECTOR_INSTALL_COMMAND4</code>	
<code>DIRECTOR_INSTALL_COMMAND5</code>	
<code>DIRECTOR_INSTALL_COMMAND6</code>	
<code>DIRECTOR_INSTALL_COMMAND7</code>	
<code>DIRECTOR_INSTALL_COMMAND8</code>	
<code>DIRECTOR_INSTALL_COMMAND9</code>	
<code>DIRECTOR_INSTALL_COMMAND10</code>	
<code>DIRECTOR_INSTALL_SCRIPT1</code>	
<code>DIRECTOR_INSTALL_SCRIPT2</code>	

## Insights Reports configurations

To configure Insights Reports for Cloud Native Unica, make the necessary modifications to the `birt-configMap.yaml` file.

To access the `birt-configMap.yaml` file, navigate to `/unica/templates/` in the Unica charts folder. Open the file and make modifications to the following parameters:

Update the following configurations:

- configurations at Affinium | Plan | `umoConfiguration` | reports.
- `reportsAnalysisSectionHome` - Plan/Affinium Plan
- `reportsAnalysisTabHome` - Plan/Affinium Plan - Object Specific Reports

After updating the configurations, restart the pods for Plan and Insights Reports.

**Table 28. Common Insights Reports parameters**

Parameter name	Parameter description
<code>INSIGHTS_PRODUCT_NAME</code>	The name assigned for Insights Reports.
<code>INSIGHTS_WAR_NAME</code>	The name of the <code>WAR</code> file.
<code>INSIGHTS_APPLICATION_NAME</code>	The name of the main application. For example, <code>Unica</code> .
<code>INSIGHTS_DOMAIN_USERNAME</code>	The domain username for Insights Reports.
<code>INSIGHTS_DOMAIN_PASSWORD</code>	The domain password for Insights Reports.
<code>PRODUCT_OPTS_INSIGHTS</code>	Product specific options for Insights Reports.

**Table 29. Application server-related Insights Reports parameters**

Parameter name	Parameter description
<code>INSIGHTS_HOST_NAME</code>	The system host name of Insights Reports.
<code>INSIGHTS_MANAGEMENT_PORT</code>	The management port number for the Insights Reports system.
<code>INSIGHTS_MANAGEMENT_HTTPS_PORT</code>	The management <code>HTTPS</code> port number for the Insights Reports system.
<code>INSIGHTS_AJP_PORT</code>	The <code>AJP</code> port number for the Insights Reports system.
<code>INSIGHTS_HTTP_PORT</code>	The <code>HTTP</code> port number for the Insights Reports system.
<code>INSIGHTS_HTTPS_PORT</code>	The <code>HTTPS</code> port number for the Insights Reports system.
<code>INSIGHTS_RECOVERY_ENV_PORT</code>	The recovery environment port number of the Insights Reports system.
<code>INSIGHTS_STATUS_MANAGER_PORT</code>	The status manager port number of the Insights Reports system.
<code>INSIGHTS_MIN_HEAP</code>	The minimum heap size allocated for Insights Reports.

**Table 29. Application server-related Insights Reports parameters (continued)**

Parameter name	Parameter description
INSIGHTS_MAX_HEAP	The maximum heap size allocated for Insights Reports.

**Installation parameters for Unica Insights Reports**

Parameter name	Parameter description
INSIGHTS_INSTALL_COMMAND1	Parameters used for Installation commands and scripts that can be used for customization.
INSIGHTS_INSTALL_COMMAND2	
INSIGHTS_INSTALL_COMMAND3	
INSIGHTS_INSTALL_COMMAND4	
INSIGHTS_INSTALL_COMMAND5	
INSIGHTS_INSTALL_COMMAND6	
INSIGHTS_INSTALL_COMMAND7	
INSIGHTS_INSTALL_COMMAND8	
INSIGHTS_INSTALL_COMMAND9	
INSIGHTS_INSTALL_COMMAND10	
INSIGHTS_INSTALL_SCRIPT1	
INSIGHTS_INSTALL_SCRIPT2	

## Interact configurations

To configure Interact for Cloud Native Unica, make the necessary modifications to the `interact-configMap.yaml` file.

To access the `interact-configMap.yaml` file, navigate to `/unica/templates/` in the Unica charts folder. Open the file and make modifications to the following parameters:

**Table 30. Common parameters for Interact**

Parameter name	Parameter description
CONTEXT_ROOTS	To enable multiple server groups in Interact. Ensure that the context root and deployment name are in sync. If you change the deployment name, remember to change the context root as well. For example, if server groups are named atm, callcenter, and web, define the deployment

Table 30. Common parameters for Interact (continued)

Parameter name	Parameter description
	and services with similar names like interactatm, interactcallcenter, and interactweb and ensure that the <b>CONTEXT_ROOT</b> parameter contains the following values: <code>INTERACTATM; INTERACTCALLCENTER; INTERACTWEB.</code>
<b>INTERACT_PROD_JNDI_NAME</b>	JNDI name for Interact production.
<b>INTERACT_PROD_POOL_NAME</b>	Pool name for Interact production.
<b>INTERACT_TEST_JNDI_NAME</b>	JNDI name for Interact test.
<b>INTERACT_TEST_POOL_NAME</b>	Pool name for Interact test.
<b>INTERACT_LEARNING_JNDI_NAME</b>	JNDI name for Interact learning.
<b>INTERACT_LEARNING_POOL_NAME</b>	Pool name for Interact learning.
<b>INTERACT_CHRH_JNDI_NAME</b>	JNDI name for Interact CHRH.
<b>INTERACT_CHRH_POOL_NAME</b>	Pool name for Interact CHRH.
<b>INTERACT05_JNDI_NAME</b>	JNDI name for Interact05.
<b>INTERACT05_POOL_NAME</b>	Pool name for Interact05.
<b>INTERACTATM_JNDI_NAME</b>	JNDI name for Interact ATM.
<b>INTERACTATM_POOL_NAME</b>	Pool name for Interact ATM.
<b>INTERACTCALLCNTR_JNDI_NAME</b>	JNDI name for Interact Call Center.
<b>INTERACTCALLCNTR_POOL_NAME</b>	Pool name for Interact Call Center.
<b>INTERACTWEB_JNDI_NAME</b>	JNDI name for Interact Web.
<b>INTERACTWEB_POOL_NAME</b>	Pool name for Interact Web.
<b>PRODUCT_OPTS_INTERACT</b>	Product specific options for Interact.
<b>TERM</b>	The database host name.
<b>INTERACT_PRODUCT_NAME</b>	The name assigned for Interact.
<b>INTERACT_WAR_NAME</b>	The name of the <code>WAR</code> file.
<b>INTERACT_APPLICATION_NAME</b>	The name of the main application. For example, <code>Unica</code> .
<b>INTERACT_DOMAIN_USERNAME</b>	The domain username for Interact.
<b>INTERACT_DOMAIN_PASSWORD</b>	The domain password for Interact.

**Table 31. Platform server-related parameters of Interact**

Parameter name	Parameter description
<b>INTERACTATM_PLATFORM_DATABASE_HOST</b>	Host system details of the system hosting the Platform-Interact ATM database.
<b>INTERACTATM_PLATFORM_DATABASE_PORT</b>	Port number of the Platform-Interact ATM database.
<b>INTERACTATM_PLATFORM_DATABASE_USERNAME</b>	Username to access the Platform-Interact ATM database.
<b>INTERACTATM_PLATFORM_DATABASE_PASSWORD</b>	Password to access the Platform-Interact ATM database.
<b>INTERACTATM_PLATFORM_DATABASE_NAME</b>	Name of the Interact Platform-Interact database.
<b>INTERACTATM_PLATFORM_DS_INITIAL_SIZE</b>	The initial size of the Platform-Interact ATM datasource connection pool.
<b>INTERACTATM_PLATFORM_DS_MIN_IDLE</b>	The minimum number of idle connections (not connected to a database) in the Platform-Interact ATM datasource connection pool.
<b>INTERACTATM_PLATFORM_DS_MAX_IDLE</b>	The maximum number of idle connections (not connected to a database) in the Platform-Interact ATM datasource connection pool. Any idle connections, which exceeds the configured value, will be removed from the pool.
<b>INTERACTATM_PLATFORM_DS_MAX_TOTAL</b>	The maximum number of connections that the Platform-Interact ATM datasource can hold. If the number of connection requests exceed the configured value, the connection will be refused.
<b>INTERACTATM_PLATFORM_DS_STATEMENT_CACHE_SIZE</b>	Maximum number of statements that can be cached in the Platform-Interact ATM datasource. Statement caching improves performance by caching executable statements that are used repeatedly.

**Table 32. Server group-related database parameters of Interact**

Parameter name	Parameter description
<b>INTERACTATM_DATABASE_HOST</b>	Host system details of the system hosting the Interact ATM database.
<b>INTERACTATM_DATABASE_PORT</b>	Port number of the Interact ATM database.
<b>INTERACTATM_DATABASE_USERNAME</b>	Username to access the Interact ATM database.
<b>INTERACTATM_DATABASE_PASSWORD</b>	Password to access the Interact ATM database.
<b>INTERACTATM_DATABASE_NAME</b>	Name of the Interact ATM database.

Table 32. Server group-related database parameters of Interact (continued)

Parameter name	Parameter description
<b>INTERACTATM_DS_INITIAL_SIZE</b>	The initial size of the Interact ATM datasource connection pool.
<b>INTERACTATM_DS_MIN_IDLE</b>	The minimum number of idle connections (not connected to a database) in the Interact ATM datasource connection pool.
<b>INTERACTATM_DS_MAX_IDLE</b>	The maximum number of idle connections (not connected to a database) in the Interact ATM datasource connection pool. Any idle connections, which exceeds the configured value, will be removed from the pool.
<b>INTERACTATM_DS_MAX_TOTAL</b>	The maximum number of connections that the Interact ATM datasource can hold. If the number of connection requests exceed the configured value, the connection will be refused.
<b>INTERACTATM_DS_STATEMENT_CACHE_SIZE</b>	Maximum number of statements that can be cached in the Interact ATM datasource. Statement caching improves performance by caching executable statements that are used repeatedly.
<b>INTERACTWEB_DATABASE_HOST</b>	Host system details of the system hosting the Interact Web database.
<b>INTERACTWEB_DATABASE_PORT</b>	Port number of the Interact Web database.
<b>INTERACTWEB_DATABASE_USERNAME</b>	Username to access the Interact Web database.
<b>INTERACTWEB_DATABASE_PASSWORD</b>	Password to access the Interact Web database.
<b>INTERACTWEB_DATABASE_NAME</b>	Name of the Interact Web database.
<b>INTERACTWEB_DS_INITIAL_SIZE</b>	The initial size of the Interact Web datasource connection pool.
<b>INTERACTWEB_DS_MIN_IDLE</b>	The minimum number of idle connections (not connected to a database) in the Interact Web datasource connection pool.
<b>INTERACTWEB_DS_MAX_IDLE</b>	The maximum number of idle connections (not connected to a database) in the Interact Web datasource connection pool. Any idle connections, which exceeds the configured value, will be removed from the pool.
<b>INTERACTWEB_DS_MAX_TOTAL</b>	The maximum number of connections that the Interact Web datasource can hold. If the number of connection requests exceed the configured value, the connection will be refused.

**Table 32. Server group-related database parameters of Interact (continued)**

Parameter name	Parameter description
<b>INTERACTWEB_DS_STATEMENT_CACHE_SIZE</b>	Maximum number of statements that can be cached in the Interact Web datasource. Statement caching improves performance by caching executable statements that are used repeatedly.
<b>INTERACTCALLCNTR_DATABASE_HOST</b>	Host system details of the system hosting the Interact Call Center database.
<b>INTERACTCALLCNTR_DATABASE_PORT</b>	Port number of the Interact Call Center database.
<b>INTERACTCALLCNTR_DATABASE_USERNAME</b>	Username to access the Interact Call Center database.
<b>INTERACTCALLCNTR_DATABASE_PASSWORD</b>	Password to access the Interact Call Center database.
<b>INTERACTCALLCNTR_DATABASE_NAME</b>	Name of the Interact Call Center database.
<b>INTERACTCALLCNTR_DS_INITIAL_SIZE</b>	The initial size of the Interact Call Center datasource connection pool.
<b>INTERACTCALLCNTR_DS_MIN_IDLE</b>	The minimum number of idle connections (not connected to a database) in the Interact Call Center datasource connection pool.
<b>INTERACTCALLCNTR_DS_MAX_IDLE</b>	The maximum number of idle connections (not connected to a database) in the Interact Call Center datasource connection pool. Any idle connections, which exceeds the configured value, will be removed from the pool.
<b>INTERACTCALLCNTR_DS_MAX_TOTAL</b>	The maximum number of connections that the Interact Call Center datasource can hold. If the number of connection requests exceed the configured value, the connection will be refused.
<b>INTERACTCALLCNTR_DS_STATEMENT_CACHE_SIZE</b>	Maximum number of statements that can be cached in the Interact Call Center datasource. Statement caching improves performance by caching executable statements that are used repeatedly.

**Table 33. Server-related database parameters of Interact**

Parameter name	Parameter description
<b>INTERACT_PROD_DATABASE_HOST</b>	Host system details of the system hosting the Interact Production database.
<b>INTERACT_PROD_DATABASE_PORT</b>	Port number of the Interact Production database.



Table 33. Server-related database parameters of Interact (continued)

Parameter name	Parameter description
<b>INTERACT_PROD_DATABASE_NAME</b>	Username to access the Interact Production database.
<b>INTERACT_PROD_DATABASE_USERNAME</b>	Password to access the Interact Production database.
<b>INTERACT_PROD_DATABASE_PASSWORD</b>	Name of the Interact Production database.
<b>INTERACT_PROD_DS_INITIAL_SIZE</b>	The initial size of the Interact Production datasource connection pool.
<b>INTERACT_PROD_DS_MIN_IDLE</b>	The minimum number of idle connections (not connected to a database) in the Interact Production datasource connection pool.
<b>INTERACT_PROD_DS_MAX_IDLE</b>	The maximum number of idle connections (not connected to a database) in the Interact Production datasource connection pool. Any idle connections, which exceeds the configured value, will be removed from the pool.
<b>INTERACT_PROD_DS_MAX_TOTAL</b>	The maximum number of connections that the Interact Production datasource can hold. If the number of connection requests exceed the configured value, the connection will be refused.
<b>INTERACT_PROD_DS_STATEMENT_CACHE_SIZE</b>	Maximum number of statements that can be cached in the Interact Production datasource. Statement caching improves performance by caching executable statements that are used repeatedly.
<b>INTERACT_PROD_DSN_NAME</b>	The <code>dbname</code> of the respective database.
<b>INTERACT_TEST_DATABASE_HOST</b>	Host system details of the system hosting the Interact Test database.
<b>INTERACT_TEST_DATABASE_PORT</b>	Port number of the Interact Test database.
<b>INTERACT_TEST_DATABASE_NAME</b>	Username to access the Interact Test database.
<b>INTERACT_TEST_DATABASE_USERNAME</b>	Password to access the Interact Test database.
<b>INTERACT_TEST_DATABASE_PASSWORD</b>	Name of the Interact Test database.
<b>INTERACT_TEST_DS_INITIAL_SIZE</b>	The initial size of the Interact Test datasource connection pool.
<b>INTERACT_TEST_DS_MIN_IDLE</b>	The minimum number of idle connections (not connected to a database) in the Interact Test datasource connection pool.

**Table 33. Server-related database parameters of Interact (continued)**

Parameter name	Parameter description
<b>INTERACT_TEST_DS_MAX_IDLE</b>	The maximum number of idle connections (not connected to a database) in the Interact Test datasource connection pool. Any idle connections, which exceeds the configured value, will be removed from the pool.
<b>INTERACT_TEST_DS_MAX_TOTAL</b>	The maximum number of connections that the Interact Test datasource can hold. If the number of connection requests exceed the configured value, the connection will be refused.
<b>INTERACT_TEST_DS_STATEMENT_CACHE_SIZE</b>	Maximum number of statements that can be cached in the Interact Test datasource. Statement caching improves performance by caching executable statements that are used repeatedly.
<b>INTERACT_TEST_DSN_NAME</b>	The <code>dbname</code> of the respective database.
<b>INTERACT_LEARNING_DATABASE_HOST</b>	Host system details of the system hosting the Interact Learning database.
<b>INTERACT_LEARNING_DATABASE_PORT</b>	Port number of the Interact Learning database.
<b>INTERACT_LEARNING_DATABASE_NAME</b>	Username to access the Interact Learning database.
<b>INTERACT_LEARNING_DATABASE_USERNAME</b>	Password to access the Interact Learning database.
<b>INTERACT_LEARNING_DATABASE_PASSWORD</b>	Name of the Interact Learning database.
<b>INTERACT_LEARNING_DS_INITIAL_SIZE</b>	The initial size of the Interact Learning datasource connection pool.
<b>INTERACT_LEARNING_DS_MIN_IDLE</b>	The minimum number of idle connections (not connected to a database) in the Interact Learning datasource connection pool.
<b>INTERACT_LEARNING_DS_MAX_IDLE</b>	The maximum number of idle connections (not connected to a database) in the Interact Learning datasource connection pool. Any idle connections, which exceeds the configured value, will be removed from the pool.
<b>INTERACT_LEARNING_DS_MAX_TOTAL</b>	The maximum number of connections that the Interact Learning datasource can hold. If the number of connection requests exceed the configured value, the connection will be refused.
<b>INTERACT_LEARNING_DS_STATEMENT_CACHE_SIZE</b>	Maximum number of statements that can be cached in the Interact Learning datasource. Statement caching improves

Table 33. Server-related database parameters of Interact (continued)

Parameter name	Parameter description
	performance by caching executable statements that are used repeatedly.
<b>INTERACT_CHRH_DATABASE_HOST</b>	Host system details of the system hosting the Interact CHRH database.
<b>INTERACT_CHRH_DATABASE_PORT</b>	Port number of the Interact CHRH database.
<b>INTERACT_CHRH_DATABASE_NAME</b>	Username to access the Interact CHRH database.
<b>INTERACT_CHRH_DATABASE_USERNAME</b>	Password to access the Interact CHRH database.
<b>INTERACT_CHRH_DATABASE_PASSWORD</b>	Name of the Interact CHRH database.
<b>INTERACT_CHRH_DS_INITIAL_SIZE</b>	The initial size of the Interact CHRH datasource connection pool.
<b>INTERACT_CHRH_DS_MIN_IDLE</b>	The minimum number of idle connections (not connected to a database) in the Interact CHRH datasource connection pool.
<b>INTERACT_CHRH_DS_MAX_IDLE</b>	The maximum number of idle connections (not connected to a database) in the Interact CHRH datasource connection pool. Any idle connections, which exceeds the configured value, will be removed from the pool.
<b>INTERACT_CHRH_DS_MAX_TOTAL</b>	The maximum number of connections that the Interact CHRH datasource can hold. If the number of connection requests exceed the configured value, the connection will be refused.
<b>INTERACT_CHRH_DS_STATEMENT_CACHE_SIZE</b>	Maximum number of statements that can be cached in the Interact CHRH datasource. Statement caching improves performance by caching executable statements that are used repeatedly.
<b>INTERACT05_DATABASE_HOST</b>	Host system details of the system hosting the Interact05 database.
<b>INTERACT05_DATABASE_PORT</b>	Port number of the Interact05 database.
<b>INTERACT05_DATABASE_NAME</b>	Username to access the Interact05 database.
<b>INTERACT05_DATABASE_USERNAME</b>	Password to access the Interact05 database.
<b>INTERACT05_DATABASE_PASSWORD</b>	Name of the Interact05 database.
<b>INTERACT05_DS_INITIAL_SIZE</b>	The initial size of the Interact05 datasource connection pool.

**Table 33. Server-related database parameters of Interact (continued)**

Parameter name	Parameter description
INTERACT05_DS_MIN_IDLE	The minimum number of idle connections (not connected to a database) in the Interact05 datasource connection pool.
INTERACT05_DS_MAX_IDLE	The maximum number of idle connections (not connected to a database) in the Interact05 datasource connection pool. Any idle connections, which exceeds the configured value, will be removed from the pool.
INTERACT05_DS_MAX_TOTAL	The maximum number of connections that the Interact05 datasource can hold. If the number of connection requests exceed the configured value, the connection will be refused.
INTERACT05_DS_STATEMENT_CACHE_SIZE	Maximum number of statements that can be cached in the Interact05 datasource. Statement caching improves performance by caching executable statements that are used repeatedly.

**Table 34. Application server-related parameters of Interact**

Parameter name	Parameter description
INT_HOST_NAME	The system host name of Interact.
INT_MANAGEMENT_PORT	The management port number for the Interact system.
INT_MANAGEMENT_HTTPS_PORT	The management <code>HTTPS</code> port number for the Interact system.
INT_AJP_PORT	The <code>AJP</code> port number for the Interact system.
INT_HTTP_PORT	The <code>HTTP</code> port number for the Interact system.
INT_HTTPS_PORT	The <code>HTTPS</code> port number for the Interact system.
INT_RECOVERY_ENV_PORT	The recovery environment port number of the Interact system.
INT_STATUS_MANAGER_PORT	The status manager port number of the Interact system.
INT_MIN_HEAP	The maximum heap size allocated for Interact.
INT_MAX_HEAP	The maximum heap size allocated for Interact.

**Installation parameters for Interact**

Parameter name	Parameter description
INTERACT_INSTALL_COMMAND1	Parameters used for Installation commands and scripts that can be used for customization.

Parameter name	Parameter description
INTERACT_INSTALL_COMMAND2	
INTERACT_INSTALL_COMMAND3	
INTERACT_INSTALL_COMMAND4	
INTERACT_INSTALL_COMMAND5	
INTERACT_INSTALL_COMMAND6	
INTERACT_INSTALL_COMMAND7	
INTERACT_INSTALL_COMMAND8	
INTERACT_INSTALL_COMMAND9	
INTERACT_INSTALL_COMMAND10	
INTERACT_INSTALL_SCRIPT1	
INTERACT_INSTALL_SCRIPT2	

## InteractDT configurations

To configure Interact DT for Cloud Native Unica, make the necessary modifications to the `interactDT-configMap.yaml` file.

To access the `interactDT-configMap.yaml` file, navigate to `/unica/templates/` in the Unica charts folder. Open the file and make modifications to the following parameters:

**Table 35. Common parameters of InteractDT configuration**

Parameter name	Parameter description
INTERACTDT_PRODUCT_NAME	The name assigned for InteractDT.
INTERACTDT_WAR_NAME	The name of the <code>WAR</code> file.
INTERACTDT_APPLICATION_NAME	The name of the main application. For example, <code>Unica</code> .
INTERACTDT_DOMAIN_USERNAME	The domain username for InteractDT.
INTERACTDT_DOMAIN_PASSWORD	The domain password for InteractDT.
WAR_SCRIPT_INTERACTDT	The path where the <code>WAR</code> execution script exists.
PRODUCT_OPTS_INTERACTDT	Product-specific options for InteractDT.

**Table 36. Database-related parameters of Campaign**

Parameter name	Parameter description
<b>CAMPAIGN_JNDI_NAME</b>	JNDI name for Campaign.
<b>CAMPAIGN_POOL_NAME</b>	Pool name for Campaign.
<b>CAMPAIGN_DATA_SOURCE_PARAMETERS</b>	Parameters related to Campaign Data Source. Add multiple parameters using ; as the delimiter between parameters.
<b>CAMPAIGN_DATABASE_HOST</b>	Host system details of the system hosting the Campaign database.
<b>CAMPAIGN_DATABASE_PORT</b>	Port number of the Campaign database.
<b>CAMPAIGN_DATABASE_NAME</b>	Name of the Campaign database.
<b>CAMPAIGN_DATABASE_USERNAME</b>	Username to access the Campaign database.
<b>CAMPAIGN_DATABASE_PASSWORD</b>	Password to access the Campaign database.
<b>CAMPAIGN_DSN_NAME</b>	Name of the Campaign DSN.
<b>CAMPAIGN_DS_INITIAL_SIZE</b>	The initial size of the Campaign datasource connection pool.
<b>CAMPAIGN_DS_MIN_IDLE</b>	The minimum number of idle connections (not connected to a database) in the Campaign datasource connection pool.
<b>CAMPAIGN_DS_MAX_IDLE</b>	The maximum number of idle connections (not connected to a database) in the Campaign datasource connection pool. Any idle connections, which exceeds the configured value, will be removed from the pool.
<b>CAMPAIGN_DS_MAX_TOTAL</b>	The maximum number of connections that the Campaign datasource can hold. If the number of connection requests exceed the configured value, the connection will be refused.
<b>CAMPAIGN_DS_STATEMENT_CACHE_SIZE</b>	Maximum number of statements that can be cached in the Campaign datasource. Statement caching improves performance by caching executable statements that are used repeatedly.

**Table 37. Application Server-related parameters for InteractDT**

Parameter name	Parameter description
<b>INTERACTDT_URL</b>	The URL to access InteractDT.
<b>INTERACTDT_HOST_NAME</b>	The system host name of InteractDT.
<b>INTERACTDT_MANAGEMENT_PORT</b>	The management port number for the InteractDT system.

**Table 37. Application Server-related parameters for InteractDT (continued)**

Parameter name	Parameter description
<b>INTERACTDT_MANAGEMENT_HTTPS_PORT</b>	The management HTTPS port number for the InteractDT system.
<b>INTERACTDT_AJP_PORT</b>	The AJP port number for the InteractDT system.
<b>INTERACTDT_HTTP_PORT</b>	The HTTP port number for the InteractDT system.
<b>INTERACTDT_HTTPS_PORT</b>	The HTTPS port number for the InteractDT system.
<b>INTERACTDT_RECOVERY_ENV_PORT</b>	The recovery environment port number of the InteractDT system.
<b>INTERACTDT_STATUS_MANAGER_PORT</b>	The status manager port number of the InteractDT system.
<b>INTERACTDT_MIN_HEAP</b>	The maximum heap size allocated for InteractDT.
<b>INTERACTDT_MAX_HEAP</b>	The maximum heap size allocated for InteractDT.

**Table 38. Interact DT upgrade-related parameters**

<b>IS_INTERACTDT_DDLs_EXECUTED</b>	Parameter to indicate if Interact DDLs is executed. Valid values are <code>TRUE</code> or <code>FALSE</code> .
------------------------------------	--

## Journey configurations

To configure the Journey server for Cloud Native Unica, make the necessary modifications to the `journey-configMap.yaml` file.

To access the `journey-configMap.yaml` file, navigate to `/unica/templates/` in the Unica charts folder. Open the file and make modifications to the following parameters:

**Table 39. Common parameters of Journey**

Parameter name	Parameter description
<b>JOURNEY_HOST_NAME</b>	The system host name of Journey.
<b>JOURNEY_MANAGEMENT_PORT</b>	The management port number for the Journey system.
<b>JOURNEY_MANAGEMENT_HTTPS_PORT</b>	The management <code>HTTPS</code> port number for the Journey system.
<b>JOURNEY_AJP_PORT</b>	The <code>AJP</code> port number for the Journey system.
<b>JOURNEY_HTTP_PORT</b>	The <code>HTTP</code> port number for the Journey system.
<b>JOURNEY_HTTPS_PORT</b>	The <code>HTTPS</code> port number for the Journey system.

**Table 39. Common parameters of Journey (continued)**

Parameter name	Parameter description
JOURNEY_RECOVERY_ENV_PORT	The recovery environment port number of the Journey system.
JOURNEY_STATUS_MANAGER_PORT	The status manager port number of the Journey system.
JOURNEY_MIN_HEAP	The maximum heap size allocated for Journey. For example, 1024m.
JOURNEY_MAX_HEAP	The maximum heap size allocated for Journey. For example, 6614m.
MIN_ENGINE_MEMORY	<b>Example:</b> "1g"
MAX_ENGINE_MEMORY	<b>Example:</b> "3g"
DB_TYPE_JOURNEY	The name of the database used by the Journey system. For example, Oracle.
DB_DRIVER_CLASS_JOURNEY	The class name of the Journey Database drivers. For example <code>oracle.jdbc.OracleDriver</code> .
JOURNEYREPORT_DB_NAME	The database name of the server hosting the Journey Reports. For example, <code>journeyuser</code> .

**Multicast parameters for Journey**

KAFKA_BROKER	<b>Example:</b> "kafka-0.kafka.default.svc.cluster.local:9092"
REPLICATION_COUNT	"1"
JOURNEY_MULTICAST_IP	<b>Example:</b> "{{ .Values.journeyMultiCastData.JOURNEY_MULTICAST_IP }}"
JOURNEY_MULTICAST_PORT	<b>Example:</b> "{{ .Values.journeyMultiCastData.JOURNEY_MULTICAST_PORT }}"

**Installation parameters for Journey**

Parameter name	Parameter description
JOURNEY_INSTALL_COMMAND1	Parameters used for Installation commands and scripts that can be used for customization.
JOURNEY_INSTALL_COMMAND2	
JOURNEY_INSTALL_COMMAND3	



Parameter name	Parameter description
JOURNEY_INSTALL_COMMAND4	
JOURNEY_INSTALL_COMMAND5	
JOURNEY_INSTALL_COMMAND6	
JOURNEY_INSTALL_COMMAND7	
JOURNEY_INSTALL_COMMAND8	
JOURNEY_INSTALL_COMMAND9	
JOURNEY_INSTALL_COMMAND10	
JOURNEY_INSTALL_SCRIPT1	
JOURNEY_INSTALL_SCRIPT2	

## Journey web configurations

To configure the Journey web server for Cloud Native Unica, make the necessary modifications to the `journeyweb-configMap.yaml` file.

To access the `journeyweb-configMap.yaml` file, navigate to `/unica/templates/` in the Unica charts folder. Open the file and make modifications to the following parameters:

**Table 40. Common parameters of Journey web configuration**

Parameter name	Parameter description
JOURNEYWEB_JNDI_NAME	JNDI name for Journey web.
JOURNEYWEB_POOL_NAME	Pool name for Journey web.
PRODUCT_OPTS_PLATFORM	Product-specific options for Journey web.
JOURNEYWEB_PRODUCT_NAME	The name assigned for Journey web.
JOURNEYWEB_WAR_NAME	The name of the <code>WAR</code> file.
JOURNEYWEB_APPLICATION_NAME	The name of the main application. For example, <code>Unica</code> .
JOURNEYWEB_DOMAIN_USERNAME	The domain username for Journey web.
JOURNEYWEB_DOMAIN_PASSWORD	The domain password for Journey web.

**Table 41. Database parameters of Journey web configuration**

Parameter name	Parameter description
JOURNEYWEB_DATABASE_HOST	Host system details of the system hosting the Journey web database.
JOURNEYWEB_DATABASE_PORT	Port number of the Journey web database.
JOURNEYWEB_DATABASE_USERNAME	Username to access the Journey web database.
JOURNEYWEB_DATABASE_PASSWORD	Password to access the Journey web database.
JOURNEYWEB_DATABASE_NAME	Name of the Journey web database.
JOURNEYWEB_DS_INITIAL_SIZE	The initial size of the Journey web datasource connection pool.
JOURNEYWEB_DS_MIN_IDLE	The minimum number of idle connections (not connected to a database) in the Journey web datasource connection pool.
JOURNEYWEB_DS_MAX_IDLE	The maximum number of idle connections (not connected to a database) in the Journey web datasource connection pool. Any idle connections, which exceeds the configured value, will be removed from the pool.
JOURNEYWEB_DS_MAX_TOTAL	The maximum number of connections that the Journey web datasource can hold. If the number of connection requests exceed the configured value, the connection will be refused.
JOURNEYWEB_DS_STATEMENT_CACHE_SIZE	Maximum number of statements that can be cached in the Journey web datasource. Statement caching improves performance by caching executable statements that are used repeatedly.

**Table 42. Application server parameters of Journey web configuration**

Parameter name	Parameter description
JOURNEYWEB_URL	The URL to access Journey web.
JOURNEYWEB_HOST_NAME	The system host name of Journey web.
JOURNEYWEB_MANAGEMENT_PORT	The management port number for the Journey web system.
JOURNEYWEB_MANAGEMENT_HTTPS_PORT	The management <b>HTTPS</b> port number for the Journey web system.
JOURNEYWEB_AJP_PORT	The <b>AJP</b> port number for the Journey web system.
JOURNEYWEB_HTTP_PORT	The <b>HTTP</b> port number for the Journey web system.
JOURNEYWEB_HTTPS_PORT	The <b>HTTPS</b> port number for the Journey web system.

Table 42. Application server parameters of Journey web configuration (continued)

Parameter name	Parameter description
JOURNEYWEB_RECOVERY_ENV_PORT	The recovery environment port number of the Journey web system.
JOURNEYWEB_STATUS_MANAGER_PORT	The status manager port number of the Journey web system.
JOURNEYWEB_MIN_HEAP	The maximum heap size allocated for Journey web.
JOURNEYWEB_MAX_HEAP	The maximum heap size allocated for Journey web.

Table 43. Apache Tomcat server-specific parameters of Journey web configuration

Parameter name	Parameter description
TOMCAT_INSTALLER_TARGZ	The name of the Apache Tomcat installer <code>TARGZ</code> file.
TOMCAT_INSTALLER_UNZIP_DIRNAME	The location to extract the Apache Tomcat installer <code>TARGZ</code> file.
TOMCAT_INSTALL_LOCATION	The location to install Apache Tomcat.
TOMCAT_INSTALL_CHECK_LOCATION	
FORCE_INIT_TOMCAT	Set whether you want to force initialize Apache Tomcat. <code>TRUE</code> to activate for initialization and <code>FALSE</code> to deactivate force initialization.
TOMCAT_SHUTDOWN_PORT	The <code>TCP/IP</code> port number of the Apache Tomcat server waiting for a shutdown command.
TOMCAT_MAX_EXECUTOR_THREADS	The maximum number of threads (based on the <code>maxThreads</code> property of Apache Tomcat) used for <code>HTTP</code> connections.
TOMCAT_MIN_EXECUTOR_THREADS	The minimum number of threads (based on the <code>minSpareThreads</code> property of Apache Tomcat) that is always present in the thread pool.
TOMCAT_REDIRECT_PORT	The redirect port number ( <code>redirectPort</code> property) of the Apache Tomcat server handling SSL connections.

Table 44. Other parameters of Journey web configuration

Parameter name	Parameter description
JOURNEYWEB_IP_FINDER_LIST	
JOURNEYWEB_MULTICAST_GROUP	
JOURNEYWEB_MULTICAST_PORT	

**Table 44. Other parameters of Journey web configuration (continued)**

Parameter name	Parameter description
JOURNEYWEB_MULTICAST_ENABLED	
JOURNEYWEB_DEFAULT_DATA_REGION_MAX_SIZE	
JOURNEYWEB_GOAL_MAX_SIZE_ALLOWED	

**Table 45. Configuration of Journey report parameters**

Parameter name	Parameter description
JOURNEYREPORT_DATABASE_NAME	Name of the Journey report database.
JOURNEY_REPORT_DATABASE_USERNAME	Username to access the Journey report database.
JOURNEY_REPORT_DATABASE_PASSWORD	Password to access the Journey report database.
JOURNEYREPORT_DS_INITIAL_SIZE	The initial size of the Journey report datasource connection pool.
JOURNEYREPORT_DS_MIN_IDLE	The minimum number of idle connections (not connected to a database) in the Journey report datasource connection pool.
JOURNEYREPORT_DS_MAX_IDLE	The maximum number of idle connections (not connected to a database) in the Journey report datasource connection pool. Any idle connections, which exceeds the configured value, will be removed from the pool.
JOURNEYREPORT_DS_MAX_TOTAL	The maximum number of connections that the Journey report datasource can hold. If the number of connection requests exceed the configured value, the connection will be refused.
JOURNEYREPORT_DS_STATEMENT_CACHE_SIZE	Maximum number of statements that can be cached in the Journey report datasource. Statement caching improves performance by caching executable statements that are used repeatedly.
JOURNEYREPORT_JNDI_NAME	JNDI name for Journey report.
JOURNEYREPORT_POOL_NAME	Pool name for Journey report.
JOURNEYREPORT_DB_NAME	The database name of the server hosting the Journey Reports. For example, <code>journeyuser</code> .

## Multicast parameters for Journey web configuration

<b>JOURNEY_MULTICAST_IP</b>	<b>Example:</b> " <code>{{ .Values.journeyMultiCastData.JOURNEY_MULTICAST_IP }}</code> "
<b>JOURNEY_MULTICAST_PORT</b>	<b>Example:</b> " <code>{{ .Values.journeyMultiCastData.JOURNEY_MULTICAST_PORT }}</code> "

## Installation parameters for Journey web configuration

Parameter name	Parameter description
<b>JOURNEYWEB_INSTALL_COMMAND1</b>	Parameters used for Installation commands and scripts that can be used for customization.
<b>JOURNEYWEB_INSTALL_COMMAND2</b>	
<b>JOURNEYWEB_INSTALL_COMMAND3</b>	
<b>JOURNEYWEB_INSTALL_COMMAND4</b>	
<b>JOURNEYWEB_INSTALL_COMMAND5</b>	
<b>JOURNEYWEB_INSTALL_COMMAND6</b>	
<b>JOURNEYWEB_INSTALL_COMMAND7</b>	
<b>JOURNEYWEB_INSTALL_COMMAND8</b>	
<b>JOURNEYWEB_INSTALL_COMMAND9</b>	
<b>JOURNEYWEB_INSTALL_COMMAND10</b>	
<b>JOURNEYWEB_INSTALL_SCRIPT1</b>	
<b>JOURNEYWEB_INSTALL_SCRIPT2</b>	

## Kafka configurations

To configure the Kafka server for Journey, make the necessary modifications to the `kafka-configMap.yaml` file.

To access the `kafka-configMap.yaml` file, navigate to `/unica/templates/` in the Unica charts folder. Open the file and make modifications to the following parameters:

**Table 46. Database-parameters of Kafka configuration**

Parameter name	Parameter description
JOURNEY_DATABASE_HOST	Host system details of the system hosting the Journey database.
JOURNEY_DATABASE_PORT	Port number of the Journey database.
JOURNEY_DATABASE_USERNAME	Username to access the Journey database.
JOURNEY_DATABASE_PASSWORD	Password to access the Journey database.
JOURNEY_DATABASE_NAME	Name of the Journey database.

**Table 47. Common parameters of Kafka configuration**

Parameter name	Parameter description
KAFKA_SERVER	The details of the system hosting the Kafka server.
KAFKA_HOST_NAME	The host name of the Kafka server. In case of multiple hosts, specify the value as follows: <pre>host1:port,host2:port,host3:port,...host&lt;n&gt;</pre> Do not add port number for the last host.
KAFKA_PORT	The port number to access the Kafka server.
JOURNEY_HOST_NAME	The host name of the Journey server.
JOURNEY_PORT	The port number to access the Journey server.
ZOOKEEPER_PORT	

## Plan configurations

To configure Plan for Cloud Native Unica, make the necessary modifications to the `plan-configMap.yaml` file.

To access the `plan-configMap.yaml` file, navigate to `/unica/templates/` in the Unica charts folder. Open the file and make modifications to the following parameters:

**Table 48. Common parameters of Plan**

Parameter name	Parameter description
PRODUCT_OPTS_PLAN	Product specific options for Plan.
PLAN_JNDI_NAME	JNDI name for Plan.
PLAN_POOL_NAME	Pool name for Plan.
PLAN_PRODUCT_NAME	The name assigned for Plan.

Table 48. Common parameters of Plan (continued)

Parameter name	Parameter description
PLAN_WAR_NAME	The name of the <code>WAR</code> file.
PLAN_APPLICATION_NAME	The name of the main application. For example, <code>Unica</code> .
PLAN_DOMAIN_USERNAME	The domain username for Plan.
PLAN_DOMAIN_PASSWORD	The domain password for Plan.

Table 49. Application server-related parameters of Plan

Parameter name	Parameter description
PLAN_HOST_NAME	The system host name of Plan.
PLAN_MANAGEMENT_PORT	The management port number for the Plan system.
PLAN_MANAGEMENT_HTTPS_PORT	The management <code>HTTPS</code> port number for the Plan system.
PLAN_AJP_PORT	The <code>AJP</code> port number for the Plan system.
PLAN_HTTP_PORT	The <code>HTTP</code> port number for the Plan system.
PLAN_HTTPS_PORT	The <code>HTTPS</code> port number for the Plan system.
PLAN_RECOVERY_ENV_PORT	The recovery environment port number of the Plan system.
PLAN_STATUS_MANAGER_PORT	The status manager port number of the Plan system.
PLAN_MIN_HEAP	The minimum heap size allocated for Plan.
PLAN_MAX_HEAP	The maximum heap size allocated for Plan.
PLAN_URL	The URL to access Plan.

Table 50. Database-related parameters for Plan

Parameter name	Parameter description
PLAN_PORT	The port number to access the Plan system.
PLAN_HOST	The host name of the Plan system.
DB_PLAN	The database name for Plan.
DB_PLAN_HOST	The host details of the database in the Plan system.
DB_PLAN_PORT	The database port number of the Plan system.
DB_PLAN_HOST_NAME	Host name of the system hosting the Plan database.
PLAN_DATABASE_HOST	Host system details of the system hosting the Plan database.

**Table 50. Database-related parameters for Plan (continued)**

Parameter name	Parameter description
PLAN_DATABASE_PORT	Port number of the Plan database.
PLAN_DATABASE_NAME	Name of the Plan database.
PLAN_DATABASE_USERNAME	Username to access the Plan database.
PLAN_DATABASE_PASSWORD	Password to access the Plan database.
PLAN_DS_INITIAL_SIZE	The initial size of the Plan datasource connection pool.
PLAN_DS_MIN_IDLE	The minimum number of idle connections (not connected to a database) in the Plan datasource connection pool.
PLAN_DS_MAX_IDLE	The maximum number of idle connections (not connected to a database) in the Plan datasource connection pool. Any idle connections, which exceeds the configured value, will be removed from the pool.
PLAN_DS_MAX_TOTAL	The maximum number of connections that the Plan datasource can hold. If the number of connection requests exceed the configured value, the connection will be refused.
PLAN_DS_STATEMENT_CACHE_SIZE	Maximum number of statements that can be cached in the Plan datasource. Statement caching improves performance by caching executable statements that are used repeatedly.

**Installation parameters for Plan**

Parameter name	Parameter description
PLAN_INSTALL_COMMAND1	Parameters used for Installation commands and scripts that can be used for customization.
PLAN_INSTALL_COMMAND2	
PLAN_INSTALL_COMMAND3	
PLAN_INSTALL_COMMAND4	
PLAN_INSTALL_COMMAND5	
PLAN_INSTALL_COMMAND6	
PLAN_INSTALL_COMMAND7	
PLAN_INSTALL_COMMAND8	
PLAN_INSTALL_COMMAND9	



Parameter name	Parameter description
PLAN_INSTALL_COMMAND10	
PLAN_INSTALL_SCRIPT1	
PLAN_INSTALL_SCRIPT2	

## Platform configurations

To configure Platform for Cloud Native Unica, make the necessary modifications to the `platform-configMap.yaml` file.

To access the `platform-configMap.yaml` file, navigate to `/unica/templates/` in the Unica charts folder. Open the file and make modifications to the following parameters:

**Table 51. Common parameters of Platform**

Parameter name	Parameter description
PLATFORM_JNDI_NAME	JNDI name for Platform.
PLATFORM_POOL_NAME	Pool name for Platform.
PRODUCT_OPTS_BASE	Base options for all products of Unica.
PRODUCT_OPTS_PLATFORM	Product specific options for Platform.
FORCE_INIT_WEBLOGIC	Set whether you want to force initialize WebLogic. <code>TRUE</code> to activate for initialization and <code>FALSE</code> to deactivate force initialization.
JAVA_HOME_WEBLOGIC	Location of Java Home on your system.
PLATFORM_PRODUCT_NAME	The name assigned for Platform.
PLATFORM_WAR_NAME	The name of the <code>WAR</code> file.
PLATFORM_APPLICATION_NAME	The name of the main application. For example, <code>Unica</code> .
PLATFORM_DOMAIN_USERNAME	The domain username for Platform.
PLATFORM_DOMAIN_PASSWORD	The domain password for Platform.
REPLACE_ADMIN_USR_NAME	
REPLACE_ADMIN_USR_PASSWORD	

**Table 52. Database-related parameters of Platform**

Parameter name	Parameter description
PLATFORM_DATABASE_HOST	Host system details of the system hosting the Platform database.

**Table 52. Database-related parameters of Platform (continued)**

Parameter name	Parameter description
PLATFORM_DATABASE_PORT	Port number of the Platform database.
PLATFORM_DATABASE_USERNAME	Username to access the Platform database.
PLATFORM_DATABASE_PASSWORD	Password to access the Platform database.
PLATFORM_DATABASE_NAME	Name of the Platform database.
DB_PLAT	The database name for Platform.
PLATFORM_DS_INITIAL_SIZE	The initial size of the Platform datasource connection pool.
PLATFORM_DS_MIN_IDLE	The minimum number of idle connections (not connected to a database) in the Platform datasource connection pool.
PLATFORM_DS_MAX_IDLE	The maximum number of idle connections (not connected to a database) in the Platform datasource connection pool. Any idle connections, which exceeds the configured value, will be removed from the pool.
PLATFORM_DS_MAX_TOTAL	The maximum number of connections that the Platform datasource can hold. If the number of connection requests exceed the configured value, the connection will be refused.
PLATFORM_DS_STATEMENT_CACHE_SIZE	Maximum number of statements that can be cached in the Platform datasource. Statement caching improves performance by caching executable statements that are used repeatedly.

**Table 53. Application server-related parameters of Platform**

Parameter name	Parameter description
MANAGER_URL	The URL to access Manager.
PLAT_HOST_NAME	The system host name of Platform.
PLAT_MANAGEMENT_PORT	The management port number for the Platform system.
PLAT_MANAGEMENT_HTTPS_PORT	The management <code>HTTPS</code> port number for the Platform system.
PLAT_AJP_PORT	The <code>AJP</code> port number for the Platform system.
PLAT_HTTP_PORT	The <code>HTTP</code> port number for the Platform system.
PLAT_HTTPS_PORT	The <code>HTTPS</code> port number for the Platform system.

Table 53. Application server-related parameters of Platform (continued)

Parameter name	Parameter description
PLAT_RECOVERY_ENV_PORT	The recovery environment port number of the Platform system.
PLAT_STATUS_MANAGER_PORT	The status manager port number of the Platform system.
PLAT_MIN_HEAP	The minimum heap size allocated for Platform.
PLAT_MAX_HEAP	The maximum heap size allocated for Platform.

Table 54. Apache Tomcat-specific parameters

Parameter name	Parameter description
TOMCAT_INSTALLER_TARGZ	The name of the Apache Tomcat installer <code>TARGZ</code> file.
TOMCAT_INSTALLER_UNZIP_DIRNAME	The location to extract the Apache Tomcat installer <code>TARGZ</code> file.
TOMCAT_INSTALL_LOCATION	The location to install Apache Tomcat.
FORCE_INIT_TOMCAT	Set whether you want to force initialize Apache Tomcat. <code>TRUE</code> to activate for initialization and <code>FALSE</code> to deactivate force initialization.
TOMCAT_SHUTDOWN_PORT	The <code>TCP/IP</code> port number of the Apache Tomcat server waiting for a shutdown command.
TOMCAT_MAX_EXECUTOR_THREADS	The maximum number of threads (based on the <code>maxThreads</code> property of Apache Tomcat) used for <code>HTTP</code> connections.
TOMCAT_MIN_EXECUTOR_THREADS	The minimum number of threads (based on the <code>minSpareThreads</code> property of Apache Tomcat) that is always present in the thread pool.
TOMCAT_REDIRECT_PORT	The redirect port number ( <code>redirectPort</code> property) of the Apache Tomcat server handling <code>SSL</code> connections.

### Installation parameters for Platform

Parameter name	Parameter description
PLATFORM_INSTALL_COMMAND1	Parameters used for Installation commands and scripts that can be used for customization.
PLATFORM_INSTALL_COMMAND2	
PLATFORM_INSTALL_COMMAND3	
PLATFORM_INSTALL_COMMAND4	

Parameter name	Parameter description
PLATFORM_INSTALL_COMMAND5	
PLATFORM_INSTALL_COMMAND6	
PLATFORM_INSTALL_COMMAND7	
PLATFORM_INSTALL_COMMAND8	
PLATFORM_INSTALL_COMMAND9	
PLATFORM_INSTALL_COMMAND10	
PLATFORM_INSTALL_SCRIPT1	
PLATFORM_INSTALL_SCRIPT2	

## RTP configurations

Helm chart configuration for RTP are as follows:

### Update values-local.yaml

In the values-local.yaml file, within the port configuration, define the ports for RTP backend and UI services.

```
port:
  rtp: 9001
  rtpui: 3000
```

Here:

- **rtp** is the port for the RTP backend service.
- **rtpui** is the port for the RTP user interface service.

### Update common-configMap.yaml

Append the RTP in existing MODE property configuration to the unica/templates/common-configMap.yaml file.

```
Example:
MODE: "PLT_CMP_INT_RTP"
```

The **MODE** variable sets the operational mode for Unica to enable RTP functionality.

### Update unica-ingress.yaml

Modify the unica/templates/unica-ingress.yaml file to include the following paths for routing requests to the RTP backend and UI services:

```
- path: /rtp/servlet
  pathType: Prefix
  backend:
```

```

service:
  name: {{ include "unica.fullname" . }}-rtp
  port:
    number: {{ .Values.service.port.rtp }}

- path: /rtp/api
  pathType: Prefix
  backend:
    service:
      name: {{ include "unica.fullname" . }}-rtp
      port:
        number: {{ .Values.service.port.rtp }}

- path: /rtp
  pathType: Prefix
  backend:
    service:
      name: {{ include "unica.fullname" . }}-rtptui
      port:
        number: {{ .Values.service.port.rtptui }}

```

Here:

- `/rtp/servlet` and `/rtp/api` are the route requests to the RTP backend service.
- `/rtp` is the route request to the RTP user interface service.

## Segment Central configurations

To configure Segment Central for Cloud Native Unica, make the necessary modifications to the `segmentcentral-configMap.yaml` file.

To access the `segmentcentral-configMap.yaml` file, navigate to `/unica/templates/` in the Unica charts folder. Open the file and make modifications to the following parameters:

**Table 55. Common parameters for Segment Central**

Parameter name	Parameter description
<code>SEGMENTCENTRAL_PRODUCT_NAME</code>	<code>Segmentcentral</code>
<code>SEGMENT_CENTRAL_WAR_NAME</code>	<code>SegmentCentral.war</code>
<code>SEGMENTCENTRAL_APPLICATION_NAME</code>	<code>segmentcentral</code>
<code>SEGMENTCENTRAL_DOMAIN_USERNAME</code>	<code>root</code>
<code>SEGMENTCENTRAL_DOMAIN_PASSWORD</code>	<code>unica*03</code>
<code>SEGMENTATIONENGINE_PRODUCT_NAME</code>	<code>Segmentationengine</code>
<code>SEGMENTATION_ENGINE_WAR_NAME</code>	<code>SegmentationEngine.war</code>
<code>SEGMENTATIONENGINE_APPLICATION_NAME</code>	<code>segmentationengine</code>
<code>SEGMENTATIONENGINE_DOMAIN_USERNAME</code>	<code>root</code>

**Table 55. Common parameters for Segment Central (continued)**

Parameter name	Parameter description
SEGMENTATIONENGINE_DOMAIN_PASSWORD	unica*03

**Table 56. Application Server-related parameters for Segment Central**

Parameter name	Parameter description
SEGMENTCENTRAL_HOST_NAME	{{ .Release.Name }}-unica-segmentcentral
SEGMENTCENTRAL_MANAGEMENT_PORT	9066
SEGMENTCENTRAL_MANAGEMENT_HTTPS_PORT	9995
SEGMENTCENTRAL_AJP_PORT	8010
SEGMENTCENTRAL_HTTP_PORT	9140
SEGMENTCENTRAL_HTTPS_PORT	9446
SEGMENTCENTRAL_RECOVERY_ENV_PORT	4714
SEGMENTCENTRAL_STATUS_MANAGER_PORT	4715
SEGMENTCENTRAL_MIN_HEAP	1024m
SEGMENTCENTRAL_MAX_HEAP	2048m
SEGMENTCENTRAL_URL	{{ include ip.protocol . }}://{{ .Values.service.hostname }}/SegmentCentral
SEGMENTCENTRAL_INTERNAL_URL	http://{{ .Release.Name }}-unica-segmentcentral:9140/SegmentCentral
PRODUCT_OPTS_SEGMENTCENTRAL	-DSEGMENT_CENTRAL_HOME=/docker/unica/SegmentCentral/ -DENABLE_NON_PROD_MODE=true

**Table 57. Application Server-related parameters for Segment Central Engine**

Parameter name	Parameter description
SEGMENTATIONENGINE_HOST_NAME	{{ .Release.Name }}-unica-segmentationengine
SEGMENTATIONENGINE_MANAGEMENT_PORT	9067
SEGMENTATIONENGINE_MANAGEMENT_HTTPS_PORT	9996
SEGMENTATIONENGINE_AJP_PORT	8011
SEGMENTATIONENGINE_HTTP_PORT	9141
SEGMENTATIONENGINE_HTTPS_PORT	9447

Table 57. Application Server-related parameters for Segment Central Engine (continued)

Parameter name	Parameter description
SEGMENTATIONENGINE_RECOVERY_ENV_PORT	4715
SEGMENTATIONENGINE_STATUS_MANAGER_PORT	4716
SEGMENTATIONENGINE_MIN_HEAP	1024m
SEGMENTATIONENGINE_MAX_HEAP	2048m
SEGMENTATIONENGINE_INTERNAL_URL	http://{{ .Release.Name }}-unica-segmentationengine:9141/SegmentationEngine
PRODUCT_OPTS_SEGMENTATIONENGINE	-DSEGMENT_CENTRAL_HOME=/docker/unica/SegmentCentral/ -DENABLE_NON_PROD_MODE=true

Table 58. Database-related parameters for Segment Central

Parameter name	Parameter description
SEGMENTCENTRAL_USER_JNDI_NAME	{{ .Values.segmentcentralData.segmentcentralConfigMapData.SEGMENTCENTRAL_USER_JNDI_NAME }}
SEGMENTCENTRAL_USER_POOL_NAME	{{ .Values.segmentcentralData.segmentcentralConfigMapData.SEGMENTCENTRAL_USER_POOL_NAME }}
SEGMENTCENTRAL_USER_DATABASE_HOST	{{ .Values.segmentcentralData.segmentcentralConfigMapData.SEGMENTCENTRAL_USER_DATABASE_HOST }}
SEGMENTCENTRAL_USER_DATABASE_PORT	{{ .Values.segmentcentralData.segmentcentralConfigMapData.SEGMENTCENTRAL_USER_DATABASE_PORT }}
SEGMENTCENTRAL_USER_DATABASE_NAME	{{ .Values.segmentcentralData.segmentcentralConfigMapData.SEGMENTCENTRAL_USER_DATABASE_NAME }}
SEGMENTCENTRAL_USER_DATABASE_USERNAME	{{ .Values.segmentcentralData.segmentcentralConfigMapData.SEGMENTCENTRAL_USER_DATABASE_USERNAME }}
SEGMENTCENTRAL_USER_DATABASE_PASSWORD	{{ .Values.segmentcentralData.segmentcentralConfigMapData.SEGMENTCENTRAL_USER_DATABASE_PASSWORD }}
SEGMENTCENTRAL_USER_DS_INITIAL_SIZE	{{ .Values.segmentcentralData.segmentcentralDSMData.SEGMENTCENTRAL_USER_DS_INITIAL_SIZE }}
SEGMENTCENTRAL_USER_DS_MIN_IDLE	{{ .Values.segmentcentralData.segmentcentralDSMData.SEGMENTCENTRAL_USER_DS_MIN_IDLE }}
SEGMENTCENTRAL_USER_DS_MAX_IDLE	{{ .Values.segmentcentralData.segmentcentralDSMData.SEGMENTCENTRAL_USER_DS_MAX_IDLE }}

**Table 58. Database-related parameters for Segment Central (continued)**

Parameter name	Parameter description
SEGMENTCENTRAL_USER_DS_MAX_TOTAL	{{ .Values.segmentcentralData.segmentcentralDSMData.SEGMENTCENTRAL_USER_DS_MAX_TOTAL }}
SEGMENTCENTRAL_USER_DS_STATEMENT_CACHE_SIZE	{{ .Values.segmentcentralData.segmentcentralDSMData.SEGMENTCENTRAL_USER_DS_STATEMENT_CACHE_SIZE }}
SEGMENTCENTRAL_USER_DATA_SOURCE_PARAMETERS	{{ .Values.segmentcentralData.segmentcentralDSMData.SEGMENTCENTRAL_USER_DATA_SOURCE_PARAMETERS }}

**Table 59. Database-related parameters for Segment Central Engine**

Parameter name	Parameter description
SEGMENTATIONENGINE_USER_POOL_NAME	{{ .Values.segmentationengineData.segmentationengineConfigMapData.SEGMENTATIONENGINE_USER_POOL_NAME }}
SEGMENTATIONENGINE_USER_DATABASE_HOST	{{ .Values.segmentationengineData.segmentationengineConfigMapData.SEGMENTATIONENGINE_USER_DATABASE_HOST }}
SEGMENTATIONENGINE_USER_DATABASE_PORT	{{ .Values.segmentationengineData.segmentationengineConfigMapData.SEGMENTATIONENGINE_USER_DATABASE_PORT }}
SEGMENTATIONENGINE_USER_DATABASE_NAME	{{ .Values.segmentationengineData.segmentationengineConfigMapData.SEGMENTATIONENGINE_USER_DATABASE_NAME }}
SEGMENTATIONENGINE_USER_DATABASE_USERNAME	{{ .Values.segmentationengineData.segmentationengineConfigMapData.SEGMENTATIONENGINE_USER_DATABASE_USERNAME }}
SEGMENTATIONENGINE_USER_DATABASE_PASSWORD	{{ .Values.segmentationengineData.segmentationengineConfigMapData.SEGMENTATIONENGINE_USER_DATABASE_PASSWORD }}
SEGMENTATIONENGINE_USER_DS_INITIAL_SIZE	{{ .Values.segmentationengineData.segmentationengineDSMData.SEGMENTATIONENGINE_USER_DS_INITIAL_SIZE }}
SEGMENTATIONENGINE_USER_DS_MIN_IDLE	{{ .Values.segmentationengineData.segmentationengineDSMData.SEGMENTATIONENGINE_USER_DS_MIN_IDLE }}
SEGMENTATIONENGINE_USER_DS_MAX_IDLE	{{ .Values.segmentationengineData.segmentationengineDSMData.SEGMENTATIONENGINE_USER_DS_MAX_IDLE }}
SEGMENTATIONENGINE_USER_DS_MAX_TOTAL	{{ .Values.segmentationengineData.segmentationengineDSMData.SEGMENTATIONENGINE_USER_DS_MAX_TOTAL }}
SEGMENTATIONENGINE_USER_DS_STATEMENT_CACHE_SIZE	{{ .Values.segmentationengineData.segmentationengineDSMData.SEGMENTATIONENGINE_USER_DS_STATEMENT_CACHE_SIZE }}
SEGMENTATIONENGINE_USER_DATA_SOURCE_PARAMETERS	{{ .Values.segmentationengineData.segmentationengineDSMData.SEGMENTATIONENGINE_USER_DATA_SOURCE_PARAMETERS }}



## Installation parameters for Segment Central

Parameter name	Parameter description
SEGMENTCENTRAL_INSTALL_COMMAND1	Parameters used for Installation commands and scripts that can be used for customization.
SEGMENTCENTRAL_INSTALL_COMMAND2	
SEGMENTCENTRAL_INSTALL_COMMAND3	
SEGMENTCENTRAL_INSTALL_COMMAND4	
SEGMENTCENTRAL_INSTALL_COMMAND5	
SEGMENTCENTRAL_INSTALL_COMMAND6	
SEGMENTCENTRAL_INSTALL_COMMAND7	
SEGMENTCENTRAL_INSTALL_COMMAND8	
SEGMENTCENTRAL_INSTALL_COMMAND9	
SEGMENTCENTRAL_INSTALL_COMMAND10	
SEGMENTCENTRAL_INSTALL_SCRIPT1	
SEGMENTCENTRAL_INSTALL_SCRIPT2	

## Sub-chart configuration in Helm charts

To run a database container as a sub-chart, the database must reside within the cluster. Sub-charts have their own `configMap` for configurations.



**Note:** Cloud Native Unica does not own the database.

## values.yaml driven configurations

1. Database and Data source memory related parameters can be configured in `values.yaml` and Product `configmap.yaml` files as shown in the following examples:

- **Values file example:**

```
campaignData:
  campaignConfigMapData:
    CAMPAIGN_DATABASE_HOST: "hcl-unica-suite-database"
    CAMPAIGN_DATABASE_PORT: "9088"
    CAMPAIGN_DATABASE_NAME: "campuser:ONEDB_SERVER=onedb"
    CAMPAIGN_DATABASE_USERNAME: "onedbsa"
    CAMPAIGN_DATABASE_PASSWORD: "onedb4ever"
    CAMPAIGN_DSN_NAME: "campuser"
  campaignDSMData:
```

```

CAMPAIGN_DS_INITIAL_SIZE: "1"
CAMPAIGN_DS_MIN_IDLE: "1"
CAMPAIGN_DS_MAX_IDLE: "1"
CAMPAIGN_DS_MAX_TOTAL: "80"
CAMPAIGN_DS_STATEMENT_CACHE_SIZE: "180"
CAMPAIGN_DATA_SOURCE_PARAMETERS:
"removeAbandonedTimeout='300';removeAbandoned='true';testOnBorrow='true'"

```

◦ **Reflected in Campaign configmap file:**

```

CAMPAIGN_DATABASE_HOST: "{{ .Values.campaignData.campaignConfigMapData.CAMPAIGN_DATABASE_HOST }}"
CAMPAIGN_DATABASE_PORT:
"{{ .Values.campaignData.campaignConfigMapData.CAMPAIGN_DATABASE_PORT }}"
CAMPAIGN_DATABASE_NAME:
"{{ .Values.campaignData.campaignConfigMapData.CAMPAIGN_DATABASE_NAME }}"
CAMPAIGN_DATABASE_USERNAME:
"{{ .Values.campaignData.campaignConfigMapData.CAMPAIGN_DATABASE_USERNAME }}"
CAMPAIGN_DATABASE_PASSWORD:
"{{ .Values.campaignData.campaignConfigMapData.CAMPAIGN_DATABASE_PASSWORD }}"
CAMPAIGN_DSN_NAME: "{{ .Values.campaignData.campaignConfigMapData.CAMPAIGN_DSN_NAME }}"

CAMPAIGN_DS_INITIAL_SIZE: "{{ .Values.campaignData.campaignDSMData.CAMPAIGN_DS_INITIAL_SIZE }}"
CAMPAIGN_DS_MIN_IDLE: "{{ .Values.campaignData.campaignDSMData.CAMPAIGN_DS_MIN_IDLE }}"
CAMPAIGN_DS_MAX_IDLE: "{{ .Values.campaignData.campaignDSMData.CAMPAIGN_DS_MAX_IDLE }}"
CAMPAIGN_DS_MAX_TOTAL: "{{ .Values.campaignData.campaignDSMData.CAMPAIGN_DS_MAX_TOTAL }}"
CAMPAIGN_DS_STATEMENT_CACHE_SIZE:
"{{ .Values.campaignData.campaignDSMData.CAMPAIGN_DS_STATEMENT_CACHE_SIZE }}"

```

2. Parameters categorization: Each product is separately defined by a tag in the `values.yaml` file and subtag is provided for Data type: database or data source memory.

◦ **Example: Data type categorisation (Database and Data source memory)**

```

campaignData:
  campaignConfigMapData:
    CAMPAIGN_DATABASE_HOST: "hcl-unica-suite-database"
    CAMPAIGN_DATABASE_PORT: "9088"
    CAMPAIGN_DATABASE_NAME: "campuser:ONEDB_SERVER=onedb"
    CAMPAIGN_DATABASE_USERNAME: "onedbsa"
    CAMPAIGN_DATABASE_PASSWORD: "onedb4ever"
    CAMPAIGN_DSN_NAME: "campuser"
  campaignDSMData:
    CAMPAIGN_DS_INITIAL_SIZE: "1"
    CAMPAIGN_DS_MIN_IDLE: "1"
    CAMPAIGN_DS_MAX_IDLE: "1"
    CAMPAIGN_DS_MAX_TOTAL: "80"
    CAMPAIGN_DS_STATEMENT_CACHE_SIZE: "180"
    CAMPAIGN_DATA_SOURCE_PARAMETERS:
"removeAbandonedTimeout='300';removeAbandoned='true';testOnBorrow='true'"

```

◦ **Example: Product wise categorisation**

```

collaborateData:
  collaborateConfigMapData:
    COLLABORATE_DATABASE_HOST: "hcl-unica-suite-database"
    COLLABORATE_DATABASE_PORT: "9088"
    COLLABORATE_DATABASE_NAME: "platuser"
    COLLABORATE_DATABASE_USERNAME: "informix"
    COLLABORATE_DATABASE_PASSWORD: "in4mix"

```

```

collaborateDSMData:
  COLLABORATE_DS_INITIAL_SIZE: "1"
  COLLABORATE_DS_MIN_IDLE: "1"
  COLLABORATE_DS_MAX_IDLE: "1"
  COLLABORATE_DS_MAX_TOTAL: "80"
  COLLABORATE_DS_STATEMENT_CACHE_SIZE: "180"
  COLLABORATE_DATA_SOURCE_PARAMETERS:
    "removeAbandonedTimeout='300';removeAbandoned='true';testOnBorrow='true'"

contactcentralData:
  contactcentralConfigMapData:
    CONTACTCENTRAL_DATABASE_HOST: "hcl-unica-suite-database"
    CONTACTCENTRAL_DATABASE_PORT: "9088"
    CONTACTCENTRAL_DATABASE_USERNAME: "onedbsa"
    CONTACTCENTRAL_DATABASE_PASSWORD: "onedb4ever"
    CONTACTCENTRAL_DATABASE_NAME: "platuser:ONEDB_SERVER=onedb"
  contactcentralDSMData:
    CONTACTCENTRAL_DS_INITIAL_SIZE: "1"
    CONTACTCENTRAL_DS_MIN_IDLE: "1"
    CONTACTCENTRAL_DS_MAX_IDLE: "1"
    CONTACTCENTRAL_DS_MAX_TOTAL: "80"
    CONTACTCENTRAL_DS_STATEMENT_CACHE_SIZE: "180"
    CONTACTCENTRAL_DATA_SOURCE_PARAMETERS:
      "removeAbandonedTimeout='300';removeAbandoned='true';testOnBorrow='true'"

```

### 3. `JAVA_HOME` is set in `values.yaml`.

- `JAVA_HOME`, `DOCKER_HOME`, `JRE_HOME`, `DIRECTOR_JAVA_HOME` parameters have same value assigned in common configmap files.

```

DOCKER_JAVA_HOME: "{{ .Values.commonConfigMapMiscData.JAVA_HOME }}"
DIRECTOR_JAVA_HOME: "{{ .Values.commonConfigMapMiscData.JAVA_HOME }}"
JRE_HOME: "{{ .Values.commonConfigMapMiscData.JAVA_HOME }}"
JavaHOME: "{{ .Values.commonConfigMapMiscData.JAVA_HOME }}"

```

- `JAVA_HOME`: `docker/unica/jre` is defined in values file and used in the `common_configmap.yaml` file. If you have installed JRE in a custom path, set `JAVA_HOME` to `<Custom-JRE-Path>`. For example, if the custom JRE installation path is `/docker/unica/JdbcDrivers/jre`, replace `<Custom-JRE-Path>` by `/docker/unica/JdbcDrivers/jre`.

### 4. Ingress updates with version 1.22:

- For k8s 1.22 version API updates have been made to RBAC and INGRESS files also ingress structure is changed as per K8S update.
- **Example old ingress:**

```

rules:
  - host: {{ .Values.service.hostname }}
    http:
      paths:
        - path: /Insights
          backend:
            serviceName: {{ include "unica.fullname" . }}-insights
            servicePort: {{ .Values.service.port.insights }}

```

- **Example new ingress:**

```
rules:
- host: {{ .Values.service.hostname }}
  http:
    paths:
    - path: /Insights
      pathType: Prefix
      backend:
        service:
          name: {{ include "unica.fullname" . }}-insights
          port:
            number: {{ .Values.service.port.insights }}
```